



Features

Video System

- ATI ES1000 Graphics Card

Capacity

- 1000 IP Extensions
- 48 Analog Extensions
- 48 Analog Lines
- 24 ISDN BRI Lines
- 120 ISDN PRI Lines
- 200-400 Concurrent Calls

Processor(s)

- 2x Intel Xeon E5405 Quad-Core 2.00GHz

Memory

- Error Detection
- 8GB Installed/Max Memory

System Control and Indicators

- NIC 1 Activity
- NIC 2 Activity
- Power Switch
- HDD Status LED
- Power LED
- System Status LED
- Reset button
- Alarm Reset button
- Overheat

Operating System

- Gentoo Linux

I/O Ports

- 1x PS/2 keyboard & Mouse
- 1x Serial port(s)
- 2x USB port(s)
- 1x Parallel port(s)

Motherboard

- 1333MHz System Bus
- Intel® 5000P (Blackford) Chipset

Storage

- 8x 160GB Western Digital RE (3.0Gb/s, 7.2Krpm, 16MB Cache) SATA Hot-Swap
- 16X DVD IDE (Black) Optical Drive
- 1x DVD IDE 16x

- 1x 1.44MB Floppy

Ethernet Ports(s)

- 2x 1000Mbps Ethernet Port(s)

Regulatory & Safety

- FCC, CE Regulatory & Safety Certification

Chassis

- 2x Full Length PCIe8, 1x Full Length PCIe4, 3x Full Length PCIe1
- Floor or Rack Mounting

Physical & Environment

- 8% to 90% Relative Humidity
- -40°C to 60°C Storage Temperature
- 10°C to 35°C Operating Temperature
- 178 mm (H) x 437 mm (W) x 648 mm (D) Dimensions
- Rack Form Factor
- Black face, plated metal body Colour(s)

Certified Software

- Server and Network SERVERware Edition(s)
- Business, Call Centre and Multi Tenant PBXware Edition(s)

Photo Gallery

MaxiRACK

- Front
- Back

Contact Details

Bicom Systems
511 E San Ysidro Blvd #103
San Ysidro
California
92173
United States

Tel: 1-619-760-7777

E-mail:
sales@bicomsystems.com