Yealink T22P IP Phone (SIP-T22P)



Product Name: Yealink T22P IP Phone (SIP-T22P)
Manufacturer: -
Model Number: SIP-T22P

Yealink T22P IP Phone (SIP-T22P)

Please Note: The Yealink T22P has been discontinued. For an alternative, we recommend the Yealink T23G IP Phone (SIP-T23G).

The Yealink T22P is an Enterprise HD VoIP Phone that features a TI TITAN chipset, TI voice engine, 132x64 graphic LCD, 3 VoIP accounts and 32 keys including 4 soft keys. The T22P is an ideal solution for offices looking for an effective but affordable IP Phone.
Yealink T22P IP Phone Key Features

ï¿½ Supports 3 SIP Accounts
ï¿½ Blue Backlit LCD Display 132x64
ï¿½ 3 Programmable Keys
ï¿½ 2 Indication LED's
ï¿½ Power over Ethernet POE
ï¿½ 3 Way Conference Calls
ï¿½ Speakerphone
ï¿½ Personal Ringtones and Voicemail.
ï¿½ Call Hold, Waiting and Transfer.
ï¿½ Wall mountable

Note: Please refer to the Yealink VoIP Phone Range Detailed Comparison Table for more information.
Yealink T22P Technical Specifications
Phone Features

ï¿½ 3 VoIP accounts, Hotline, Emergency call
ï¿½ Call hold, call waiting, call forward & call return
ï¿½ Call transfer (blind/semi-attended/attended)
ï¿½ Caller ID display, Redial, Mute, DND
ï¿½ Auto-answer; 3-way conferencing
ï¿½ Direct IP call without SIP proxy
ï¿½ Speed dial, SMS, Voicemail
ï¿½ Message Waiting Indication (MWI) LED
ï¿½ Tone scheme, volume control
ï¿½ Soft keys programmable
ï¿½ Ring tone selection/import/delete
ï¿½ Phonebook (300 entries), Black list
ï¿½ Call history: dialed/received/missed/forwarded
ï¿½ Menu-driven user interface
ï¿½ Localised language and input method

Advanced Features

ï¿½ XML phonebook search & import
ï¿½ XML Browser
ï¿½ LDAP phonebook

VoIP PBX System Integration

Yealink T22P IP Phone (SIP-T22P)

ï¿½ Busy lamp field (BLF); BLF list
ï¿½ Bridged line appearance (BLA)
ï¿½ Intercom, Paging, Music on hold
ï¿½ DND & Forward synchronisation
ï¿½ Call park, call pickup
ï¿½ Call recording, call completion
ï¿½ Group listening, group pickup
ï¿½ Anonymous call, anonymous call rejection
ï¿½ Network conference
ï¿½ Dial Plan, Dial-now
ï¿½ Distinctive ringtone

Voice Features & Codecs

ï¿½ Wideband codec: G.722
ï¿½ Narrowband codec: G.711µ/A, G.723.1
ï¿½ G.726, G.729AB
ï¿½ Full-duplex speakerphone with AEC
ï¿½ VAD, CNG, AEC, PLC, AJB, AGC

Network Features

ï¿½ SIP v1 (RFC2543) & v2 (RFC3261)
ï¿½ DNS SRV (RFC3263)
ï¿½ NAT Traversal: STUN mode
ï¿½ Redundant server support
ï¿½ DTMF: In-Band, RFC2833, SIP Info
ï¿½ Proxy mode and peer-to-peer SIP link mode
ï¿½ IP Assignment: Static/DHCP/PPPoE
ï¿½ Bridge/router mode for PC port
ï¿½ Telnet/HTTP/HTTPS server
ï¿½ TFTP/DHCP/PPPoE client
ï¿½ DNS client, NAT/DHCP server
ï¿½ Logout

Phone Management

ï¿½ Auto-provision via FTP/TFTP/HTTP/HTTPS
ï¿½ Auto-provision with PnP
ï¿½ Configuration: browser/phone/auto-provision
ï¿½ SNMP V1/2 optional, TR069 optional
ï¿½ Factory configuration customised
ï¿½ Trace package & system log export

Phone Security

ï¿½ 802.1x, VLAN QoS (802.1pq)
ï¿½ Transport Layer Security (TLS)
ï¿½ HTTPS (server/client), SRTP (RFC3711)
ï¿½ Secure configuration file via AES encryption
ï¿½ Digest authentication using MD5/MD5-sess
ï¿½ Phone lock for personal privacy protection
ï¿½ Admin/VAR/User three-level configuration mode

Yealink T22P IP Phone (SIP-T22P)

Connectivity

Physical Specification

ï¿½ 132 x 64 graphic LCD
ï¿½ TI TITAN chipset
ï¿½ 32 keys including 4 soft keys
ï¿½ 5 LEDs: 1 x power, 3 x line, 1 x message
ï¿½ 2 x RJ45 10/100M Ethernet ports
ï¿½ 1 x RJ9 handset port
ï¿½ 1 x RJ9 headset port
ï¿½ Power adapter: AC 100~240V input and DC 5V/1.2A Output (Optional)
ï¿½ Power over Ethernet (IEEE 802.3af)
ï¿½ Power consumption: 1.4-2.6W
ï¿½ Net weight: 0.77kg
ï¿½ Dimension: 185 x 200 x 90mm
ï¿½ Operating humidity: 10~95%
ï¿½ Storage temperature: up to 60°C
ï¿½ Wall-mountable

Yealink T22P Standards Certifications

Please Enquire

Options available for Yealink T22P IP Phone (SIP-T22P) :

Power Supply Required?

UK PSU required (+£3.99), EU PSU required (+£3.99), None - Using PoE.