Snom MeetingPoint Conference Phone



Product Name: Snom MeetingPoint Conference Phone
Manufacturer: Snom
Model Number: MP

Snom MeetingPoint Conference Phone (MEETINGPOINT)
The Snom MeetingPoint is the perfect solution for anybody who makes frequent cross-location consultations. The Snom MeetingPoint is the only SIP conference phone that allows you to use Microsoft Office Communication Server 2007 R2 and Standard SIP accounts in one conference phone.
Snom MeetingPoint Key Features

ï¿½ Full duplex broadband sound technology
ï¿½ 3-way conference calls
ï¿½ Recording range up to 30 m² room area or 10 participants
ï¿½ Simultaneous access to internal and external telephone books (LDAP)
ï¿½ Connection for add-on microphones for a larger recording range
ï¿½ Multiple SIP registrations

With the Snom MeetingPoint, you are able to allow for a total of four parties to participate in the phone conference from different locations all over the world. This helps minimise time wasting and cuts costs. The Snom MeetingPoint is perfect for use in medium to large conference rooms. As result of the reliable suppression of disturbing background noise and its excellent sound quality you can hold your telephone conferences in large groups of up to 10 persons without affecting the intelligibility of the call.
Snom MeetingPoint Technical Specifications
Features

ï¿½ Omnisound Full duplex wideband sound technology
ï¿½ Management of up to 4 external participants
ï¿½ Recording range up to 30M or 10 participants
ï¿½ Simultaneous management of internal and external telephone listings (LDAP)
ï¿½ Connection type for add-on microphones for a alarger reception range
ï¿½ Microsoft Office Communication Server 2007 R2 ready
ï¿½ Multiple SIP registrations
ï¿½ OpenVPN

General Features

ï¿½ Size: Diameter: 240mm, Height: 77mm
ï¿½ Display: Backrground-lit graphical LCD, 128x64 pixels
ï¿½ Weight: 1kg
ï¿½ Colour: black
ï¿½ Keypad: Alphaneumeric 0-9, *, #, dial, hang up, mute, increase volume, menu, conference, recording, volume control, 5 keys for navigation in the menu system
ï¿½ Microphone: Circular (360) recording characteristics
ï¿½ Reception range: up to 30m2, <10 persons
ï¿½ Speaker: Frequency range: 150-15000 Hz playback
ï¿½ Volume: 90db SPI 0.5m. Equaliser function
ï¿½ Anti-theft protection: Kensington security slot

Connections

ï¿½ Network connection: 1x RJ-45, PoE 10/100MBit
ï¿½ Power Supply: Power adapter 100-240 VAC/14 V DC - PoE

Snom MeetingPoint Conference Phone

ï¿½ Add-on microphones: modular 4/4 possible

Surrounding Conditions

ï¿½ Temperature: 5°-40°C.
ï¿½ Air Humidity: 20 - 80%
ï¿½ Suggested acoustic room conditions
ï¿½ Reverberation time: 0.5 S Rt 60
ï¿½ Background noise: 45 dbA

Permissions

ï¿½ Telecoms: TBR21, 47 CFR part 68/ TIA, IC CS-03 Issue 1999/01/01
ï¿½ EMC: EN301 489-1,3. EN 300 220-1,2, FC subpart B and C.
ï¿½ Electrical safety class: UL 60950-1, EN 60950-1:200

Price: £673.20