



Product Name: Linksys SPA962 IP Phone

Manufacturer: -

Model Number: SPA-962-C

Availability: Discontinued

Please note that the Linksys SPA962 has been discontinued. We recommend the Cisco

SPA504G as a good alternative.

A Highly Functional Business VoIP Phone.

The SPA962 VoIP Phone is a must for businesses using a Hosted IP telephony Service, an IP PBX, or a large scale IP Centrex deployment. The SPA-962 utilizes Industry Leading VoIP Technology from Linksys to deliver a high quality IP Phone that is unparalleled in features, value, and support.

Up to Six Configurable Phone Lines!

Some of the many features on the SPA962 include six active lines, dual switched Ethernet ports, 802.3af PoE support and a high resolution colour display. Each line can be independently configured to use a unique phone number (or extension), or can be configured to use a shared number that is assigned to multiple phones.

Interoperable

The SPA962 has been tested to ensure comprehensive interoperability with equipment in a VoIP infrastructure. With hundreds of features and configurable service parameters, the SPA962 addresses the requirements of traditional business whilst utilizing the advantages of IP Telephony. Technical Data

Key features continued:

- آزار On-Hook Dialing
- � Call Pick Up Selective and Group
- � Call Park and UnPark
- � Call Swap
- � Call Back on Busy
- تز½ Call Blocking Anonymous and Selective
- i¿½ Do Not Disturb (callers hear line busy tone)
- آز½ URI (IP) Dialing Support (Vanity Numbers)
- آزا 2 On Hook Default Audio Configuration (Speaker phone and Headset)
- ī¿½ Multiple Ring Tones with Selectable Ring Tone per Line
- تزن Called Number with Directory Name Matching
- า๊¿½ Call Number using Name Directory Matching or via Caller ID
- าั¿½ Subsequent Incoming Calls with Calling Name and Number
- ī¿½ Date and Time with Intelligent Daylight Savings Support
- าั¿½ Call Duration and Start Time Stored in Call Logs
- � Call Timer
- า๊¿½ Call Forwarding Unconditional, No Answer, On Busy
- 17.1/2 Hot Line and Warm Line Automatic Calling
- ī¿1/2 Call Logs (60 entries each): Made, Answered, and Missed Calls
- � Redial from Call Logs
- � Personal Directory with Auto-dial (100 entries)
- آذِ Name and Identity (Text) Displayed at Start Up
- រ៉េ្ស Distinctive Ringing Based on Calling and Called Number
- าั¿½ Ten User Downloadable Ring Tones Ring Tone Generator Free from www.linksys.com
- ï¿⅓ Speed Dialling
- าั¿½ Configurable Dial/Numbering Plan Support per Line
- � Intercom **
- ï¿⅓ Group Paging **
- ī¿½ DNS SRV and Multiple A Records for Proxy Lookup and Proxy Redundancy
- � Syslog, Debug, Report Generation, and Event Logging



- ī¿1/2 Secure Call Encrypted Voice Communication Support SIP over TLS, and SRTP
- าั¿½ Built-in Web Server for Administration and Configuration with Multiple Security Levels
- าั¿½ Automated Provisioning, Multiple Methods. Up to 256 Bit Encryption: (HTTP, HTTPS, TFTP)
- آذِيًّ Optionally Require Admin Password to Reset Unit to factory Defaults ** Feature requires support by SIP server

Hardware:

- าั¿½ 320 x 240 True colour, Four inch, Liquid Crystal Display (LCD)
- ī సైస్త Four Illuminated Call Appearance Line buttons with tricolour LED's
- ī సై LED Indicates Line State Active, Idle, On-Hold, Unregistered
- آذًا Line LED Configurable to 13 Different States (On/off, Colour, Flash)
- آذِ 1/2 Dedicated Illuminated buttons for -
- � Audio Mute On/off
- ï¿1/2 Headset On/Off
- ï¿1/2 Speaker phone On/Off
- ï¿⅓ Four Soft Key Buttons
- าั¿½ Four way Rocking Directional Knob for Menu Navigation
- � Support for up to two attendant Consoles; adds up to 64 programmable buttons
- า๊¿½ Voice Mail Message Waiting Indicator Light
- � Voice Mail retrieval button
- � Dedicated Hold
- រី¿½ Settings button for Access to Feature, Set-up, and configuration Menus
- ī¿½ Volume Control Rocking Up/Down Controls Handset, speaker, Ringer
- ï¿1/2 Standard 12-Button Dialling Pad
- ï¿⅓ Headset Jack 2.5 millimetre
- � LED Test Function
- آذِا Two Ethernet LAN Ports with Integrated Ethernet Switch 100BaseT RJ-45
- آز½ 802.3af Compliant Power over Ethernet (PoE)
- าั¿½ Optional 5 volt DC Universal (100-240 Volt) (ORDERED SEPARATELY)
- � Regulatory Compliance & Decurity:
- آزر FCC, CE, Class B Canadian ICES-003, A-Tick Certification
- تَىٰ Password Protected System, pre-set to factory default
- ī సై Password Protected Access to Administrator and User level Features
- า๊¿½ HTTPS with Factory Installed Client Certificate
- าั¿½ HTTP Digest Encrypted Authentication via MD5 (RFC 1321)
- ï¿⅓ Up to 256-bit Encryption

Documentation:

- 17.1/2 Quick-Start Installation and Configuration Guide
- ï¿⅓ User Guide

Administration Guide Package contents:

- تز½ 1 SPA-962 IP Phone, Handset and Stand
- � 1 Handset Cord
- ï¿1/2 1 RJ45 Ethernet Cable
- � 1 Quick installation Guide

Environmental:

- � Dimensions: 8" x 7.63" x 7.50" (203 x 194 x 191 mm) W x H x D
- � Unit weight: 2.4lbs (1.088 kg)
- � Operating Temp: 41?~113?F (5?~45?C)



ϊ¿½ Storage Temp: 10~90% Non-Condensing ϊ¿½ Storage Temp: 10-90% Non-Condensing
Linksys SPA Series VoIP Phone (SIP) Comparison Table
SPA Model
Voice Lines
Ethernet Ports
High Resolution Display
Power Over Ethernet
Mains Power Supply
SPA901
1
1
N
N
Υ
SPA921



1				
1				
Y				
N				
Υ				
SP	A922			
1				
2				
Υ				
Y				
N				
SP	A941			
2-4	1			
1				
Υ				
N				
Υ				



SPA942		
2-4		
2		
Υ		
Υ		
N		
SPA962		
6		
2		
Y Colour		
Υ		
N		
Please Enquire		

Options available for Linksys SPA962 IP Phone:

Power Supply Unit

Default - UK 5V Power Supply Unit (PSU) (+£10.00), - Not Required -.