

Yealink CP860 VoIP Conference Phone



Product Name: Yealink CP860 VoIP Conference Phone

Manufacturer: -

Model Number: CP860

Please Note: This product is no longer available. Please see alternative products in our Yealink VoIP Conference Phone section.

Yealink CP860 VoIP Conference Phone

The Yealink CP860 IP conference phone is a perfect choice for small and medium-sized conference room and can meet the demands of up to 16 people with optional expansion microphones. The CP860 provides many important audio features including optima HD technology, a built-in 3 microphone array, full-duplex technology, and acoustic echo canceling. Yealink CP860 Features

- Optima HD voice, full duplex technology
- 10-feet and 360-degree voice pickup
- Optional expansion microphones for wider reception
- 320ms echo cancellation tail length
- Connect to a mobile phone or PC for conference calls
- 5-way conferencing support

Users can enjoy rich, clear, and life-like conference calls. The Yealink CP860 also supports call recording, plus linkages to mobile phones or PCs for a more convenient conference call experience. Professional, Sleek Design The sleek, diamond-like shape of the CP860 provides the very best user experience, whilst fitting seamlessly into any professional environment. HD Sound Quality Support for Optima HD allows the CP860 to provide excellent HD sound quality. With a built-in three microphone matrix, the phone also supports 360° omnidirectional high-quality sound pickup within a 3 meter radius. This can be extended to 5 meters using the Yealink CPE80 microphones – perfect for small and medium-sized conference rooms. Yealink CP860 Technical Specifications

Audio Features

- Optima HD voice
- 10-foot (3-meter) microphone pickup, can be applied to medium-sized conference room
- Built in 3-microphone array, 360 degree voice pickup
- 112 mm diameter and 2.7w speaker
- Full-duplex speakerphone with AEC
- Echo cancellation tail length is up to 320ms
- Background noise suppression
- Codecs: G.722, G.711(Aµ), G.729AB, iLBC
- DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
- VAD, CNG, PLC, AJB, AGC

Phone Features

- 1 VoIP account
- Call hold, mute, DND
- Call recording, hotline
- 5-way conferencing calls
- Redial, call waiting, emergency call
- Call forward, call transfer, call return, dial plan
- Ring tone selection/import/delete
- Set date time manually or automatically

Yealink CP860 VoIP Conference Phone

• Volume adjustment

Directory

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Black list

IP-PBX Features

- Intercom, multicast paging
- Anonymous call, anonymous call rejection
- Voice mail, distinctive ringtone, call pickup

Display

- 192x64-pixel graphical LCD with backlight
- 24 total keys: 4 softkey, off-hook key, on-hook key, redial, mute, volume key, 3 navigation keys
- Phone lock
- National language selection
- Caller ID with name, number
- LCD display logo

Interface

- 1xRJ45 10/100M Ethernet port
- Power over Ethernet (IEEE 802.3af), class 0
- 2xEX mic port
- 1xUSB2.0 port
- 1xmobile phone/PC port: 3.5mm
- 1xSecurity lock port

Network & Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server redundancy supported
- IPv4/IPv6
- NAT transverse: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronisation using SNTP
- UDP/TCP/DNS-SRV(RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice encryption
- Transport Layer Security (TLS)
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- OpenVPN, IEEE802.1X

Yealink CP860 VoIP Conference Phone

Management

- Setup wizard
- Configuration: browser/phone/auto-provision
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069, SNMP
- Reset to factory, reboot
- Package tracing export, system log

Other Physical Features

- 4 context-sensitive "soft" keys
- External universal AC adapter (optional): AC 100~240V input and DC 5V/2A Output
- Power consumption (PSU): 2.8-5.6W
- Power consumption (PoE): 3.9-8.1W
- Dimension(W*D*H): 320mm*260m*52mm
- Operating humidity: 10~95%
- Storage temperature: -10~50°C

Package Features

- Yealink CP860 IP conference phone
- Ethernet Cable
- Mobile Device Cable (3.5mm Jack)
- Quick Start Guide
- Power Adapter
- Qty/CTN: 5PCS
- N.W/CTN: 8.9KG
- G.W/CTN: 9.9KG
- Giftbox size: 334mm x 365mm x 96mm
- Carton size: 500mm x 379mm x 342mm

Please Enquire

Options available for Yealink CP860 VoIP Conference Phone :

Power Supply Required?

EU PSU required (+£3.99), None - Using PoE, UK PSU required (+£3.99).