

Gigaset Hybird 120 IP PBX



Product Name: Gigaset Hybird 120 IP PBX Manufacturer: -Model Number: Hybird120IPBX

Please Note: The Hybird 120 has been discontinued. For alternatives, we recommend taking a look at the Gigaset IP PBX range.

Gigaset Hybird 120 IP PBX

The Gigaset Hybird 120 IP PBX is a powerful telephone system that offers many advance features with maximum flexibility. Up to 20 users can be registered with the system and multiple telephone calls can be made in parallel. Gigaset Hybird 120 IP PBX Features

ï¿1/2 Up to 10 users (expandable to 20 users)

- $i_{2}^{1/2}$ Up to 2 parallel external calls (expandable to 7 calls)
- i¿½ Up to 7 voicemail boxes (expandable to 17 voicemail boxes)
- i¿1/2 Telephony system, IP based with ISDN and traditional analogue
- ï¿¹/₂ Configuration via webbrowser – custom user portal
- ï¿¹/₂ Manage calls, voicemail, direction, conferences via browser
- ï¿1/₂ Fanless design
- ï¿1/2 Fax server, voicemail with IVR, auto attendant
- ï¿¹/₂ CTI for data transfer between phone and PC
- ï¿1/2 Supports Windows platforms
- ï¿1/2 Free internal calls and uniform phone numbers
- i¿1/2 SD memory card for storing announcements, messages, fees, etc.
- ï¿1/2 Compatible with all Gigaset pro products
- ï¿1/2 2 year warranty

The Hybird is compatible with all Gigaset pro DECT and desktop phones offering users with a wide variety of choice and flexibility. With the Hybird 120 Gigaset Edition you get everything a small or mid-sized business may need. What's in the box

 Hybird 120 IP PBX 4GB SD card Cat5e cable RJ11 - RJ11 cable 3 x screws and rawlplugs PSU Installation Guide Declaration of conformity

Technical Specification Performance Data

ï¿1/2 RAM - 64 MB ï¿1/2 Hard drive - Flash memory ROM, 16 MB

General Information

i¿½ Maximum concurrent connections - 10 i¿½ Maximum concurrent conference - Up to 8 three-party conference calls for TDM terminals i¿½ Maximum user - 20



Gigaset Hybird 120 IP PBX

Hardware

ï¿1/2 Weight - 0.86 kg (without packaging and accessories)

- ï¿1/2 Dimensions (H x W x D in mm) 305 x 218 x 41 mm
- ï¿1/2 Available colors white/red
- ï¿¹/₂ Case wall mountable
- ï¿1/2 Wallmount optional yes
- ï¿1/2 Power supply 100~240V AC: separate wall power supply
- ï¿1/2 Power consumption idle: 12W / in use: 21.5W

Interfaces

i¿½ 10/100/1000 Mbps Ethernet Ports - 4 i¿½ FXS / FXO / ISDN2 - 4/1/2 (PtP, PtMP) and UP0 i¿½ Voice over IP (SIP) - yes i¿½ USB (Front) for disaster recovery - 1

VOIP Lines

� SIP-Provider - 25 � SIP-Trunking - yes, 2 (7 max. with one licence)

Basic IP features

i¿1/2 Number of parallel calls: VoIP and fixed-line - 9 (G.711) i¿1/2 VoIP accounts - 2 i¿1/2 Integrated router - yes

Please Enquire

Options available for Gigaset Hybird 120 IP PBX :

Require IP PBX License

Not Required, Hybird 5 Additional SIP trunk licence, Hybird 5 Additional user licences 5 Additional voice mail boxe.