

Akuvox SDP-R29 Door Phone



Product Name: Akuvox SDP-R29 Door Phone

Manufacturer: -

Model Number: SDP-R29

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SDP-R29 SIP Door Phone

The Akuvox SDP-R29 offers users the security that comes with being able to control who comes into a building, along with the ability to verbally and visually confirm their identity. The SDP-R29 enables users to easily monitor an entrance door or gate and offers the peace of mind knowing that the facility is more secure.

Akuvox SDP-R29 Door Phone Key Features

- រី¿½ Enables audio and visual monitoring of doors/gates which increases security on residential or commercial premises
- T¿½ Uses the latest H.264 video and G.722 audio codec to provide the highest quality video image and audio clarity
- ī¿½ Allows both audio and video communication to an IP phone, mobile client, or softphone
- าั¿½ Enables the ability to remotely control the door/gate
- រី¿½ Presents information and user navigation options unique to your business
- آذِاً Eliminates the need for personnel to be physically stationed at the door/gate which improves productivity and frees them up to work on other things
- آزار Speeds response time to visitors, delivery and service personnel that require access

Akuvox Video IntegrationThe SDP-R29 seamlessly integrates with Akuvox phones and its camera is ideal for working with Akuvox VP-R4X series. The real time video is streamed to the 7" TFT LCD of VP-R47P and VP-R49P and can be viewed at any time. There is no need for any 3rd party software or IP PBX support to view the video stream.

Akuvox SDP-R29 Door Phone - Technical Specifications

Physical & amp; Power

ï¿1/2 Size: 317x130x23mm (HxWxD)

� Weight: 1.34kg

� Body material: all-aluminum � Display: 7" IPS LCD

าั¿½ Screen: 7" capacitive touch screen าั¿½ Camera: 5 Mega pixels, automatic lighting

� 12V DC connector

� Water-proof & Dust-proof: IP65

� Collision-proof: IK06

SIP Endpoint

� SIP v1(RFC2543), SIP v2(RFC3261)

ï¿1/2 Audio codecs: G.711a, G.711μ, G.722

ï¿1/2 Video codecs: H.263, H.264

� Echo Cancellation

� Voice Activation Detection

� Comfort Noise Generator

Video



Akuvox SDP-R29 Door Phone

- ï¿1/2 Resolution: up to 1080p
- ï¿1/2 Maximum image transfer rate: 1080p 30fps
- ï¿1/2 Video codecs: H.263, H.264
- าั¿¼ High intensity white LEDs for picture lighting during dark hours with internal light sensor

Networking

- ï¿1/2 10/100 Mbps Ethernet connection
- � DHCP Client or Static IP
- � Network-Time-Protocol

Door Entry Feature

- � Android OS for any 3rd party software or customization
- � Internal DPDT relay for controlling a door opener;
- ī సై Relays controlled individually by DTMF tones or messages
- � Multi-way Unlock: IC Card, PassNumber, Guestures
- � G-sensor for self-defence alarm
- ï¿1/2 Volume control for speaker
- ï¿⅓ Gain control for microphone
- าั¿½ Camera permanently optrational, not just during calls
- � White balance: auto
- � Viewing angle: 90 °
- � Auto-night mode with LED illumination
- آذً Minimum illumination: 1LUX (without LED illumination)
- ï¿1/2 Max call length setting

Application Scenarios

- า๊¿1/2 Office door phone with on-site or hosted IP-PBX
- ï¿⅓ Remote site entry over Internet
- � Apartment / flat intercom with door access control
- ī సై Business information or a welcome experience for guests

Please Enquire