

## Akuvox SP-R55P IP Phone



Product Name: Akuvox SP-R55P IP Phone

Manufacturer: -

Model Number: SP-R55P

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Akuvox SP-R55P IP Phone

The Akuvox SP-R55P IP Phone is a high-quality, cost effective solution, ideal for front line staff handling moderate volume of calls through advanced telephony features. The intuitive user interface of the Akuvox SP-R55P makes navigation easy and requires minimal training. Akuvox SP-R55P IP Phone Features

- HD Voice
- Up to 3 SIP Accounts
- Black Acrylic Cover
- 2.3" Graphical LCD with Backlight
- Support 3-way Conference
- Fully Compatible with Asterisk, BroadSoft Platform

### Akuvox IP Phone SP-R55P - Technical Specifications

Phone Features:

- 3 Lines (support 3 SIP accounts)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Ring tones Selectable
- Speed Dial, Hotline
- Daylight Saving Time
- Network Packet Capture
- Country Ringtone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- XML Browser
- Hot Desking
- Keypad Lock
- Action URL/URI
- Phonebook (500 entries), Blacklist (100 entries), Call logs (100 entries)
- 5 Remote Phone Book URL Supported
- LDAP
- Multi-Language Support

### IP-PBX Features:

- SMS.Voicemail.MWI Message Notification
- Music on hold, Intercom
- BLF (Busy Lamp Field)
- Call Pickup, Group Call Pickup
- Call Recording
- Anonymous Call, Anonymous Call Rejection

## Akuvox SP-R55P IP Phone

### Audio Features:

- 1/2 HD Voice
- 1/2 Wideband Codec: G.722
- 1/2 Narrowband Codec: PCMA, PCMU, G.729, G723\_53, G723\_63, G726\_16, G726\_24, G726\_32, G726\_40
- 1/2 VAD, CNG, Echo Cancellor
- 1/2 Full-Duplex Speakerphone

### Security Features:

- 1/2 Support HTTPS (SSL)
- 1/2 Support SRTP for Voice Data Encryption
- 1/2 Support Login for Administration
- 1/2 SIP Over TLS

### Network Features:

- 1/2 SIP V1(RFC2543), V2(RFC3261)
- 1/2 Static IP/DHCP for IP configuration
- 1/2 3 DTMF modes: In-Band, RFC2833, SIP INFO
- 1/2 HTTP/HTTPS Web Server for Management
- 1/2 NTP for Auto Time Setting
- 1/2 TFTP/FTP/HTTP/HTTPS Protocols
- 1/2 802.1Q VLAN

### Administration Features:

- 1/2 Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- 1/2 Dial through IP PBX Using Phone Number
- 1/2 Dial through IP PBX Using URL Address
- 1/2 Configuration Manamements with Web, Keypad onthe phone and Auto Provisioning
- 1/2 SNMP
- 1/2 TR069

### Physical Features:

- 1/2 Audiocodes Chipset
- 1/2 2.3" 132\*64 Graphical LCD with Backlight
- 1/2 34 Keys (13 Programmable keys)
- 1/2 4 LED Lights (1 Power Light, 3 Account Lights)
- 1/2 RJ9 Handset Jack and Headset Jack
- 1/2 2 RJ45 10/100M Ethernet Jacks
- 1/2 AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A
- 1/2 PoE: IEEE 802.3af
- 1/2 Gift Box Size: 248 x 204 x 107 (mm), weight: 1.19 kg

**Please Enquire**