

## Akuvox SP-R67G IP Phone



Product Name: Akuvox SP-R67G IP Phone

Manufacturer: -

Model Number: SP-R67G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

### Akuvox SP-R67G IP Phone

The Akuvox SP-R67G is Akuvox latest Gigabit Ethernet IP Phone for executives and busy professionals. The new design is based on flagship product Akuvox R59P, with high resolution TFT colour display, delivering a rich visual experience. Akuvox's Optima HD technology enables rich, clear, life-like voice communications.

### Akuvox SP-R67G Key Features

- 1/2 HD Voice
- 1/2 Dual-port Gigabit Ethernet, PoE
- 1/2 Up to 6 SIP accounts
- 1/2 4.3" 480\*272 pixel colour display with backlight
- 1/2 Supports Expansion Modules
- 1/2 Full Compatible with Asterisk, BroadSoft Platform

### Akuvox SP-R67G - Technical Specifications

#### Phone Features

- 1/2 6 Lines (Support 6 SIP accounts)
- 1/2 Support Call Waiting, Call Forward, Call Transfer
- 1/2 Call on Hold, Mute, Auto-answer, Redial, DND
- 1/2 Local 3-Way Conference
- 1/2 Volume Adjustable, Ring tones Selectable/Import/Delete
- 1/2 Speed Dial, Hotline
- 1/2 Daylight Saving Time
- 1/2 Network Packet Capture
- 1/2 Country Ringtone Signal
- 1/2 Direct IP call
- 1/2 Auto Redial, Call Return
- 1/2 Dial Plan
- 1/2 XML Browser
- 1/2 Hot Desking
- 1/2 Keypad Lock
- 1/2 Action URL/URI
- 1/2 Phonebook (1000 groups), Blacklist (200 groups), Call logs (200 entries)
- 1/2 5 Remote Phone Book URL Supported
- 1/2 LDAP
- 1/2 Multi-Languages Support
- 1/2 Support up to 6 Expansion Modules
- 1/2 Support Wireless Headset Adapter

### IP-PBX Features

- 1/2 SMS.Voicemail.MWI Message Notification
- 1/2 Music on hold, Intercom, Paging
- 1/2 BLF (Busy Lamp Field)
- 1/2 Call Pickup, Group Call Pickup

## Akuvox SP-R67G IP Phone

- Call Recording
- Call Completion
- Anonymous Call, Anonymous Call Rejection

### Audio Features

- HD Voice: HD Handset, HD Speaker
- Wideband Codec: G.722
- Narrowband Codec: PCMA, PCMU, G.729, G723\_53, G723\_63, G726\_16, G726\_24, G726\_32, G726\_40, iLBC
- VAD, CNG, Echo Cancellor
- PLC, AJB, AGC
- Full-duplex Hands-free Speakerphone with AEC

### Network Features

- SIP V1(RFC2543), V2(RFC3261)
- NAT Transverse: STUN Mode
- Static IP/DHCP for IP Configuration
- 3 DTMF modes: In-Band, RFC2833, SIP INFO
- HTTP/HTTPS Web Server for Management
- Proxy Mode and Peer-to-peer SIP Link Mode
- NTP for Auto Time Setting
- UDP/TCP/DNS-SRV(RFC 3263)
- TFTP/FTP/HTTP/HTTPS Protocols
- 802.1 VLAN

### Administration Features

- Auto provisioning using FTP/TFTP/HTTP/HTTPS/PnP
- Dial through IP PBX Using Phone Number
- Dial through IP PBX Using URL Address
- Configuration Managements with web, keypad on the phone, and Auto Provisioning
- SNMP
- TR069
- Package Tracing Export, System Log

### Security Features

- Support HTTPS (SSL)
- Support SRTP for Voice Data Encryption
- Support Login for Administration
- OpenVPN, IEEE802.1X
- Digest Authentication Using MD5/MD5-sess
- AES Encryption for Configuration file
- SIP Over TLS

### Physical Features

- Audiocodes Chipset
- 16M Flash Memory
- 4.3" 480\*272 pixel color display with backlight, 16 bit depth color;
- Acrylic Cover
- 8 Line Keys with LED
- 49 Keys (with 4 Soft Keys)

## Akuvox SP-R67G IP Phone

1/2 19 LED Lights (1 Power Light, 8 Line LEDs, 10 dual-color(red and green) LEDs for Extended key

1/2 2\*RJ45 10/100/1000Mbps Ethernet Ports

1/2 1\*RJ9 (4P4C) Handset port

1/2 1\*RJ9 (4P4C) Headset port

1/2 1\*RJ12 (6P6C) EXT port:

1/2 AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

1/2 PoE: IEEE 802.3af, Class 3

1/2 Operating Humidity: 10~95%

1/2 Storage Temperature: -10~50&deg;C

1/2 Giftbox Size: :285.5\*224\*96.2 (mm),weight: 1.23kg

**Please Enquire**

---