

Akuvox SP-R59G IP Phone



Product Name: Akuvox SP-R59G IP Phone

Manufacturer: -

Model Number: SP-R59G

Please Note: This product is no longer available. To find an alternative, please see our VoIP Phone Comparison Charts.

Akuvox SP-R59G IP Phone

The Akuvox SP-R59G is a premium business media phone designed to enhance collaboration and personal productivity. It is built for executives and managers who need a powerful, yet intuitive, expandable office phone that helps them stay connected lead your organization. Premium high-range business phone delivering best-in-class desktop productivity for busy corporate executives and managers.

Akuvox SP-R59G Key Features

- Up to 6 SIP Accounts
- 2 Gigabit Ethernet Ports
- Support Expansion Model and Wireless Headsets
- 4.3" 480*272 Graphical LCD with Backlight, 4-bit Grayscale
- Support 3-way Conference
- Fully Compatible with Asterisk, BroadSoft Platform

Akuvox SP-R59G - Technical Specifications

Phone Features

- 6 Lines (Support 6 SIP accounts)
- Support Call Waiting, Call Forward, Call Transfer
- Call on Hold, Mute, Auto-answer, Redial, DND
- Local 3-Way Conference
- Volume Adjustable, Ring tones Selectable
- Speed Dial, Hotline
- Daylight Saving Time
- Network Packet Capture
- Country Ringtone Signal
- Direct IP call
- Auto Redial, Call Return
- Dial Plan
- XML Browser
- Hot Desking
- Keypad Lock
- Action URL/URI
- Phonebook (500 entries), Blacklist (100 entries), Call logs (100 entries)
- 5 Remote Phone Book URL Supported
- LDAP
- Multi-Language Support

IP-PBX Features

- SMS.Voicemail.MWI Message Notification
- Music on hold, Intercom
- BLF (Busy Lamp Field)
- Call Pickup, Group Call Pickup
- Call Recording

Akuvox SP-R59G IP Phone

• Anonymous Call, Anonymous Call Rejection

Audio Features

• HD Voice

• Wideband Codec: G.722

• Narrowband Codec: PCMA, PCMU, G.729, G723_53, G723_63, G726_16, G726_24, G726_32, G726_40

• VAD, CNG, Echo Cancellor

• Full-Duplex Speakerphone

Security Features

• Support HTTPS (SSL)

• Support SRTP for Voice Data Encryption

• Support Login for Administration

• SIP Over TLS

Network Features

• SIP V1(RFC2543), V2(RFC3261)

• Static IP/DHCP for IP configuration

• 3 DTMF modes: In-Band, RFC2833, SIP INFO

• HTTP/HTTPS Web Server for Management

• NTP for Auto Time Setting

• TFTP/FTP/HTTP/HTTPS Protocols

• 802.1Q VLAN

Administration Features

• Audiocodes Chipset

• 4.3" 480*272 Graphical LCD with Backlight, 4-bit Grayscale

• 49 Keys (28 Programmable keys)

• 19 LED Lights (1 Power Light, 7 Account Lights, 1 Voice Mail Light and 10 extended key color indicators)

• RJ9 Handset Jack and Headset Jack

• 2 RJ45 10/100/1000M Ethernet Jacks

• RJ12 Expansion Socket

• AC Power Adapter: Input: AC 100-240V; Output: DC 5V/1A

• POE: IEEE 802.3af

• Gift Box Size: 295 x 225 x 98 (mm), weight: 1.23kg

Please Enquire