Yealink W60B DECT IP Base Station



Product Name: Yealink W60B DECT IP Base Station
Manufacturer: -
Model Number: W60B

Please Note: This product has been discontinued. Please see the other Yealink Dect IP Phones for an available alternative.

Yealink W60B DECT IP Base Station
The Yealink W60B is the DECT IP base station for small and medium-sized businesses. Paring with up to a total of 8 Yealink W56H DECT handsets, the W60B allows you enjoy mobility and flexibility. A powerful chip ensures a better and higher performance, allowing this DECT IP base station to support up to 8 VoIP accounts and 8 concurrent calls.
Yealink W60B Key Features

ï¿½ Up to 8 concurrent calls
ï¿½ Up to 8 DECT cordless handsets
ï¿½ Up to 8 VoIP accounts
ï¿½ Support Opus audio codec
ï¿½ TLS and SRTP security encryption
ï¿½ Noise Reduction System

Designed with a modern and elegant style, this compact DECT IP base station possesses a wire-hidden design, with the option to be wall-mounted. By supporting Opus codec, Yealink W60B consistently delivers excellent and professional audio quality in both high-bandwidth and poor network conditions.
Yealink W60B - Technical Specifications
Phone Features

ï¿½ Up to 8 concurrent calls
ï¿½ Up to 8 handsets
ï¿½ Up to 8 VoIP accounts
ï¿½ Up to 5 repeaters per base station
ï¿½ Paging, intercom, auto answer
ï¿½ Call hold, call transfer, call waiting
ï¿½ Three-way conference
ï¿½ Switching between calls
ï¿½ Mute, silence, DND
ï¿½ Caller ID with name and number
ï¿½ Redial
ï¿½ Anonymous call
ï¿½ Anonymous call rejection
ï¿½ Call forward (always/busy/no answer)
ï¿½ Speed dial
ï¿½ Voicemail
ï¿½ Message Waiting Indication (MWI)
ï¿½ Local phonebook for up to 500 entries (store in the base)
ï¿½ Remote phonebook/LDAP
ï¿½ Phonebook search/import/export
ï¿½ Call history (all/missed/placed/received)
ï¿½ Direct IP call without SIP proxy
ï¿½ Reset to factory, reboot
ï¿½ Emergency call
ï¿½ Dial plan

Yealink W60B DECT IP Base Station

ï¿½ Music on hold
ï¿½ Broadsoft directory
ï¿½ BroadSoft call log
ï¿½ Broadworks feature key synchronisation
ï¿½ Shared Call Appearance (SCA)

Management

ï¿½ Auto-provision via TFTP/FTP/HTTP/HTTPS/RPS
ï¿½ Auto-provision with PnP
ï¿½ Handset upgrade: OTA (Over-The-Air)/USB port
ï¿½ Configuration: browser/phone/auto-provision
ï¿½ Trace package and system log export

Audio Features

ï¿½ Wideband codec: Opus, AMR-WB (optional), G.722
ï¿½ Narrowband codec: PCMU, PCMA, G.726, G.729, iLBC
ï¿½ VAD, CNG, AEC, AGC, PLC, AJB
ï¿½ Support VQ-RTCPXR (RFC6035)

Network Features

ï¿½ SIP v1 (RFC2543), v2 (RFC3261)
ï¿½ SNTP/NTP
ï¿½ VLAN (802.1Q and 802.1P)
ï¿½ 802.1x, LLDP, PPPoE
ï¿½ STUN Client (NAT Traversal)
ï¿½ UDP/TCP/TLS
ï¿½ IP assignment: static/DHCP
ï¿½ Support outbound proxy server backup

Security

ï¿½ Open VPN
ï¿½ Transport Layer Security (TLS)
ï¿½ HTTPS (server/client)
ï¿½ SRTP (RFC3711)
ï¿½ Digest authentication using MD5
ï¿½ Secure configuration file via AES encryption
ï¿½ Support SHA256/SHA512/SHA384
ï¿½ Three-level configuration mode: Admin/Var/User

DECT

ï¿½ Frequency bands: 1880 – 1900 MHz (Europe), 1920 – 1930 MHz (US)
ï¿½ DECT Standards: CAT-iq2.0

Interface

ï¿½ 1 x RJ45 10/100M Ethernet port
ï¿½ Power over Ethernet (IEEE 802.3af), Class 1

Physical Features

Yealink W60B DECT IP Base Station

ï¿½ Indoor Range: 20m~50m (The ideal distance is 50m)
ï¿½ Outdoor Range: 300m (in ideal conditions)
ï¿½ Desktop or wall mountable
ï¿½ Energy-saving ECO mode/ECO Mode+
ï¿½ Three LED indicators on W60B:1 x Registration LED1 x Network Status LED1 x Power Indicator LED
ï¿½ External Yealink AC adapter：AC 100-240V Input and DC 5V/600mA Output
ï¿½ Dimension (W*D*H): 130mm x 100mm x 25.1mm
ï¿½ Operating humidity: 10~95%
ï¿½ Operating temperature: -10~+50°C (+14~122°F)

Package Features

ï¿½ Package content:-W60B Base Station-Base Stand-Power Adapter-Ethernet Cable-Quick Start Guide
ï¿½ Qty/CNT: 10 PCS
ï¿½ Giftbox size: 205mm*196mm*95mm
ï¿½ Carton measures: 512mm*414mm*213mm
ï¿½ N.W: 3.6 kg
ï¿½ G.W: 4.3 kg

Please Enquire

Options available for Yealink W60B DECT IP Base Station :

DECT Repeater Required

Yealink DECT Repeater RT30 (RT30-repeater) (+£80.45), Not Required.

Need Product Setup / Training / Support?

Required - 1 Hour (+£65.00), Required - 30 minutes (+£40.00), Not Required.

Handset Required?

Yealink W53H (+£47.30), Yealink CP930W (+£284.80), Yealink W56H (+£67.00), Not Required, Yealink W59R (+£88.00).