

## Draytek Vigor2820Vn ADSL/Cable/3G Router Firewall



Product Name: Draytek Vigor2820Vn ADSL/Cable/3G Router Firewall

Manufacturer: -

Model Number: V2820VN

**Please Note:** The Draytek 2820 series has been discontinued. It has been replaced by the 2830 Series.

The Vigor 2820 series is DrayTek's latest premium ADSL and broadbandrouter/firewall family, featuring an entirely new stylish case designand new DrayOS 3 operating system. Packed with features, the Vigor 2820offers truly comprehensive ADSL connectivity and security.

Compatiblewith all variants of ADSL (include ADSLMax and ADSL2+) the Vigor 2820can also be used for cable-modem and leased line applications thanks toits additional WAN port (Ethernet). A Gigabit Ethernet port on the WANside provides high speed connectivity for your server (or uplink to alarger Ethernet Switch). Security features include content filtering,web application controls and a new object based firewall managementsystem.

**Robust & Comprehensive Firewall**

As with previous DrayTek firewalls, security is taken seriously onthe Vigor 2820 Series. The firewall features measures for protectionagainst attacks including DoS (Denial of Service) attacks, IP-basedattacks and access by unauthorised remote systems. Wireless, Ethernetand VPN are also protected by various protection systems (see later). Anew DrayTek object-based firewall allows even more setup flexibilitythan ever, enabling you to create combinations of users, rules andrestrictions to suit multi-departmental organisations.

Content control features of the firewall allow you to setrestrictions on web site access, blocking download of certain filetypes, blocking specific web sites, blocking IM/P2P applications orother potentially harmful or wasteful content. Using the SurfControlsite categorisations enable you to block whole categories of web sites(e.g. gambling, pornography etc.), subject to subscription Dual-WAN Load Balancing & Backup

As well as the primary ADSL interface, the Vigor 2820 features asecondary WAN port for Internet access. This is an Ethernet interfaceand can connect to a second ADSL modem, cable modem or any otherEthernet-based Internet feed. The secondary interface can be usedeither for WAN-Backup or load balancing.

WAN-Backup provides contingency (redundancy) in case of your primaryADSL line or ISP suffering temporary outage). Internet Traffic will be temporarily routed via the secondary Internet access.

When normalservices is restored to your primary ADSL line, all traffic is switchback to that.

If you don't have ADSL, the Ethernet WAN port can instead be used asyour primary/only Internet connection (using NAT) so the same routercan be used for either ADSL or Ethernet Internet connections.

The USB port provides an alternative connection method (Firmware Upgradable) for Internet backup by connecting to a compatible USB modem (or cellphone) for access to the high speed 3G cellular networksfrom UK providers such as Vodafone, Orange, 3 and T-Mobile. If youdon't have ADSL at all, the USB/3G access method can be used as yourprimary/only Internet connection, ideal for temporary locations, mobileapplications or where broadband access is not available.

**Note :** For WAN2 you can use either a Ethernet or USB 3G connection but not both at the same time.

**Wireless LAN ('n' models only)**

The Vigor2820 Series features the latest 802.11n Draft 2.0 wirelessLAN specification and has been certified by the WiFi alliance for crosscompatibility and WiFi compliance (including WPA/WPA2 and WMM).

802.11n Draft 2.0 provides a total wireless bandwidth of up to300Mb/s using new methods such as packet aggregation and channelbonding. Throughput depends on your own environment (factors such as obstructions, number of hosts and distance all make a significantdifference), but actual transfer speeds of 100Mb/s are achievable(based on our real world tests). In addition, 802.11n Draft 2.0provides greater coverage and resilience to interference compared toprevious wireless standards thanks to the MIMO technology and theVigor's triple-antennae diversity

## Draytek Vigor2820Vn ADSL/Cable/3G Router Firewall

arrangement. This offset arrangement of aerials provides offset paths between hosts so that interference can be overcome.

Wireless Security is comprehensive too; the Vigor2820 Series provides several independent levels of security including encryption (up to WPA2), authentication (802.11x) and methods such as MAC address locking and DHCP fixing to restrict access to authorised users only. The Web interface lets you see how many and which clients are currently connected as well as their current bandwidth usage. An 'instant' block lets you disconnect a wireless user temporarily in case of query. The Wireless VLAN facility allows you to isolate wireless clients from each other or from the 'wired' LAN.

The Multiple SSID features enables you to have up to four distinct or common virtual wireless access points. For example, you could have one for company usage, with access to your company LAN and another for public access which allows internet surfing only. Setting up wireless security is made easier thanks to the WPS feature (WiFi protected setup) whereby your client PC can get its security keys by pressing a button on the front of the router.

### Voice-over-IP Features ('V' Models Only)

The Vigor 2820 Series 'V' models build on the established DrayTek VoIP pedigree by adding even more new features. Twin analogue phone ports and an FXO analogue line port provide full PSTN and VoIP integration on the same phones, via both the Internet and your regular analogue line. The two phones can be used independently and simultaneously for both incoming and outgoing calls. As well as the two telephone ports, a third port, the FXO (Line) port, connects into your regular analogue line (PSTN/POTS\*). This then gives the telephones access to your analogue line to allow you to make calls as well as your VoIP facility (you can select the PSTN line instead of VoIP by dialling #0). Incoming calls are automatically switched through to your telephone(s) (either one or both) so that each phone can be used for both VoIP and POTS calls. Both telephones plugged into your router have access to VoIP and your analogue line. In addition, using the 'Digit-Map' facility you can set rules about particular call destinations using either the POTS line or your SIP/VoIP service. For example, local calls can be routed via your PSTN line (if you have a free calls package for example) whereas international calls can go via your preferred VoIP provider; there is flexibility to have several digit-map rules.

### Detailed Specification:

#### Physical Interfaces:

##### LAN Ports (Switch)

1 X Gigabit Ethernet (1000Mb/s) Ports

3 X Megabit (100Mb/s) Ports

Port-Based VLAN (Inclusive/Exclusive Groups)

#### WAN Ports:

##### ADSL Port Compliant with:

ANSI T1.413 Issue2

ITU-T G.992.1 G.dmt (ADSL)

ITU-T G.992.2 G.lite

ITU-T G.992.3 ADSL2

ITU-T G.992.5 ADSL2+

Annex L (READSL)

Annex M

Secondary WAN Port : 10/100 Base-TX Ethernet for load balance and WAN failover

USB Port for 3G Cellular Modem or Printer

## Draytek Vigor2820Vn ADSL/Cable/3G Router Firewall

• VoIP: 2-port FXS Phone Ports (Vigor2820 'V' models only)

• Load Balance/Failover Features:

- Outbound Policy-Based Load-Balance
- WAN Connection Fail-over
- BoD (Bandwidth on Demand)

• Vigor 2820 ATM Protocols (DSL):

- RFC-2684/RFC-1483 Multiple Protocol over AAL5
- RFC-2516 PPP over Ethernet
- RFC-2364 PPP over AAL5
- PPPoE pass through LAN/WLAN
- PPPoE/PPPoA Relay
- Transparent bridge for MPoA
- Multiple PVC support for Triple Play Applications (up to 8 simultaneous)

• Wireless LAN Features ('n' Models Only):

- 802.11n Compliant (Draft 2.0)
- Latest 'MIMO' Technology with three aerials (2T3R)
- Multiple SSID : Create up to 4 virtual wireless LANs (independent or joined)
- Packet Aggregation and Channel Bonding
- Compatible with 802.11b and 802.11g Standards
- Active Client list in Web Interface
- Wireless LAN Isolation (from VLAN groups and wired Ethernet interfaces)
- 64/128-bit WEP Encryption
- WPA/WPA2 Encryption
- Switchable Hidden SSID
- Restricted access list for clients (by MAC address)
- Time Scheduling (WLAN can be disabled at certain times of day)
- Access Point Discovery
- WDS (Wireless Distribution system) for WLAN Bridging and Repeating (Firmware Upgradable)
- 802.1x Radius Authentication
- Wireless Rate-Control
- Automatic Power Management
- 802.11e WMM (Wi-Fi Multimedia)

• VoIP Features (Vigor2820 'V' Models only):

- Protocols: SIP, RTP / RTCP
- 12 SIP Registrar Accounts (for up to 12 VoIP providers)
- Line port for PSTN Passthrough (integrates POTS line)
- Auto-fallback to PSTN under power/Internet failure
- G.168 Line Echo-cancellation
- Automatic Gain Control
- Jitter Buffer ( 125ms )

## Draytek Vigor2820Vn ADSL/Cable/3G Router Firewall

### • Voice Codecs:

- G.711 A / &micro; Law
- G.723.1
- G.726
- G.729 A / B

### • VAD / CNG

- Tone Generation: DTMF , Dial , Busy , Ring Back , Call Progress
- DTMF Transmission: In Band / Out Band ( RFC-2833 ) / SIP info
- FAX / Modem Support G.711 Pass-through

### • T.38 for FAX

### • Supplemental Services:

- Caller ID
- Call Hold / Retrieve
- Call Waiting
- Call Waiting with Caller ID
- Call Transfer
- Call Forwarding ( Always , On Busy and On No Answer )
- DND (Do not Disturb)
- Call Barring ( Incoming / Outgoing )
- MWI ( Message Waiting Indicator ) ( RFC-3842 )
- Hotline (Dial preset number when handset lifted)

### • WAN Protocols (Ethernet):

- DHCP Client
- Static IP
- PPPoE
- PPTP
- L2TP \*
- BPA

### • Firewall & Security Features:

#### • CSM (Content Security Management):

- URL Keyword Filtering - Whitelist or Blacklist specific sites or keywords in URLs
- Surfcontrol Support - Block Web sites by category (subject to subscription)
- Prevent accessing of web sites by using their direct IP address (thus URLs only)
- Blocking automatic download of Java applets and ActiveX controls
- Blocking of web site cookies
- Block http downloads of file types :

• Binary Executable : .EXE / .COM / .BAT / .SCR / .PIF

• Compressed : .ZIP / .SIT / .ARC / .CAB/ .ARJ / .RAR

• Multimedia : .MOV / .MP3 / .MPEG / .MPG / .WMV / .WAV / .RAM / .RA / .RM / .AVI / .AU

## Draytek Vigor2820Vn ADSL/Cable/3G Router Firewall

- Time Schedules for enabling/disabling the restrictions
- Block P2P (Peer-to-Peer) file sharing programs (e.g. Kazza, WinMX etc.)
- Block Instant Messaging programs (e.g. IRC, MSN/Yahoo Messenger etc.)

- Multi-NAT, DMZ Host
- Port Redirection and Open Port Configuration
- Policy-Based Firewall
- MAC Address Filter
- SPI ( Stateful Packet Inspection ) with new FlowTrack Mechanism
- DoS / DDoS Protection
- IP Address Anti-spoofing
- E-Mail Alert and Logging via Syslog
- Bind IP to MAC Address

### • Bandwidth Management:

- QoS
- Guaranteed Bandwidth for VoIP
- Class-based Bandwidth Guarantee by User-Defined Traffic Categories
- DiffServ Code Point Classifying
- 4-level Priority for each Direction (Inbound / Outbound)
- Bandwidth Borrowed
- Temporary (5 minute) Quick Blocking of any LAN Client
- Bandwidth / Session Limitation

### • Network/Router Management:

- Web-Based User Interface (HTTP / HTTPS)
- CLI ( Command Line Interface ) / Telnet / SSH\*
- Administration Access Control
- Configuration Backup / Restore
- Built-in Diagnostic Function
- Firmware Upgrade via TFTP / FTP
- Logging via Syslog
- SNMP Management with MIB-II
- TR-069
- TR-104

### • VPN Facilities:

- Up to 32 Concurrent VPN Tunnels (incoming or outgoing)
- Tunnelling Protocols: PPTP, IPsec, L2TP, L2TP over IPsec
- IPsec Main and Aggressive modes
- Encryption : MPPE and Hardware-Based AES / DES / 3DES
- Authentication : Hardware-Based MD5 and SHA-1
- IKE Authentication : Pre-shared Key and X.509 Digital Signature
- LAN-to-LAN & Teleworker-to-LAN connectivity
- DHCP over IPsec
- NAT-Traversal ( NAT-T )
- Dead Peer Detection (DPD)
- VPN Pass-Through

## Draytek Vigor2820Vn ADSL/Cable/3G Router Firewall

### • Network Features:

- DHCP Client / Relay / Server
- Dynamic DNS
- NTP Client (Syncronise Router Time)
- Call Scheduling (Enable/Trigger Internet Access by Time)
- RADIUS Client
- DNS Cache / Proxy
- Microsoft® UPnP Support

### • Routing Protocols:

- Static Routing
- RIP V2

### • Operating Requirements:

- Rack Mountable (Optional Vigor 2820 mounting bracket required)
- Wall Mountable
- Temperature Operating : 0°C ~ 45°C
- Storage : -25°C ~ 70°C
- Humidity 10% ~ 90% (non-condensing)
- Power Consumption: 18 Watt Max.
- Dimensions: L240.96 \* W165.07 \* H43.96 ( mm )
- Operating Power: DC 15V (via external PSU, supplied)
- Warranty : Two (2) Years RTB
- Power Requirements : 220-240VAC

**Please Enquire**