

## V3 SIP Office Ringer

The CyberData SIP-enabled V3 SIP Office Ringer is a Power-over-Ethernet (PoE 802.3af) and Voice-over-IP (VoIP) notification device that easily connects into existing local area networks (LANs) with a single cable connection.

The V3 SIP Office Ringer provides a user uploadable audible ring indication when part of a ring group. The SIP Office Ringer also supports direct SIP voice paging and priority-based Multicast broadcasts.

### Typical Applications

- Office Environment Ringer
- General Paging
- Mass Notification

### Features

- Faster V3 Processor
- Supports Cisco SRST
- User uploadable ring/messages
- PoE 802.3af enabled (Powered-over-Ethernet)
- SIP compliant
- Network web management
- Network adjustable speaker volume
- Network downloadable firmware
- Concurrent SIP and multicast paging
- Dry relay contact for auxiliary control (controls external power)
- Peer-to-peer capable
- Sensor and tamper alert signal



### Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +12 to +24 VDC at 1000 mA (500 mA minimum)
Operating Temperature	-30 to 55 C (-22 to 131 F)
Payload Types	G711, A-law and $\mu$ -law
Regulatory Compliance	FCC Class A, UL 60950
Sound volume level	87db at 1 meter
Dimensions	5" x 5" x 2.5" (H x W x D)
Warranty	2 years limited
Boxed Weight	1.2 lbs.
Part Number	011216, RAL 9003, Signal White



Outdoor Intercom  
#011186



Emergency Intercom  
#011209



Wall Mount Keypad  
#011113



Flush Mount Keypad  
#011123

# V3 SIP Office Ringer

