

The Singlewire-enabled SIP Speaker is for use with Singlewire's paging and emergency notification software InformaCast® or InformaCast CK. This PoE-powered device hooks up easily to new and existing Singlewire installations.

New Features

- Dual registration for Singlewire and SIP
- Support for security code to prevent unwanted SIP calls
- Optional red/green/blue/white strobe kit connection available (coming soon)
- Autoprovisioning via HTTP, HTTPS, or TFTP
- HTTPS or HTTP web based configuration. HTTPS is enabled by default.
- 802.11q VLAN tagging
- Configurable sense input for use with fault detection or with optional lighted button kit
- Configurable event generation for device health and status monitoring
- Support for G.722 codecs
- Powered via PoE (802.3AF or 802.3AT) or 24V auxiliary power supply (not included)
- Enhanced interoperability for hosted environments

Features

- SIP (RFC 3261) compatible
- Night Ringer function
- Plays audio from Multicast
- Web-based configuration
- Paging prioritization and background music
- User upgradeable firmware via web interface or autoprovisioning
- External volume control
- Small footprint
- High efficiency speaker driver
- IGMP | SIP endpoint or Multicast group member
- Network-adjustable speaker volume
- Can drive one external analog speaker for greater coverage (part #011120/011121 sold separately)
- Optional clock kit available (part #011153/011154 sold separately)
- Support for 10 multicast paging groups
- Support for multiple SIP servers for redundancy
- Support for Cisco SRST resiliency
- Relay for activating door locks, external amplifiers, etc.
- Line-level audio output for connecting to an external amplifier



Specifications

Sensitivity	96dB / 1W / 1M S.P Level
Output	10 Watts Peak Power
Operating Temperature	-30 to 55 C (-22 to 131 F)
Ethernet I/F	10/100 Mbps
Protocol	InformaCast and/or SIP (RFC 3261)
Power Input	PoE 802.3af/802.3at
Payload Types	G.711 u-law, G.711 a-law, and G.722
Dimensions	9" x 2.4"
Boxed Weight	4.0 lbs
Warranty	2 years limited

Part Number

011395*, Standard Color, RAL 9002, Gray White


011396*, Optional Color, RAL 9003, Signal White

*This number replaces the 011102 and 011103 number.


Singlewire InformaCast Features

- Singlewire Informacast compatibility available.
- Includes support for Informacast resiliency.
- Supports both SIP and Singlewire InformaCast
- InformaCast compliant
- InformaCast CK compliant

Singlewire InformaCast Speaker



Singlewire InformaCast Speaker with Extra Speaker Connection



Speaker with Strobe Kit

