

Secure Access Control Keypad

The CyberData Secure Access Control Keypad uses the existing VoIP or PoE network infrastructure to securely unlock and lock gates or doors.

PoE-powered and in a secure outdoor-rated case, this VoIP Security Endpoint can store up to 500 access codes. There is a blacklisted code list that when activated, will make a phone call and play a pre-recorded message or can broadcast a multicast message to IP speakers when registered to the VoIP server. Good code and blacklisted code lists can be updated on the web interface or autoprovisioned by a remote server.

CyberData has maintained one of the most comprehensive list of IP PBX servers certified to work with CyberData VoIP Products.

Features

- Alert buzzer
- Red/Green lock status lights
- Can operate in standalone mode. PBX not required. Future-proof and adaptable when upgrading to new VoIP PBX
- Built in time of access scheduler
- Local and remote logging with time stamp
- NTP time support
- Network web management
- Blacklisted code alert via dialout and multicast stored message
- Network downloadable firmware
- Dry contact relay to trigger door lock or unlock gates
- Door closure and tamper alert signal
- Security Torx screws with driver kit included

Related Products:




011375 Network Dual Door Strike Relay




011269 Door Strike Intermediate Relay Module



011188 Outdoor Intercom Shroud



011423 Desktop Stand for 1X Outdoor Backboxes



011443 Flush Mount Kit, 1X

CyberData

The IP Endpoint Company



Specifications

Ethernet I/F	10/100 Mbps
Protocol	SIP RFC 3261 Compatible
Power Input	PoE 802.3af compliant or +8 to +12VDC @ 1000mA Regulated Power Supply (not included)
On-Board Relay	1A @ 30 VDC
Payload Types	G.711 a-law, G.711μ-law, and G.722
IP Rating	IP65
Operating Range	Temperature: -40° C to 55° C (-40° F to 131° F) Humidity: 5-95%, non-condensing
Storage Temperature	-40° C to 70° C (-40° F to 158° F)
Storage Altitude	Up to 15,000 ft. (4573 m)
Dimensions*	5.118 inches [130 mm] Length 2.252 inches [57.21 mm] Width 5.118 inches [130 mm] Height
Weight	2.0 lbs. [0.90 kg]
Boxed Weight	3.0 lbs. [1.36 kg]
Compliance	CE; EMC Directive – Class A EN 55032 & EN 55024, LV Safety Directive – EN 60950-1, RoHS Compliant, FCC; Part 15 Class A, Industry Canada; ICES-3 Class A, IEEE 802.3 Compliant
Warranty	2 Years Limited
Part Number	011433

*Dimensions are measured from the perspective of the product being upright with the front of the product facing you.

Secure Access Control Keypad

Typical Installation (Door Strike Options)

