


Future-ready Security along with Flexi Ports for SME | CR300iNG-XP

Data Sheet 

Cyberoam NG series of Unified Threat Management appliances are the Next-Generation network security appliances that include UTM security features along with performance required for future networks. The NG series for SMEs are the “fastest UTM” made for this segment, offering unmatched throughput speeds compared to any other UTM appliance in this market. The Flexi Ports (XP) available in CR300iNG-XP UTM appliances offer flexible network connectivity with I/O slot that allows additional Copper/Fiber 1G/10G ports on the same security appliance. To SMEs who want to shift to Fiber 1GbE/10GbE connectivity, Flexi Ports give freedom from forced purchase of higher end security appliances to get desired I/O interfaces. Flexi Ports consolidate the number of devices in a network, offering benefits of power efficiency, reduced network complexity and reduced OPEX.



With Cyberoam NG series, businesses get assured Security, Connectivity and Productivity. The Layer 8 Technology treats User-Identity as the 8th Layer or the HUMAN layer in the protocol stack. It attaches User-Identity to security, which adds speed to an organization’s security by offering instant visibility into the source of attacks by username rather than only IP address. Cyberoam’s Extensible Security Architecture (ESA) supports feature enhancements that can be developed rapidly and deployed with minimum efforts, offering future-ready security to organizations.



The ‘Next-Generation’ Series:
The fastest UTM’s made for SMEs with flexible Internet connectivity options



Cyberoam’s **Layer 8 Technology** treats “User Identity” as the 8th Layer in the protocol stack

L8	USER	
L7	Application	
L6	Presentation	ASCII, EBCDIC, ICA
L5	Session	L2TP, PPTP
L4	Transport	TCP, UDP
L3	Network	192.168.1.1
L2	Data Link	00-17-BB-8C-E3-E7
L1	Physical	

Cyberoam UTM offers security across Layer 2-Layer 8 using Identity-based policies

Cyberoam UTM features assure Security, Connectivity, Productivity

Security

Network Security

- Firewall
- Intrusion Prevention System
- Web Application Firewall

Content Security

- Anti-Virus/Anti-Spyware
- Anti-Spam (Inbound/Outbound)
- HTTPS/SSL Content Security

Administrative Security

- Next-Gen UI
- iView- Logging & Reporting



Connectivity

Business Continuity

- Multiple Link Management
- High Availability

Network Availability

- VPN
- 3G/4G/WiMAX Connectivity

Future-ready Connectivity

- “IPv6 Ready” Gold Logo



Productivity

Employee Productivity

- Content Filtering
- Instant Messaging Archiving & Controls

IT Resource Optimization

- Bandwidth Management
- Traffic Discovery
- Application Visibility & Control

Administrator Productivity

- Next-Gen UI



Specification

Interfaces

Maximum number of Available Ports	14
Fixed Copper GbE Ports	6
Number of Slots for Flexi Ports Module	1
Port options per Flexi Ports Module*** (GbE Copper/GbE Fiber/10GbE Fiber)	8 / 8 / 4
Console Ports (RJ45)	1
Configurable Internal/DMZ/WAN Ports	Yes
USB Ports	2
Hardware Bypass Segment†	2

System Performance*

Firewall Throughput (UDP) (Mbps)	21,000
Firewall Throughput (TCP) (Mbps)	10,500
New sessions/second	100,000
Concurrent sessions	3,200,000
IPSec VPN Throughput (Mbps)	1,300
No. of IPSec Tunnels	5,000
SSL VPN Throughput (Mbps)	500
WAF Protected Throughput (Mbps)	1,250
Anti-Virus Throughput (Mbps)	2,900
IPS Throughput (Mbps)	4,000
UTM Throughput (Mbps)	1,700

Stateful Inspection Firewall

- Layer 8 (User - Identity) Firewall
- Multiple Security Zones
- Location-aware and Device-aware Identity-based Access Control Policy
- Access Control Criteria (ACC): User-Identity, Source and Destination Zone, MAC and IP address, Service
- Security policies - IPS, Web Filtering, Application Filtering, Anti-virus, Anti-spam and QoS
- Country-based Traffic Control
- Access Scheduling
- Policy based Source and Destination NAT, Gateway Specific NAT Policy
- H.323, SIP NAT Traversal
- DoS and DDoS attack prevention
- MAC and IP-MAC filtering
- Spoof Prevention

Intrusion Prevention System

- Signatures: Default (4500+), Custom
- IPS Policies: Pre-configured Zone-based multiple policies, Custom
- Filter based selection: Category, Severity, Platform and Target (Client/Server)
- IPS actions: Recommended, Allow Packet, Drop Packet, Disable, Drop Session, Reset, Bypass Session
- User-based policy creation
- Automatic signature updates via Cyberoam Threat Research Labs
- Protocol Anomaly Detection
- SCADA-aware IPS with pre-defined category for ICS and SCADA signatures

Gateway Anti-Virus & Anti-Spyware

- Virus, Worm, Trojan Detection and Removal
- Spyware, Malware, Phishing protection
- Automatic virus signature database update
- Scans HTTP, HTTPS, FTP, SMTP/S, POP3, IMAP, IM, VPN Tunnels
- Customize individual user scanning
- Self Service Quarantine area
- Scan and deliver by file size
- Block by file types

Gateway Anti-Spam

- Inbound and Outbound Scanning
- Real-time Blacklist (RBL), MIME header check
- Filter based on message header, size, sender, recipient
- Subject line tagging
- Language and Content-agnostic spam protection using RPD Technology
- Zero Hour Virus Outbreak Protection
- Self Service Quarantine area
- IP address Black list/White list
- Spam Notification through Digest
- IP Reputation based Spam filtering

Web Filtering

- On-Cloud Web Categorization
- Controls based on URL, Keyword and File type
- Web Categories: Default (89+), External URL Database, Custom
- Protocols supported: HTTP, HTTPS
- Block Malware, Phishing, Pharming URLs
- Block Java Applets, Cookies, Active X, Google Cache pages
- CIPA Compliant
- Data leakage control by blocking HTTP and HTTPS upload
- Schedule-based access control
- Custom Denied Message per Web Category
- Safe Search enforcement, YouTube for Schools

†If Enabled, will bypass traffic only in case of power failure. ***Additional purchase required, only single Flexi Ports Module can be used at a time. Flexi Ports are not HOT swappable. Appliance needs to be turned off prior to changing the Flexi Ports Module. *Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments. **For details, refer Cyberoam's Technical Alliance Partner list on Cyberoam website.

****Additional Purchase Required. For list of compatible platforms, refer to OS Compatibility Matrix on Cyberoam DOCS.

Application Filtering

- Layer 7 (Applications) & Layer 8 (User - Identity) Control and Visibility
- Inbuilt Application Category Database
- Control over 2,000+ Applications classified in 21 Categories
- Filter based selection: Category, Risk Level, Characteristics and Technology
- Schedule-based access control
- Visibility and Controls for HTTPS based Micro-Apps like Facebook chat, Youtube video upload
- Securing SCADA Networks
- SCADA/ICS Signature-based Filtering for Protocols Modbus, DNP3, IEC, Bacnet, Omron FINS, Secure DNP3, Longtalk
- Control various Commands and Functions

Web Application Firewall

- Positive Protection model
 - Unique "Intuitive Website Flow Detector" technology
 - Protection against SQL Injections, Cross-site Scripting (XSS), Session Hijacking, URL Tampering, Cookie Poisoning etc.
 - Support for HTTP 0.9/1.0/1.1
 - Back-end servers supported: 5 to 300 servers
- ## Virtual Private Network
- IPSec, L2TP, PPTP
 - Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
 - Hash Algorithms - MD5, SHA-1
 - Authentication: Preshared key, Digital certificates
 - IPSec NAT Traversal
 - Dead peer detection and PFS support
 - Diffie Hellman Groups - 1, 2, 5, 14, 15, 16
 - External Certificate Authority support
 - Export Road Warrior connection configuration
 - Domain name support for tunnel end points
 - VPN connection redundancy
 - Overlapping Network support
 - Hub & Spoke VPN support
 - Threat Free Tunneling (TFT) Technology

SSL VPN

- TCP & UDP Tunneling
- Authentication - Active Directory, LDAP, RADIUS, Cyberoam (Local)
- Multi-layered Client Authentication - Certificate, Username/Password
- User & Group policy enforcement
- Network access - Split and Full tunneling
- Browser-based (Portal) Access - Clientless access
- Lightweight SSL VPN Tunneling Client
- Granular access control to all the enterprise network resources
- Administrative controls - Session timeout, Dead Peer Detection, Portal customization
- TCP based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

Wireless WAN

- USB port 3G/4G and WiMAX Support
- Primary WAN link
- WAN Backup link

Bandwidth Management

- Application, Web Category and Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Data Transfer Report for multiple Gateways

Networking

- WRR based Multilink Load Balancing
- Automated Failover/Failback
- Interface types: Alias, Multiport Bridge, LAG (port trunking), VLAN, WWAN, TAP
- DNS-based inbound load balancing
- IP Address Assignment - Static, PPPoE (with Schedule Management), L2TP, PPTP & DDNS, Client, Proxy ARP, Multiple DHCP Servers support, DHCP relay
- Supports HTTP Proxy, Parent Proxy with FQDN
- Dynamic Routing: RIP v1& v2, OSPF, BGP, PIM-SIM, Multicast Forwarding
- Support of ICAP to integrate third-party DLP, Web Filtering and AV applications
- Discover mode for PoC Deployments
- IPv6 Support:
 - Dual Stack Architecture: Support for IPv4 and IPv6 Protocols
 - Management over IPv6
 - IPv6 Route: Static and Source
 - IPv6 tunneling (6in4, 6to4, 6rd, 4in6)
 - Alias and VLAN
 - DNSv6 and DHCPv6 Services

- Firewall security over IPv6 traffic
- High Availability for IPv6 networks

High Availability

- Active-Active
- Active-Passive with state synchronization
- Stateful Failover with LAG Support

Administration & System Management

- Web-based configuration wizard
- Role-based Access control
- Support of API
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c)
- Multi-lingual : English, Chinese, Hindi, French, Japanese
- Cyberoam Central Console (Optional)

User Authentication

- Internal database
- AD Integration and OU-based Security Policies
- Automatic Windows/RADIUS Single Sign On
- External LDAP/LDAPS/RADIUS database Integration
- Thin Client support
- 2-factor authentication: 3rd party support**
- SMS (Text-based) Authentication
- Layer 8 Identity over IPv6
 - Secure Authentication - AD, LDAP, Radius
 - Clientless Users
 - Authentication using Captive Portal

Logging/Monitoring

- Real-time and historical Monitoring
- Log Viewer - IPS, Web filter, WAF, Anti-Virus, Anti-Spam, Authentication, System and Admin Events
- Forensic Analysis with quick identification of network attacks and other traffic anomalies
- Syslog support
- 4-eye Authentication

On-Appliance Cyberoam-View Reporting

- Integrated Web-based Reporting tool
- 1,200+ drilldown reports
- Compliance reports - HIPAA, GLBA, SOX, PCI, FISMA
- Zone based application reports
- Historical and Real-time reports
- Default Dashboards: Traffic and Security
- Username, Host, Email ID specific Monitoring Dashboard
- Reports - Application, Internet & Web Usage, Mail Usage, Attacks, Spam, Virus, Search Engine, User Threat Quotient (UTQ) for high risk users and more
- Client Types Report including BYOD Client Types
- Multi-format reports - tabular, graphical
- Export reports in - PDF, Excel, HTML
- Email notification of reports
- Report customization - (Custom view and custom logo)
- Supports 3rd party PSA Solution - ConnectWise



IPSec VPN Client***

- Inter-operability with major IPSec VPN Gateways
- Import Connection configuration

Certification

- Common Criteria - EAL4+
- ICSA Firewall - Corporate
- Checkmark Certification
- VPNC - Basic and AES interoperability
- IPv6 Ready Gold Logo
- Global Support Excellence - ITIL compliance (ISO 20000)

Hardware Specifications

Memory	2GB
Compact Flash	4GB
HDD	250GB or higher

Compliance

CE
FCC

Dimensions

H x W x D (inches)	1.7 x 17.3 x 11.85
H x W x D (cms)	4.4 X 43.9 X 30.1
Weight	5.1 kg, 11.24 lbs

Power

Input Voltage	100-240 VAC
Consumption	137W
Total Heat Dissipation (BTU)	467

Environmental

Operating Temperature	0 to 40 °C
Storage Temperature	0 to 70 °C
Relative Humidity (Non condensing)	10 to 90%

Toll Free Numbers

USA : +1-800-686-2360 | India : 1-800-301-00013

APAC/MEA : +1-877-777-0368 | Europe : +44-808-120-3958

www.cyberoam.com | sales@cyberoam.com

Copyright © 1999-2016 Cyberoam Technologies Pvt. Ltd. All Rights Reserved.
Cyberoam and Cyberoam logo are registered trademarks of Cyberoam Technologies Pvt. Ltd. Although Cyberoam has attempted to provide accurate information, Cyberoam assumes no responsibility for accuracy or completeness of information neither is this a legally binding representation. Cyberoam has the right to change, modify, transfer or otherwise revise the publication without notice. 1.1-10.6.2.210316

