



Professional Office/Contact Centre Headsets for Unified Communications

JPL-Connect

The JPL CONNECT is a **super light-weight** affordable professional office and contact centre headset suitable for regular phone users.

- Single and dual ear
- Left / right ear side compatible
- Ideal for all day comfort
- Weighted filter for clearer **Surround Shield™ ultra noise cancelling**
- Wideband enabled speakers
- Strong, robust construction
- Fitted with large **70mm leatherette ear cushions** for maximum all day comfort
- Optional **50mm leatherette ear cushions** included
- Adjustable headband
- 'Put and stay' ratchet microphone boom arm
- Supplied with quick disconnect system(QD) - QD compatible with Plantronics
- Headset weight with the 70mm ear cushions, ~ 62g / ~102g
- Protective **hard shell carry case** included
- Clothing clip & hanging hook included
- Compatible with all known office phones
- Full range of bottom leads available
- 24 Month repair or replacement warranty

NOTE: The bottom telephone connection lead is additional. Visit: <http://www.jpltele.com/jpl-compatibility.aspx> for our full headset bottom lead compatibility table.



JPL-CONNECT-1



JPL-CONNECT-2

TECHNICAL DATA

Microphone:

Impedance:	2.2kΩ
Sensitivity:	-32dB ± 3dB at 1kHz
Directivity:	Bi-directional
Frequency Range:	50Hz~20kHz ± 6dB
Distortion:	Less than 3%
Power Supply:	3V DC
S/N Ratio:	More than 58dB

Speaker:

Impedance:	150Ω ± 15% at 1kHz
Sensitivity:	93 ± 3dB at 1kHz 60mV Input
Max Input Power:	100mV
Frequency Range:	100Hz~6800Hz
Distortion:	Less 3% at 1kHz 60mV

Agency Approvals:

RoHS, CE, FCC



PLANTRONICS COMPATIBLE QD



HARD SHELL HEADSET CARRY CASE



SPARE 50mm EAR CUSHION, HANGING HOOK

Hard Shell Carry Case

The JPL CONNECT comes with a protective **hard shell carry case** to keep your headset safe whilst not in use. There is a small area inside the case to allow you to write your name.



Headset Hanging Hook

The JPL CONNECT comes with a headset hanging hook to enable you to keep your headset close at hand.

