



Universal 1080p HD 30fps webcam with integrated privacy lens cover and USB adapter



VISION Mini+

Universal 1080p HD 30fps webcam

Ideal for all webcam users from education to remote and business workers

Plug & play solution - No software or downloads needed

Integrated privacy lens cover

USB Type-A and USB Type-C connectivity using the USB adapter included

Compatible with all computers (Mac or PC) and softphones

Dual stereo full duplexed microphones for smooth natural conversations

Built-in camera in-use LED indicator

Multi-angled desk mount / monitor mount (as well as tripod fixing screw option on the base) giving full 360° camera rotation and 90° camera forward tilt

24 Month warranty



USB-A to USB-C adapter included



Optional mounting suggestion. Tripod not included



Universal 1080p HD 30fps webcam with integrated privacy lens cover and USB adapter



VISION Mini+

The JPL Vision Mini+ 1080p USB webcam comes with a full HD glass lens, integrated privacy lens shutter and a USB-A to USB-C adapter to allow optional connection to any USB-C device.


The webcam has a tri-fold hinged bracket with a gripper foot so it can be placed securely above your computer or laptop to allow long distance face to face meetings from your conference room or home office.

Compatible with all major softphones. Plug & play solution - No additional software or downloads needed.



Overview

| | |
|----------------|--|
| Features | 1080p HD 30fps CMOS Camera |
| | Full HD 1080p glass lens - No optical distortion |
| | Integrated privacy lens cover |
| | Hybrid work solution for the office, home, school or university |
| | Two full duplexed microphones - Built in dual stereo |
| | Built in camera in-use LED indicator |
| | USB 2.0 Type-A connectivity |
| | USB Type-C connectivity with USB-A to USB-C Adapter included |
| | Desk mount, monitor mount or tripod option |
| | Full 360° camera rotation including 90° tilt for over desk viewing |
| | Automatic low-light correction |
| | AEC – Automatic Echo Cancellation |
| | ANS – Automatic Noise Suppression |
| Certifications | UKCA, CE, FCC, RoHS, REACH |
| Dimensions | 72 x 33 x 31.7mm |
| Warranty | 24 Month repair or replacement warranty |
| MOQ | Master Shipping Carton: 40 |
| SKU: | 575-368-001 |
| EAN: | 5060126958833 |



Technical Data

| | |
|-------------------------------|--|
| Camera parameters: | |
| Total Pixels | 2 million pixels |
| Lens size | 1/2.7 inch |
| Aperture | 2.5±5% |
| Image area | 5.85mm x 3.27mm |
| Maximum effective pixel | 1920 (H) x 1080 (V) 2.0 million pixels |
| Output image format | MJPEG and YUY2 |
| Field of view | 67°(W) |
| AIC | Automatic Exposure (AE), Auto White Balance (AWB) Dynamic Black Level Calibration (ABLCL) |
| Resolution @ 30fps | 1920 x 1080, 1280 x 720, 640 x 480 |
| Microphone parameters: | |
| SNR | ≥60dB |
| Sensitivity | -42±3dB(0dB=1V/pa,1KHz) |
| Far-field distance | 0~2 meters |
| Horizontal voice pickup | Horizontal 180° |
| Communication mode | Full Duplex |
| AIC | Automatic: gain control, noise reduction control and echo noise reduction control |
| Other parameters: | |
| Interface type | USB 2.0 Type-A or USB Type-C |
| Voltage | 5V/500mA |
| OS Support | Win 2000/XP/Vista/Win 7/Win 8/Win 10, Win CE with UVC, Linux with UVC (above Linux - 2.6.26) Mac OS X 10.4.8 or later, Android 4.0 with UVC |
| Size (camera / gift box) | 72 x 33 x 31.7mm / 105 x 70 x 70mm |
| Weight (camera / gift box) | 106g / 150g |