## DATA SHEET



## Ascom d83 DC3 Desktop Charger

## Features

- Handset can automatically clear call history and messages when put in charger
- Handset can automatically send absent indication while in charger
- Handset can automatically enable loudspeaker during call while in charger
- Easy to wipe clean



## **Technical Specifications**

Physical		
Dimensions (I x w x h):	110 x 95 x 55 mm	
Weight:	190 g (excl. power adapter)	
Material:	Case: PC/ABS Rubber feet	
Color:	Black	
Functional		
Supply voltage:	100 - 240 V, 50 - 60 Hz AC (adapter), 5 V DC (charger)	
Charge current:	0.65 A	
Environmental		
Operating temperature:	+5°C to +40°C (41°F to +104°F)	
Storage temperature:	-20°C to +65°C (-4°F to +149°F)	
Enclosure protection:	IP30, IEC EN 60529	
Immunity to electromagnetic fields:	3 V/m EN61000-4-3	
Immunity to ESD:	4 kV contact discharge and 8 kV air discharge (EN61000-4-2)	
Compliance to European and UK Regulations and Standards		
EU directives and regulations:	2015/863 (RoHS3) amending directive 2011/65/EU EMC 2014/30/EU LVD 2014/35/EU	
UK regulations:	RoHS in Electrical and Electronic Equipment Regulations 2012 Electromagnetic Compatibility Regulations 2016 The Electrical Equipment (Safety) Regulations 2016	
Product Marking:		
Safety:	62368-1	
EMC:	55032, 55035, 61000-3-2, 61000-3-3	
Compliance to US and Canadian Regulations and Standards		
Product Marking:		
Safety:	UL 62368-1 CSA 62368-1	
EMC:	FCC CFR 47 Part 15	

Specifications are subject to change without notice

Compliance to Australian and New Zealand Regulations and Standards	
Product marking:	
Safety:	AUS/NZS 60950–1
EMC:	55032, 55035, 61000-3-2, 61000-3-3

Specifications are subject to change without notice

Ascom (Sweden) AB

Grimbodalen 2 SE–417 49 Göteborg Sweden Phone +46 31 55 93 00 www.ascom.com

