

# CP2503G



## Go Color, Go Giga, Go Green with paperless keys



- 2.8" TFT color display for easy access to a set of true business features through an intuitive interface
- Paperless programmable keys to quickly spot and reach your top features and contacts
- Access to large local and network phonebooks for enhanced contact management
- Headset and EHS\* support for convenient conversations in office environments
- Gigabit ports to make the most out of your network
- Embedded VPN client for secure remote connections

Sales & Marketing Department for SWISSVOICE brand : ATLINKS Europe 147, Avenue Paul Doumer- 92500 Rueil

147, Avenue Paul Dourner- 92500 Rueil Malmaison-France. SWISSVOICE INTERNATIONAL SA is an anonymous company capitalized at CHF380.000. Registered under no. CHE-433.189.538 in the Geneva Trade and Business Register. The manufacturer reserves the right to change product features to deliver technical improvements or comply with new regulations. Swissvoice is a trademark of Swissvoice

Swissvoice is a trademark of Swissvoice International SA. ©Copyright Swissvoice International SA 2017. Reproduction

prohibited. Non binding photos

#### **Main Features**

- 2.8", 320x240 TFT color display
- 4 sip accounts •
- Power over Ethernet Full duplex hands-free •
- Wideband audio
- RJ9 headset port and headset key \*EHS support for Plantronics headsets through ADP-80 •
- Call log: 100 entries (received, dialed, missed)
- Phonebook: local (500 entries, downloadable), XML.
- LDAP, black and white lists
- Programmable paperless keys
- Caller ID (name & number)
- Multiple built-in languages on WUI and phone MMI

#### Function Support

- Call waiting, call swap, up to 10 call handling
  - 8 paperless programmable line/function keys with
  - tricolor backlight (up to 28 virtual keys)
- 4 customizable softkeys
- Programmable shortcuts in all hardkeys Visual indicators (LED or on/screen: incoming call,
- MWI, mute, headset, no service)
- Mute, hold, transfer, call forward, call deflection, redial.
- 3-way conference

•

- 9 built-in melodies
- Do Not Disturb (per line and per phone), keypad lock
- Auto answer (per line)
- Volume control (handset, speakerphone, headset and ringers)
- Peer-to peer mode, IP Call
- Dial plans, prefix replacement, call barring
- Anonymous call, ACR •
- XML browser, action urls, click to talk •
- Keypad lock •
- Hot line
- Hot desking

#### IP PBX Integration

- Voicemail access, MWI
- Network conference •
- BLF (list/extension)
- DND&CF sync, SCA •
  - Intercom, music on hold, multicast paging
- Call park, pickup
- Call completion
- Country call progress tones
- Distinctive ringing
- **VIP** melodies

#### Keypad

- 4 customizable softkeys
- 5 way navigation key (configurable shortcuts for idle mode) .
- Hold, transfer, conference, phonebook and call history keys
- Redial, access to voicemail keys

**Commercial References** 

PSU for CP2502/CP2503/CP2503G (EU): 3700601418415

CP2503G: 3700601418392

Volume up and down, mute, hands-free and headset keys

### **Technical Specifications**

- VoIP Protocol Support:
- SIPv2 (RFC3261)
  - Voice Features:
- G722, G711A, G711u, G723.1, G726-32, G729ab - Wideband audio
- Voice Activity Detection, Comfort Noise Generation, Acoustic Echo Cancellation, Packet Loss
- Concealment, Adaptive Jitter Buffer (300ms), AGC
- Full duplex hands-free with AEC, 96ms tail length
- DTMF: In band, RFC2833, SIP Info
- Network Features:
  - DHCP/Static/PPPoE
  - DNS Srv, STUN, NTP
  - 802.1x, LLDP - Port mirroring
- QoS 802.1p/Q, ToS/DSCP
- Security Features:
  - TLS, SRTP, HTTPS
  - VPN: L2TP (Basic Unencrypted) / OpenVPN
  - Config file AES encryption
  - 2 level access privileges (user/admin)
  - Password dial and Certificate management
- Industrial Standard Certifications: CE

#### Configuration & Management

- IP address Assignment:
- DHCP, static IP, PPPoE Configuration Support:
  - Keypad
  - Web browser management (Admin/User), HTTP/HTTPS
  - Autoprovision with PnP, HTTP/HTTPS/TFTP/FTP, APRT support
  - One-click config file generation, config restore
  - TR069
  - Pcap tracing, syslog

#### Physical & Environmental

- Mounting:
  - Adjustable multiposition foot stand: 2 - Desk top and wall mountable
- Power over Ethernet:
- 802.3af
- Power Adaptor:
- AC100-240V input, 5Vdc/1000mA output (not included, order separately)
- Power Consumption: - 1.7-5.7W
- Operating temperature:
- From 0° to 40°C
- Operating Humidity:
- 10% to 60% non-condensing Storage temperature:
  - Up to 50°C

#### Interfaces

- 2 RJ-45 auto sensing 10/100/1000 Mps (LAN/PC)
- 1 RJ-9 port for handset connection
- 1 RJ-9 port for headset connection
- 5Vdc power jack



www.swissvoice.net