

## Yealink WF50(V1) Dual-Band Wi-Fi USB Dongle



Product Name: Yealink WF50(V1) Dual-Band Wi-Fi USB Dongle

Manufacturer: Yealink Model Number: WF50(V1)

Please Note: This is an updated version of this product and the compatibility has now changed. Please see the list of compatible Yealink phones in the description below.

Yealink WF50(V1) Dual-Band Wi-Fi USB Dongle

The Yealink WF50 is a next-generation Wi-Fi USB Dongle, designed to allow users to select whether to connect to a 2.4GHz (150 Mbps) Wi-Fi network or a 5GHz (up to 433 Mbps) Wi-Fi network.

Yealink WF50 Key Features

� Compatible with Yealink SIP-T42U/T43U/T46U/T48U (108.86.0.70 or later), SIP-T53 (96.86.0.70 or later)

� Dual-Band Connectivity

تزير High Transmission Rate

ï¿⅓ Interference Free

� Reliable Connection

� Easy to Use

ï¿1/2 Plug and Play

With wireless connections transmitting over the 5GHz band, users no longer need to worry about the interference from nearby wireless devices, guaranteeing high-quality connections perfect for establishing calls and HD video streaming. This dynamic plug-and-play style USB device is equipped with WPA/WPA2 encryptions, providing your network with active defence against security threats. It establishes Wi-Fi connectivity easily, quickly, and reliably, so that users can optimally communicate, collaborate and more. Yealink WF50 is compliant with IEEE 802.11a/b/g/n/ac standard, maximising reliability and throughput.

Yealink WF50 Technical Specifications

General

� Network Standard: IEEE 802.11 a/n/ac, IEEE 802.11 b/g/n

าั¿½ Transmission Rate 5GHz: - 11ac: Up to 433Mbps(dynamic) - 11n: Up to 150Mbps(dynamic) -

11a: Up to 54Mbps(dynamic)

าั¿½ Transmission Rate 2.4 GHz - 11n: Up to 150Mbps(dynamic) - 11g: Up to 54Mbps(dynamic) -

11b: Up to 11Mbps(dynamic)

ï¿1/2 Frequency Range: 2.4GHz/5GHz

 $\ddot{\imath}$  OS Support: Linux, Android

� Antenna Type: Integrated

آزر Security: WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPA2-Enterprise

ï¿1/2 Interface: USB 2.0

ï¿1/2 Operating Voltage: 5.0 V DC ±5%

� Operating Voltage: 5.0 V DC ±5%

� Dimensions (L\*W\*H): 52mm\*27mm\*8mm

تزير Weight: 28 g

آزا 2 Operating Temperature: -10°C ~ +50°C ( 14°F ~ 122°F)

Ti.1/2 Storage Temperature: -30°C ~+70°C (-22°F ~ 158°F)

าั¿½ Operating Humidity: 10% to 90% (Non-condensing)

Price: £34.00



## Yealink WF50(V1) Dual-Band Wi-Fi USB Dongle