

Algo 1128I - Algo Clear LED Strobe Light



Product Name: Algo 1128I - Algo Clear LED Strobe Light

Manufacturer: Algo

Model Number: Algo-1128I

Algo 1128 Analog Strobe Light

The Algo 1128 24V Analog Strobe Light serves as a clear/white visual alert for telephone ringing, specifically addressing noise sensitivity or hearing impairment concerns. Additionally, it is widely utilized for safety, security, and emergency event notifications.

Algo-1128 Analog Strobe Light Key Features:

- 1/2 Strobe Alert Notification System utilizing analog technology.
- 1/2 Long-life LEDs with 360 x 180 degree visibility from wall/ceiling mount.
- 1/2 34+ years of continuous use with zero light degradation.
- 1/2 Rated at 643 lumens with a maximum luminous intensity of 198 candela

The 1128 can be activated through an analog station / FXS port or ATA. It can also be triggered by dry contact closure input or auxiliary input detection of 3-30V AC or DC. Moreover, it supports audio detection from the Algo 1825PM Duet Plus analog loud ringer.

Algo-1128 Technical Specifications

Power

• 1/2 Power input: 12VDC 750 mA or 24VDC 375 mA

• 1/2 Power supply shipped: AC Mains Adapter 120V/230V

Optical

• 1/2 8 LEDs (White)

• 1/2 16 Selectable flash patterns using 4 position switch

• 1/2 198 Cd

• 1/2 643 Lumens

Input/Output

• 1/2 Relay Input: Max 1 kOhm

• 1/2 Ring Input: 20/25 Hz 20Vrms minimum

• 1/2 Auxiliary Input: 3-30V DC or AC (rms)

Environmental & Mechanical

• 1/2 Environmental: -20 to +50°C (-4 to +122°F); 10-95% RH, non-condensing. Dry indoor location only unless wiring cavity protected from water ingress using supplied gaskets or other protective measures.

• 1/2 Dimensions (Product): 4.8" x 4.8" x 3" (12.2cm x 12.2cm x 7.6cm)

• 1/2 Weight (Product): 1.0 lbs (0.5 kg) / Weight (Shipping): 1.7 lbs (0.8 kg)

Compliance

• 1/2 RoHS, CE, FCC, CSA/UL (USA & Canada), EN60950

Algo 1128l - Algo Clear LED Strobe Light

Price: \$469.87
