

Snom M400 and Snom M30 DECT Bundle



Product Name: Snom M400 and Snom M30 DECT Bundle

Manufacturer: Snom

Model Number: M430-UK

Snom M400 and Snom M30 DECT Bundle

The Snom M400 Dect single-cell base provides a comprehensive set of business telephony features, supporting up to 10 simultaneous calls (narrowband) with a maximum of 20 handsets. Cloud and VoIP PBX partners can benefit from convenient features like remote maintenance and zero-touch setup.

Snom M400 and Snom M30 DECT Bundle Key Features:

- Up to 10 simultaneous calls
- Up to 20 handsets
- Wireless software updates for handsets (OTA)
- Security

The M400 base adheres to the latest encryption standards and shares the same software and security update architecture as the Snom M900 multi-cell system. This ensures robust security and seamless integration across different Snom products, offering a reliable and scalable solution for businesses seeking advanced communication capabilities.

Snom M400 and Snom M30 DECT Bundle Technical Specifications

Basics

- Colour black
- Drop tested up to 2 m
- Product numbers
- M30 | DECT handset | EU & UK | PN 00004607

Dimensions and weight

- Dimensions (L x W x H, approx.)
- 128 mm x 53 mm x 25 mm
- Weight (approx.)
- Handset: 82 g
- Battery & belt clip: 30 g

Display and indicators

- Display
- TFT liquid crystal display (LCD), high colour, backlit
- 2" (51 mm) display size (diagonal)
- Resolution 176 x 220 pixel
- LED indicators
- 1 tricolour LED for missed calls / new voice messages, low battery

Keypad and function keys

- 28 hard keys in total
- Standard ITU telephone keypad: 12 keys with star and pound/hash key, backlit
- 5-way navigation key
- 3 context-sensitive function keys
- 4 programmable line / function keys
- 4 dedicated audio keys

Snom M400 and Snom M30 DECT Bundle

- Mute (navigation key: left), Speakerphone, Volume + (navigation key: up), Volume - (navigation key: down)

- 3 dedicated function keys

- Offhook, Onhook, Menu

Audio devices and features

- Speakerphone mode

- HD audio

- Full duplex

- Audio codecs

- G.711 (A-law, μ -law), G.722, G.726

- Related features

- Built-in assignable ringtones

- Hearing aid compatible (HAC)

Interfaces and connections

- M30 charging cradle power options

- USB powering 5 V / 1 A

- Power adapter: 100 - 240 V AC / 50 - 60 Hz / 300 mA | 5 V DC / 1 A

- M30 handset power options

- Removable, rechargeable 3.7 V / 1,100 mAh / 4.1 W (Lithium-ion) battery, up to 350 h standby time, up to 22 h narrowband talk time, up to 14 h wideband talk time

- Wireless interfaces

- DECT1

User interfaces and setup

- Configuration and setup via menu-driven phone user interface (PUI)

- Languages

- Related features

- XML Minibrowser support for Snom DECT multicell systems

Directory support and call features

- Up to 2 simultaneous calls

- Directory support

- LDAP (server-based directory)

- Local directory with up to 100 entries

- Central directory on the base station

- Speed dialling via keypad: 8 numbers

- Redial (via dialed calls list)

- Caller identification (CLIP)

- Calling Line Identification Restriction (CLIR)

- Call waiting/swapping

- Auto answer

- Call diversion

- Do Not Disturb (DND) mode

- Mute microphone

- Hold

- Blind call transfer

- Attended call transfer

- 3-way local conferencing

- Call history lists of 50 missed, received, dialed calls

Snom M400 and Snom M30 DECT Bundle

1½ Voice message waiting notification
1½ Notification of missed calls

Price: 163.72EUR
