

Snom M400 and Snom M30 DECT Bundle



Product Name: Snom M400 and Snom M30 DECT Bundle

Manufacturer: Snom Model Number: M430-UK

Snom M400 and Snom M30 DECT Bundle

The Snom M400 Dect single-cell base provides a comprehensive set of business telephony features, supporting up to 10 simultaneous calls (narrowband) with a maximum of 20 handsets. Cloud and VoIP PBX partners can benefit from convenient features like remote maintenance and zero-touch setup.

Snom M400 and Snom M30 DECT Bundle Key Features:

� Up to 10 simultaneous calls

� Up to 20 handsets

12.1/2 Wireless software updates for handsets (OTA)

� Security

The M400 base adheres to the latest encryption standards and shares the same software and security update architecture as the Snom M900 multi-cell system. This ensures robust security and seamless integration across different Snom products, offering a reliable and scalable solution for businesses seeking advanced communication capabilities.

Snom M400 and Snom M30 DECT Bundle Technical Specifications Basics

� Colour black

� Drop tested up to 2 m

� Product numbers

� M30 | DECT handset | EU & amp; UK | PN 00004607

Dimensions and weight

� Dimensions (L x W x H, approx.)

 \ddot{i} 128 mm x 53 mm x 25 mm

� Weight (approx.)

ï¿1/2 Handset: 82 g

ï¿1/2 Battery & amp; belt clip: 30 g

Display and indicators

� Display

า๊¿½ TFT liquid crystal display (LCD), high colour, backlit

� 2" (51 mm) display size (diagonal)

� Resolution 176 x 220 pixel

� LED indicators

آذِرًا 1 tricolour LED for missed calls / new voice messages, low battery

Keypad and function keys

ï¿1/2 28 hard keys in total

12.1/2 Standard ITU telephone keypad: 12 keys with star and pound/hash key, backlit

ï¿1/2 5-way navigation key

ï¿⅓ 3 context-sensitive function keys

� 4 programmable line / function keys

� 4 dedicated audio keys



Snom M400 and Snom M30 DECT Bundle

� Mute (navigation key: left), Speakerphone, Volume + (navigation key: up), Volume - (navigation key: down) � 3 dedicated function keys � Offhook, Onhook, Menu

Audio devices and features

- ï¿1/2 Speakerphone mode
- HD audio
- ï¿⅓ Full duplex
- ï¿⅓ Audio codecs
- ï¿1/2 G.711 (A-law, μ-law), G.722, G.726
- � Related features
- � Built-in assignable ringtones
- i¿½ Hearing aid compatible (HAC)

Interfaces and connections

- ï¿⅓ M30 charging cradle power options
- � USB powering 5 V / 1 A
- � Power adapter: 100 240 V AC / 50 60 Hz / 300 mA | 5 V DC / 1 A
- � M30 handset power options
- $\ddot{\imath}_{2}$ Removable, rechargeable 3.7 V / 1,100 mAh / 4.1 W (Lithium-ion) battery, up to 350 h standby time, up to 22 h narrowband talk time, up to 14 h wideband talk time
- � Wireless interfaces
- ï¿⅓ DECT1

User interfaces and setup

- า๊¿½ Configuration and setup via menu-driven phone user interface (PUI)
- � Languages
- ï¿⅓ Related features
- ī స్ట్రీ XML Minibrowser support for Snom DECT multicell systems

Directory support and call features

- � Up to 2 simultaneous calls
- ï¿⅓ Directory support
- � LDAP (server-based directory)
- � Local directory with up to 100 entries
- � Central directory on the base station
- � Speed dialling via keypad: 8 numbers
- ï¿1/2 Redial (via dialed calls list)
- � Caller identification (CLIP)
- � Calling Line Identification Restriction (CLIR)
- ï¿1/2 Call waiting/swapping
- � Auto answer
- � Call diversion
- ï¿1/2 Do Not Disturb (DND) mode
- � Mute microphone
- ï¿⅓ Hold
- � Blind call transfer
- ï¿⅓ Attended call transfer
- � 3-way local conferencing
- � Call history lists of 50 missed, received, dialed calls



Snom M400 and Snom M30 DECT Bundle

Price: £133.80