

Grandstream GWN7662 Indoor Wi-Fi 6 Access Point



Product Name: Grandstream GWN7662 Indoor Wi-Fi 6 Access Point

Manufacturer: Grandstream

Model Number: GWN7662

Grandstream GWN7662 Indoor Wi-Fi 6 Access Point

The Grandstream GWN7662 access point is an advanced 802.11ax Wi-Fi 6 solution designed for small to medium-sized businesses, retail, hospitality, and education. It employs 4x4 MU-MIMO on the 5G band and 2x2 MU-MIMO on the 2.4G band, enhancing network speed and coverage for crowded environments.

Grandstream GWN7662 Key Features:

- 5.38 Gbps wireless, 3.5 Gigabit wired speed
- 5GHz 4x4 MU-MIMO with DL/UL OFDMA
- Up to 175m coverage range
- Supports 256 Wi-Fi clients concurrently
- Advanced QoS for low-latency app performance
- Anti-hacking secure boot, data lockdown via signatures
- Self power adaptation for PoE/PoE+ detection
- Embedded controller manages 50 local GWN APs; GWN.Cloud offers unlimited AP management; GWN Manager has premise-based software control.

Its installation and management are streamlined through a controller-less approach with an embedded controller in the web interface. Compatibility with GWN.Cloud and GWN Manager offers versatile cloud-based and on-premise Wi-Fi management. Notably, it seamlessly integrates with Grandstream's Wi-Fi IP phones for reliable voice-over-Wi-Fi setups.

The GWN7662 supports advanced QoS, low-latency applications, mesh networking, and accommodates up to 256 clients per access point. With dual Gigabit network ports and PoE/PoE+ support, it's an ideal choice for medium-sized wireless networks requiring solid performance.

Grandstream GWN7662 Technical Specifications

Wi-Fi Standards

- IEEE 802.11 a/b/g/n/ac(Wave-2)/ax

Antennas

- 6 single frequency internal antennas
- 2.4GHz: 3.65dBi
- 5GHz: 5.26dBi

Wi-Fi Data Rates

5G:

- IEEE 802.11ax: 8.6Mbps to 4804Mbps
- IEEE 802.11ac: 6.5 Mbps to 3464 Mbps
- IEEE 802.11n: 6.5Mbps to 600Mbps
- IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

2.4G:

- IEEE 802.11ax: 8.6Mbps to 573.5Mbps
- IEEE 802.11n: 6.5Mbps to 300Mbps
- IEEE 802.11b: 1, 2, 5.5, 11 Mbps

Grandstream GWN7662 Indoor Wi-Fi 6 Access Point

IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

Frequency Bands

2.4GHz Radio: 2412 - 2484 MHz (WIFI)

5GHz Radio: 5180 - 5825 MHz

*Not all frequency bands can be used in all regions

Channel Bandwidth

2.4G: 20 and 40 MHz

5G: 20, 40, 80 and 160MHz

Wi-Fi and System Security

WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device

MIMO

2x2 2.4GHz (MU-MIMO)

4x4 5GHz (MU-MIMO)

Coverage Range

Up to 175 meters

*Coverage range can vary based on environment

Maximum TX Power

2.4G: 25dBm

5G: 27dBm

*Maximum power varies by country, frequency band and MCS rate

Receiver Sensitivity

2.4G:

802.11b: -96dBm @ 1Mbps, -88dBm @ 11Mbps;

802.11g: -93dBm @ 6Mbps, -75dBm @ 54Mbps;

802.11n 20MHz: -73dBm @ MCS7; 802.11n 40MHz: -70dBm @ MCS7;

802.11ax 20MHz: -60dBm @ MCS11; 802.11ax 40MHz: -58dBm @ MCS11

5G:

802.11a: -92dBm @ 6Mbps, -74dBm @ 54Mbps;

802.11n 20MHz: -74dBm @ MCS7; 802.11n 40MHz: -71dBm @ MCS7;

802.11ac 20MHz: -67dBm @ MCS8; 802.11ac HT40: -63dBm @ MCS9;

802.11ac 80MHz: -59dBm @ MCS9; 802.11ax 20MHz: -60dBm @ MCS11;

802.11ax 40MHz: -58dBm @ MCS11; 802.11ax 80MHz: -56dBm @ MCS11

Grandstream GWN7662 Indoor Wi-Fi 6 Access Point

SSIDs

• 32 SSIDs total, 16 per radio (2.4GHz & 5GHz)

Concurrent Clients

• 256

Network Interfaces

• 1x autosensing 10/100/1000 Base-T Ethernet Port
• 1x autosensing 10/100/1000/2500 Base-T Ethernet Port

Auxiliary Ports

• 1x Reset Pinhole
• 1x Kensington lock

Mounting

• Indoor wall mount or ceiling mount, kits included

LEDs

• 3 tri-color LEDs for device tracking and status indication

Network Protocols

• IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM

QoS

• 802.11e/WMM, VLAN, TOS

Network Management

• Embedded controller manages up to 50 local GWN APs
• GWN.Cloud offers free cloud management for unlimited GWN APs
• GWN Manager provides premise-based software controller for up to 3,000 GWN APs

Power and Green Energy Efficiency

• Supports 802.3az PoE 802.3af/ 802.3at;
• Maximum Power Consumption: 16W

Environmental

• Operation: -10°C to 45°C
• Storage: -30°C to 60°C
• Humidity: 5% to 95% Non-condensing

Physical Unit

Grandstream GWN7662 Indoor Wi-Fi 6 Access Point

Dimension: 205.3mm(L)x205.3mm(W)x45.9mm(H);
Unit Weight: 540g

Entire Package

Dimension: 258mm(L)x247mm(W)x86mm(H);
Entire Package Weight: 910g

Package Content

GWN7662 indoor Wi-Fi 6 Wireless AP
Mounting Kits
Quick Installation Guide

Compliance

FCC, CE, RCM, IC, UKCA

Price: £92.00