

Grandstream GWN7700P Unmanaged Network Switch



Product Name: Grandstream GWN7700P Unmanaged Network Switch

Manufacturer: Grandstream

Model Number: GWN7700P

Grandstream GWN7700P Unmanaged Network Switch

The Grandstream GWN7700 series introduces unmanaged network switches, providing a cost-effective method to add high-speed Gigabit connectivity to home offices and small/medium businesses. These switches require no configuration, offering a desktop or wall-mountable design with auto MDI/MDIX to eliminate crossover cable needs. Each port supports auto-negotiation, allowing compatibility with 10/100/1000Mbps devices.

Grandstream GWN7700P Key Features:

½ 5/8/16/24/48 Gigabit RJ45 ports

½ 4 port PoE+ output

½ Green technology reduces power consumption

½ LED Indicators;

½ Per port: Link/Activity/Speed

½ Per device: Power

½ Auto MDI/MDIX crossover for all ports

½ 802.3 af/at compliant Up to 30W on each port

½ Broadcast/Multicast/Unicast Storm Control (fixed to 100Mbps) to monitor traffic levels

½ Supports long cable connection

½ QoS - Supports Default Strict Priority when present

The GWN7700 series of unmanaged network switches efficiently enhances connectivity. Its features like auto MDI/MDIX, and auto-negotiation cater to diverse networking needs, making it an ideal choice for various setups.

Grandstream GWN7700P Technical Specifications

General

½ Gigabit ports: 5

½ PoE ports: 4

½ Enclosure: Metal

Mounting

½ Desktop/ Wall-Mount

Standards and Protocols

½ IEEE 802.3i

½ IEEE 802.3u

½ IEEE 802.3ab

½ IEEE 802.3x

½ IEEE 802.1p

½ IEEE 802.3af

½ IEEE 802.3at

Port Feature

Grandstream GWN7700P Unmanaged Network Switch

5× 10/100/1000Mbps RJ45 Ports

AUTO Negotiation

AUTO MDI/MDIX

Network Media

1000Base-T/100Base-TX/10Base-T, Half/Full-Duplex

PoE Configuration

1~4 Ports 802.3 af/at compliant

Up to 30 W on Each Port, Total 60W Power Budget;

Overload to cut off the lowest-priority port.

Priority: Port 4 to Port 1

LED Indicators

Per port: Link/Activity Green

Per device: Power Green

Mac Address Table

2K

Switching Capacity

10Gbps

Jumbo Frame

9KB

Advanced Features

Mac Address Auto-Learning And Auto-Aging

IEEE 802.3x Flow Control

802.1p/DSCP QoS

IGMP:

IGMP Fast-Leave

IGMP Snoop

Route Port Autolearn

Query Refresh Member Port

Power Adapter

External 48-53.5VDC/1.22A

Max Power Consumption by Base System

2W (excluding PoE output power)

Environmental

Grandstream GWN7700P Unmanaged Network Switch

Operating Temperature: 0 to 40 °C (32 to 104 °F)
Storage Temperature: -20 to 60 °C (-4 to 140 °F)
Operating Humidity: 10% to 90% Non-condensing
Storage Humidity: 10% to 90% Non-condensing

Dimensions (L x W x H)

Unit: 145 x 80 x 27mm
Package: 230 x 190 x 51mm

Weight

Unit Weight: 0.26KG
Entire Package: 0.75KG

Package

1x Switch, 1x Power Adapter, 1x QIG

Compliance

FCC
CE
RCM
IC
UKCA

Price: £29.25