

## Grandstream GWN7702P Unmanaged Network Switch



Product Name: Grandstream GWN7702P Unmanaged Network Switch

Manufacturer: Grandstream

Model Number: GWN7702P

### Grandstream GWN7702P Unmanaged Network Switch

The Grandstream GWN7700 series introduces unmanaged network switches, providing a cost-effective method to add high-speed Gigabit connectivity to home offices and small/medium businesses. These switches require no configuration, offering a desktop or wall-mountable design with auto MDI/MDIX to eliminate crossover cable needs. Each port supports auto-negotiation, allowing compatibility with 10/100/1000Mbps devices.

### Grandstream GWN7702P Key Features:

- 16x 2.5G PoE+ output.
- Green tech reduces power use.
- LED Indicators for Link, Activity, Speed, and Power.
- Auto MDI/MDIX for all ports.
- Storm Control (fixed to 100Mbps) for traffic monitoring.
- QoS: Supports Default Strict Priority (when present).

The GWN7700 series of unmanaged network switches efficiently enhances connectivity. Its features like auto MDI/MDIX, and auto-negotiation cater to diverse networking needs, making it an ideal choice for various setups.

### Grandstream GWN7702P Technical Specifications

#### General

- 16x 2.5 gigabit ports, (8x PoE ports)
- Enclosure: metal
- Mount: Desktop/Rack mount

#### Standards and Protocols

- IEEE 802.3i
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3x
- IEEE 802.1p
- IEEE 802.3af
- IEEE 802.3at

#### Port Features

- 16/24x 10/100/1000Mbps RJ45 Ports
- AUTO Negotiation
- AUTO MDI/MDIX

#### Network Media

- 1000Base-T/100Base-TX/10Base-T, Half/Full-Duplex

#### PoE Configuration

- 1-8 Ports 802.3 af/at compliant
- Up to 30 W on Each Port, Total 138W Power Budget;
- Overload to cut off the lowest- s priority port.

## Grandstream GWN7702P Unmanaged Network Switch

1/2 Priority: Port 1 to Port 8

### LED Indicators

1/2 Per port: Link/Activity Green  
1/2 Per port: PoE output - Yellow  
1/2 Per device: Power Green

### Mac Address Table

1/2 8K entries

### Switching Capacity

1/2 32Gbps

### Jumbo Frame

1/2 10KB

### Advanced Features

1/2 Mac Address Auto-Learning And Auto-Aging  
1/2 IEEE 802.3x Flow Control  
1/2 Half duplex backpressure

### Power Adapter

1/2 Internal 100-240V AC, 50/60Hz, 150W

### Max Power Consumption by Base System

1/2 10.1W@220V/50Hz (excluding PoE output power)

### Environmental

1/2 Operating Temperature: 0 to 40 °C (32 to 104 °F)  
1/2 Storage Temperature: -20 to 60 °C (-4 to 140 °F)  
1/2 Operating Humidity: 10% to 90% Non-condensing  
1/2 Storage Humidity: 10% to 90% Non-condensing

### Dimensions (L x W x H)

1/2 Unit: 280 x 180 x 44mm  
1/2 Package: 366 x 211 x 53mm

### Weight

1/2 Unit: 1.58KG  
1/2 Entire Package: 2.18KG

### Package

1/2 1x Switch  
1/2 1x 1.2m AC Cable

## Grandstream GWN7702P Unmanaged Network Switch

1x Quick Installation Guide (QIG)  
1x Rack-mounting Standard Brackets  
4x Rubber Feet

### Compliance

FCC  
CE  
RCM  
IC  
UKCA

**Price: 103.15EUR**

---