

Grandstream GWN7002 Multi-WAN Gigabit Router



Product Name: Grandstream GWN7002 Multi-WAN Gigabit Router

Manufacturer: Grandstream Model Number: GWN7002

Grandstream GWN7002 Multi-WAN Gigabit Router

The Grandstream GWN7000 Series comprises Multi-WAN Gigabit VPN routers featuring integrated firewalls. These routers enable businesses to establish extensive wired, wireless, and VPN networks across single or multiple sites.

Grandstream GWN7002 Key Features

 \ddot{i} 1x GbE RJ45 port with IEEE 802.3af/at PoE Input and 2x GbE RJ45 ports with 48V Passive PoE output or IEEE802.3af

- រ៉េ្ស Supports multiple Gigabit RJ45 ports and Gigabit SFP ports
- าั¿½ Built-in VPN support allows easy access to corporate networks for remote employees
- Ti2/2 Multiple WAN ports with load balancing and failover to maximize connection reliability
- าั¿½ Rich firewall features including DDNS, port forwarding, DMZ, UPnP, Anti-Dos, traffic rules, NAT and ALG
- าั¿½ Supports application/protocol monitoring and traffic statistics with Deep Packet Inspection (DPI)
- آذِيًّ Advanced QoS to ensure real-time performance of low-latency applications
- าั¿½ Supports application, URL, DNS, and web content filtering to block access from unsecure contents
- آذِ½ Embedded controller can manage itself and up to 150 GWN APs; GWN.Cloud offers a free cloud management platform for unlimited routers and GWN APs

The GWN7002 is an excellent fit for diverse deployments, serving small-to-medium businesses, educational institutions, healthcare facilities, and beyond. With its high-performance routing, integrated VPN capabilities, robust security features, and user-friendly management tools, the GWN7002 is a reliable and adaptable networking solution.

Featuring 2 Gigabit SFP ports, 4 Gigabit Ethernet ports, and 2 PoE output ports, the GWN7002 offers versatile connectivity. It can manage up to 150 GWN Series Wi-Fi Access Points via an embedded controller and is compatible with Grandstream's GWN.Cloud and GWN Manager tools for streamlined network management.

Grandstream GWN7002 Technical Specification CPU

� Dual ARM Cortex A53 1GHz

Memory and NAT Sessions

تزار 256MB RAM, 256MB Flash, 30K NAT sessions

Network Interfaces

تزرير 2x Gigabit SFP ports and 4x Gigabit Ethernet ports (WAN/LAN configurable)

NAT Throughput and IPsec VPN Throughput

� NAT Throughput: 2.2Gbps � IPsec VPN Throughput: 530Mbps

Auxiliary Ports and Mounting

� 1x USB 2.0 port, 1x Reset Pinhole



Grandstream GWN7002 Multi-WAN Gigabit Router

17.1/2 Mounting: Desktop and wall mounting

LEDs

าั¿½ 8 x single-color LEDs for device tracking and status indication

Connection Type and Network Protocols

� DHCP, Static IP, PPPoE, PPTP, L2TP

 \ddot{i} Network Protocols: IPv4, IPv6, IEEE802.1Q, IEEE 802.1p, IEEE802.1x, IEEE802.3, IEEE 802.3u, IEEE 802.3x, IEEE802.3ab

QoS (Quality of Service)

ï¿⅓ VLAN, TOS

าั¿½ Support multiple traffic classes, filter by port, IP address, DSCP, and policing

ï¿⅓ App QoS

آزٰ½ VoIP Prioritization

Firewall and Security

าั¿½ DDNS, Port Forwarding, DMZ, UPnP, Anti-DoS, traffic rules, NAT, ALG

12/2 Application/protocol monitoring and traffic statistics

ī¿½ Content filtering: Supports Application/URL/DNS/Web Content Filtering

ï¿1/2 Safe search

VPN

ï¿1/2 SSL VPN Server / Client-to-Site

ï¿1/2 IPsec VPN Client-to-Site / Site-to-Site

� PPTP VPN Server / Clien-to-Site

آزٰ½ L2TP Client-to-Site

� WireGuard (pending)

آذِ1/2 IPSec Encryption: DES, 3DES, AES

ï¿⅓ IPSec Authentication: MD5, SHA-1, SHA2-256

ī¿½ IPSec Key Exchange: Main/Aggressive Mode, Pre-shared Key, DH Groups 1/2/5/14

ϊ¿½ IPSec Protocols: ESPϊ¿½ IPSec NAT Traversal

ï¿1/2 SSL VPN Encryption: AES, DES

آذًا \$\ SSL Authentication: MD5, SHA-1, SHA2-256, SHA2-384, SHA2-512

ï¿1/2 SSL VPN Certificate: RSA

าั¿½ PPTP Encryption: MPPE 40-bit, 128-bit, IPSec าั¿½ PPTP/L2TP Authentication: MS-CHAPv1/2

Max Concurrent VPN Tunnels

� Up to 50 Tunnels

Network Management

าั¿1/2 GWN7002 embedded controller for self and up to 100 GWN APs

រី¿½ GWN.Cloud offers a free cloud management platform for unlimited GWN Routers and GWN APs

PoE Input



Grandstream GWN7002 Multi-WAN Gigabit Router

ï¿1/2 Standard: IEEE 802.3af/at

PoE Output

� 2x PoE out ports

ï¿1/2 Passive 48V or IEEE802.3af

PoE Power Budget

� 24V DC 1A: 12.8W � 24V DC 1.5A: 24.8W

Power & amp; Green Energy Efficiency

าั¿½ Universal power adaptor included: Input: 100-240VAC 50-60Hz, Output: 24V DC 1A (24W)

Environmental

� Operation: 0°C to 40°C � Storage: -30°C to 60°C � Humidity: 10% to 90% Non-condensing

Physical

าั¿½ Unit Dimension: 210mm(L)x130mm(W)x35mm(H); Unit Weight: 505g

าั¿½ Entire Package Dimension: 246mm(L)x235mm(W)x54mm(H); Entire Package Weight: 730g

Package Content

ï¿⅓ GWN7002 Router

� Universal Power Supply

ï¿1/2 Network Cable

� Quick Installation Guide

Compliance

۲¿½ FCC

CE ½'¿ï

ï¿⅓ RCM

IC ½iï

� UKCA

Price: \$64.63