

. (0)

Product Name: Yealink A30-CTP-WPP30 collabaration bar

Manufacturer: Yealink Model Number: A30-025

Yealink A30-CTP-WPP30 collabaration bar

The Yealink A30-CTP-WPP30 is an all-in-one video collaboration bar designed for medium-sized meeting rooms. With its impressive 8MP camera and a superwide-angle lens providing a 120° field of view, the A30 offers exceptional video quality. Additionally, it features advanced AI technologies such as Auto Framing and Speaker Tracking, ensuring a smarter and more secure video conferencing experience. The electric privacy shutter adds an extra layer of privacy control to your meetings. Equipped with 8 MEMS microphone arrays and Yealink's noise-proof algorithm, the A30 delivers outstanding audio quality, even in full-duplex mode, ensuring that everyone's voice is heard clearly. Its human body detection feature streamlines the meeting process, making it more convenient and efficient.

Yealink A30-CTP-WPP30 Key Features:

ï¿1/2 Smart Video Collaboration

� See Everyone Clearly

� Two cameras design with AI technology

า๊¿½ Precise Sound Localisation, Full-Duplex Experience

The Yealink MeetingBar A30 integrates a computing unit, camera, microphones, speaker, Wi-Fi, and Bluetooth, providing a straightforward deployment solution. This means you can set it up easily without the need for additional hardware or complicated installations. The A30 is compatible with popular cloud video platforms like Zoom and Microsoft Teams, eliminating the necessity for a dedicated PC or Mac. It also supports content sharing and whiteboarding, enhancing the collaborative and communicative aspects of your meetings. With its simplicity of deployment and powerful features, the Yealink MeetingBar A30 ensures excellent video collaboration performance in medium-sized meeting rooms.

Yealink A30-CTP-WPP30 Technical Specifications Dual Camera System(Wide Camera)

ï¿⅓ 8MP Camera

ï¿1/2 Field of view: 120°

ï¿1/2 4x e-PTZ Camera

Telephoto Camera

ï¿1/2 8MP Camera

� Field of view: 90°

� 10x Hybrid Zoom (3.5x optical, 3x digital)

تز½ Horizontal Rotation Angle: +25°/-25°

� Vertically Rotation Angle: +16°/-16°

� Electric Privacy Shutter

Intelligence Features

� Auto Framing � Speaker Tracking

Audio

� Built-in 8 MEMS microphone array



- ï¿⅓ Support extension mic
- � Two Built-in 5W high fidelity speakers
- ï¿1/2 Yealink Noise Proof Technology
- i¿1/2 Beamforming directed voice pickup technology
- ï¿⅓ Full-duplex
- � Echo cancellation

Operating System

ï¿⅓ Android 9.0

Meeting Features

- � Calendar
- ï¿⅓ One-click join
- � Meeting collaboration
- � Content sharing
- آز½ Whiteboard

Meeting control:

- ï¿1/2 Add participants
- ï¿⅓ Hold/Resume
- ï¿1/2 Camera On/Off
- ï¿⅓ Mute/Unmute
- ï¿⅓ Volume Up/Down
- ï¿⅓ Hang up

Teams Edition

- آز½ Microsoft DM
- ï¿⅓ Proximity join

Zoom Edition

- ï¿⅓ Zoom DM
- � Direct sharing

Video Standard and Network Suitability

تزاري Video codecs: H.264 High profile, H.264 SVC, H.264

Network and Security Features

- ï¿1/2 Built-in dual-band Wi-Fi (2.4GHz/5GHz)
- า๊ะ1/2 Built-in Bluetooth
- � IPv4 and IPv6, DHCP/static IP
- ï¿1/2 HTTP/HTTPS web server
- ï¿1/2 SRTP/TLS, AES 256-bit encryption
- ï¿1/2 QoS: 802.1p/q, Diff-serv
- ï¿⅓ VLAN, LLDP
- آذِ½ IEEE802.1X
- � EAP-MD5/EAP-TLS
- � PEAP-MSCHAPv2



� EAP-TTLS/EAP-MSCHAPv2

- � Network diagnosis: Ping, Trace route
- า๊¿½ Time and date synchronization using SNTP
- ï¿1/2 Built-in certificate
- าั¿½ Simple Certificate Enrollment Protocol (SCEP)* (coming soon)

Connections

- � 2 x HDMI output (CEC supported)
- تز½ HDMI input (through the VCH51 Sharing Kit)
- � 1 x Line-in (3.5mm)
- � 1 x Line-out (3.5mm)
- � 2 x USB 2.0
- � 1 x 10/100M/1000M Ethernet port
- � 1 x Yealink extension port (RJ-45)
- � 1 x Power port
- � 1 x Security lock slot
- � 1 x Reset slot

Other Physical Features

- آذ½ External Yealink Power Adapter: AC 100~240V input and DC 48V/0.7A Output
- ï¿1/2 USB Output: 5V 0.5A
- ī¿½ Power consumption (PSU): Idle < 13W; Normal operating: 15W; MAX: 16W
- آزار Dimension (W.D.H): 700 mm x 98 mm x 121 mm
- � Operating humidity: 10~95%
- � Operating temperature: 0~40°C
- ï¿1/2 Storage temperature: -30~70°C

MeetingBar A30 Package Content

- ï¿1/2 MeetingBar A30 endpoint
- ï¿⅓ 3m Ethernet cable
- � 2 x 1.8m HDMI cable
- ï¿⅓ Mounting Bracket and Accessories
- � Power adapter
- ï¿1/2 Quick Start Guide

Controller (optional):

- � CTP18 Touch Panel
- � VCR20 Remote Control

Content sharing (optional):

- � VCH51 Sharing Kit (HDMI/USB-C)
- ï¿1/2 WPP20 Wireless Presentation Pod

MeetingBar A30 + CTP18 Package

ï¿1/2 Carton Meas: 923*495*327mm



Price: 1,960.67EUR