

2N Clip Answering Unit



Product Name: 2N Clip Answering Unit Manufacturer: 2N Telecommunications

Model Number: 9138511

Please Note: Product comes without the stand.

2N Clip Answering Unit

The 2N Clip is a 4" video IP indoor station designed to offer high-quality video, convenience, and safety for mid-priced residential projects. It caters to the growing demand for more affordable housing without compromising on performance. Designed with the mid-range housing sector in mind, the 2N Clip delivers IP video, sleek design, and reliability, all at an accessible price point. 2N Clip Answering Unit

� Perfect for mid-range projects

� Fits seamlessly into the 2N ecosystem

� Doorbell button support

ï¿⅓ Increase security with IP video

ï¿⅓ Fast installation

The 2N Clip allows for easy remote management and configuration through the My2N Management Platform.Quick installation- just secure it to the wall with two screws and "clip" it in place. The 2N Clip is your cost-effective solution for bringing advanced video capabilities to your mid-priced residential project while ensuring a swift and straightforward setup. 2N Clip Answering Unit - Technical Specifications Power supply

� Type: PoE

� PoE: 802.3af Class 0, 48 V DC, 200 mA

User interface

� Controls: 3 capacitive buttons

ī¿½ Operation: press and hold the RESET button to restore factory settings

Audio

ï¿⅓ Microphone: integrated ï¿⅓ Speaker: integrated, 2W

� Integrated induction loop: optional

� Codecs: G.711a/u, G.722, G.729, L16/16 kHz

Video

� Display: 4.3" display � Resolution: 480x272 pixels

ï¿1/2 Codecs: H.264

Interface

ï¿1/2 LAN: 10/100BaseT, RJ-45

� Recommended cabling: Cat5e or higher

Doorbell input



2N Clip Answering Unit

� Input type: switching contact (button/relay)

� Contact type: normally open (NO) � Contact parameters: 12V/20mA, DC

Mechanical properties

ī¿½ Operating temperature: 0 to 50°C ī¿½ Storage temperature: -20 to 70°C

าั¿½ Relative operating humidity: 10 to 90% (non-condensing)

 \ddot{i} $\rlap{1}$ Recommended altitude: 0 to 2000 m \ddot{i} $\rlap{2}$ Dimensions: 124 (W) x 150 (H) x 28 (D) mm

ï¿⅓ Weight: 235 g

Price: £259.20