

## Yealink 6x Optical PTZ Camera Module for Yealink MeetingBoard



Product Name: Yealink 6x Optical PTZ Camera Module for Yealink MeetingBoard

Manufacturer: -

Model Number: MB-Camera-6X

Yealink 6x Optical PTZ Camera Module for Yealink MeetingBoard

The Yealink 6x Optical PTZ Camera Module The MB-Camera-6X represents an optical zoom camera specifically crafted for Yealink MeetingBoard's in medium and large meeting spaces. Featuring a tailored slot port design, this camera can be effortlessly mounted on the top of the MeetingBoard, streamlining the deployment process. The MB-Camera-6X, coupled with the MeetingBoard's integrated wide-angle lens, forms a sophisticated dual 4K camera solution enriched with Yealink's proprietary AI voice positioning and image algorithms. Yealink 6x Optical PTZ Camera Module Key Features:

- 1/2 Optical zoom camera for Yealink MeetingBoards in medium/large rooms
- 1/2 Customised slot port design for easy top installation
- 1/2 Dual 4K camera solution with MB-Camera-6X/12X and MeetingBoard's wide-angle lens
- 1/2 Yealink's AI voice positioning and image algorithms
- 1/2 Real-time participant analysis with wide-angle lens
- 1/2 AI-driven tracking: auto framing, speaker tracking
- 1/2 Swift 6X/12X optical lens activation for precise tracking
- 1/2 Consistent optimal viewpoint for HD, intelligent video experience

Leveraging the wide-angle lens, it continuously analyses the real-time positioning and actions of meeting participants. Subsequently, it activates the 6X optical lens to swiftly and precisely track and locate participants, enabling AI-driven tracking functionalities such as auto framing and speaker tracking. This ensures a consistently optimal viewpoint, delivering a high-definition, intelligent, and seamless video experience.

Yealink 6x Optical PTZ Camera Module Technical Specifications  
Specifications MB-Camera-6X

- 1/2 Pixel: 8 MP
- 1/2 Video Output: 4K/30FPS
- 1/2 Zoom Ratio: 6x optical zoom
- 1/2 Automatic Exposure: &radic;
- 1/2 Automatic White Balance: &radic;
- 1/2 Pan Range: &plusmn;100&deg;
- 1/2 Tilt Range: 0&deg; / -90&deg;
- 1/2 Auto Framing: &radic;
- 1/2 Speaker Tracking: &radic;
- 1/2 PiP Mode: &radic;
- 1/2 Presets: &radic;
- 1/2 Electric Privacy Shutter: &radic;
- 1/2 Physical Port: Yealink Custom Port
- 1/2 Installation Method: MeetingBoard Custom Slot

**Please Enquire**