



Product Name: Yealink CP965-W Microsoft Teams Main Unit Plus Wireless Mics

Manufacturer: Yealink

Model Number: CP965-W-Teams

Yealink CP965-W Microsoft Teams Main Unit Plus Wireless Mics

The Yealink CP965-W is the Yealink CP965 plus 2 wireless mics. The Yealink Teams CP965, an enterprise-grade conference phone, is specifically crafted for medium to large conference rooms, seamlessly extending the Teams experience and desktop functionality to the meeting space. Running on Android 11, its Teams user interface effortlessly combines ease of use with simplicity, achieving a harmonious balance between straightforwardness and sophistication. Featuring 12+1 built-in microphones equipped with Yealink's Optima HD Voice technology, the CP965 ensures a remarkably clear voice calling experience.

Yealink CP965-W Key Features:

آذِ HD Audio, Smooth Communication

� Easy-to-Use Design

า๊¿½ Efficient Provisioning and Management

Yealink CP965-W Technical Specifications **Audio Features** 

� Optimal HD audio

ī¿½ Audio codec: G722, G722.1C, G726, G.729, G.729A, G723, iLBC, Opus, PCMU (G.711A),

PCMA (G.711μ), SILK

� 20-foot (6-meter) microphone pickup range

� Apply to the medium to large conference room

าั¿½ Built-in 12-microphone array, 360-degree voice pickup

تز½ Built-in 1-microphone array, decrease noise

ï¿1/2 56mm diameter and 5w speaker

ï¿1/2 Full-duplex speakerphone with AEC

آزٰ Echo cancellation tail length is up to 320ms

ï¿1/2 Background noise suppression

#### Call Handling Features

� P2P call

� Cloud PSTN call

17.1/2 Call hold/Call mute/Call transfer/Call forward

� Group SimRing

ï¿1/2 Block calls without caller ID

#### Conference Features

� One-Click Join

17.1/2 Add a Participant to the existing meeting

� Conference Mute/Unmute participants

� Display Meeting Info

� Calendar access to my meetings

� Show acceptance status per participant

� Schedule Teams meeting



# Yealink CP965-W Microsoft Teams Main Unit Plus Wireless Mics

#### Presence and Contacts

- าั¿½ Presence status synchronizes with the client, Presence status control
- � Corporate Directory Access
- ï¿⅓ Show contact picture
- � Call history: placed/received/missed
- � Synchronized call logs

#### Phone Features

- ï¿⅓ Single sign-in
- � Visual voicemail
- � Change VM playback speed
- � Phone lock
- � Screensaver
- � Power Saving

#### Display and Indicator

- � 5" 720x1280 capacitive touch screen
- ï¿⅓ Volume key
- آذِ1⁄2 Home button
- 17.1/2 Multilingual user interface
- ï¿1/2 Modern Teams interface, Full keyboard
- آذِيً Presence status control: available, busy, DND, be right back, off work, away

### Interface

- � 1 x RJ45 10/100M Ethernet port
- آزار Power over Ethernet (IEEE 802.3af), class 4
- า๊ะไน Built-in dual band Wi-Fi
- � Built-in Bluetooth 4.2 (Pending)
- ï¿1/2 1 x USB 2.0 Type-A device port
- ï¿1/2 1 x USB 2.0 Type-C device port
- � 1 x Security slot

#### Management

- īപ്ര് Configuration: browser/phone/Auto provisioning and Device Management Platform
- 12/2 Provisioning priority management
- � Auto Provisioning via Activation Code
- آذً Yealink Redirection and Provisioning Service (RPS)
- � QoE (Monitoring Reports)
- ï¿1/2 Reset to factory, reboot
- � Package tracing export, system log
- ï¿1/2 Screenshot via URL
- � View license status
- 17.1/2 Supports Microsoft Device Management Platform
- า๊¿½ Supports Yealink Device Management Platform
- � Supports Unify Square Device Management Platform

#### Network and Security



## Yealink CP965-W Microsoft Teams Main Unit Plus Wireless Mics

� SIP v1 (RFC2543), v2 (RFC3261)

ï¿⅓ IPv4/IPv6

ï¿⅓ IP Assignment: Static/DHCP ï¿⅓ HTTP/HTTPS web server

า๊ $_{c}$  $\frac{1}{2}$  Time and date synchronization using SNTP

า๊¿½ SRTP for voice, Transport Layer Security (TLS1.3)

ï¿⅓ HTTPS certificate manager

ï¿⅓ IEEE802.1X

#### Other Physical Features

� Color: Black

� External Yealink PoE adapter (optional)

� Power consumption (PoE): 7.3W-20W

� Dimension (W\*D\*H): 328 mm\*322 mm\*62 mm

� Operating humidity: 10-90%

� Storage temperature: -10-40°C (+14~104°F)

**Price: 672.91EUR**