



Product Name: Snom HD101 Hotel/Hospitality Phone

Manufacturer: Snom Model Number: HD101

#### Snom HD101 Hotel/Hospitality Phone

The Snom HD101 is a sleek and comfortable telephone for modern hotel and guest rooms. It provides guests with maximum freedom of movement through a cordless DECT handset, offering essential features such as speed dialling for all hotel facilities and rooms, hands-free calling, hold, and mute functions.

snom HD101 Key Features

ï¿1/2 Hotel / hospitality features

� Cordless DECT handset

� Power over Ethernet (PoE)

ï¿⅓ HD audio

ï¿⅓ Anti-bacterial housing

� Large LED call indicator

� Up to 4 handsets

Additionally, it can be expanded with up to 3 extra DECT handsets of the HD1 type. With PoE power supply and Gigabit Ethernet connectivity, the device seamlessly integrates into a centrally managed, future-proof network infrastructure.

All HD101 settings can be conveniently managed centrally. Its antibacterial housing safeguards against germs and is easily cleanable. The device is equipped with prominent visual LED call and message indicators, along with customizable labelling options, enhancing the overall user experience.

Snom HD101 Technical Specifications

**Basics and Equipment** 

� Product Information

17:1/2 Guest Room Phone | Cordless DECT Handset

� PN 00007001

� Colour: Gunmetal Black

ï¿⅓ Anti-bacterial Housing

ï¿⅓ Equipment

ï¿⅓ Sturdy, Solid Construction

ī సైస్ట్ Fully Customisable Faceplate for Hotel Branding and Dialing Instructions

ī¿½ Placement: Indoor, Desktop, Nightstand, Wall Mounting

### Dimensions and Weight

� Dimensions (H x W x D, approx.)

ī¿½ Cordless DECT Handset on the Base Cradle (Desk Mounted): 79 mm × 176 mm × 163 mm

าั¿½ Cordless DECT Handset on the Base Cradle (Wall Mounted): 79 mm × 78 mm × 211 mm

� Weight (approx.)

าั¿1/2 Cordless DECT Handset on the Base Cradle: 645 g

### Indicators and Keys

آذِ2 6 LED Indicators

� Cordless DECT Handset

า๊¿½ Flash/Talk Key Indication: 1 Red LED



- Title Mute Status Indication: 1 Red LED
  Title Speakerphone Mode: 1 Red LED
  Title Status Indication: 1 Red LED
- تز½ Hold Status Indication: 1 Red LED
- � Telephone Base
- آذًا 2 Call Status Indication | Message Waiting Indication (MWI): 1 Red LED
- ï¿⅓ 31 Hard Keys in Total
- � Cordless DECT Handset
- าั¿½ 12 Keys (Standard ITU Telephone Keypad), Backlit

าั¿½ Low Battery Indication | Charging Indication: 1 Red LED

- � 4 Dedicated Audio Keys: Mute (with Red LED), Speakerphone (with Red LED), Volume + / (Rocker)
- า๊¿1/2 2 Programmable Function Keys: Speed Dialling
- � 5 Dedicated Function Keys: Talk (with Red LED), Emergency, Offhook, Hold (with Red LED), Message
- � Telephone Base
- ī సై 3 Dedicated Audio Keys: Speakerphone (with Red LED), Volume +, Volume -
- าั¿1/2 4 Programmable Function Keys: Speed Dialling
- � 1 Dedicated Function Key: Handset Localisation

#### Audio Devices and Features

- � Telephone Base
- � Casing Microphone
- � Casing Speaker
- آزار Speakerphone Mode (via Dedicated Function Key)
- ï¿1/2 Cordless DECT Handset
- ï¿⅓ Microphone
- آز½ Handset Earpiece
- � Speakerphone Mode (via Dedicated Function Key)
- ï¿⅓ Hearing Aid Compatible (HAC)
- � Built-in Assignable Ringtones

### Interfaces and Connections

- � Power Options
- � Telephone Base
- � Power over Ethernet (PoE)
- ï¿1/2 IEEE 802.3af, Class 2
- � Power Adapter
- � 1 100-240 V AC / 50/60 Hz / 500 mA | 5 V DC / 2 A
- � Cordless DECT Handset
- آذًا Battery AAA-NiMH, 2.4 V, 550 mAh, Preinstalled, Removable, Rechargeable
- � Up to 7 Hours Talk Time
- าั¿1/2 Up to 120 Hours Standby Time
- � Up to 16 Hours Charging Time

### Wired Interfaces

- ï¿1/2 Ethernet 1 Gbit/s: RJ45-8P8C Socket
- 12/2 Power Adapter: 1 Coaxial Power Connector (Socket)

#### Wireless Interfaces

- � DECT
- ï¿1/2 DECT Technology and Features



ï¿1/2 Standard: DECT

ï¿1/2 Handsets: Up to 4 Total

� Wideband Audio

تزار Easy Registration to Compatible Base Stations

### Networking Technologies and Protocols

� VLAN Support ï¿⅓ SIP (RFC 3261)

### Administration Interfaces and Setup

าั¿1/2 Configuration and Setup via Voice Menu

าั¿½ Configuration and Setup via Menu-Driven Web User Interface (WUI)

าั¿½ Advanced SIP Configuration Tool for Easy Mass Deployment and Phone Monitoring

า๊¿½ Secure Redirection And Provisioning Service (SRAPS) Support

#### Call Features

ï¿1/2 1 SIP Identity / Account

� Speed Dialling via Function Keys

าั¿½ Mute Microphone (via Dedicated Function Key)

ï¿⅓ Hold (via Dedicated Function Key)

� Multicast Paging

ī¿½ Quick Call Answer (by Simple Pick-Up from the Base/Charger)

### Interoperability

រ៉េ $^{1}$ 2 Interoperable with All Major IP-PBX Platforms

### **Environmental Conditions**

าั¿½ Operating Ambient Temperature: 5 °C - 45 °C

� Humidity (Non-condensing): 5% - 95%

### Package Contents

تز½ Hardware

� Telephone Base

� Cordless DECT Handset

آزٰ½ Footstand

تز½ Wall Mount Kit

� 2 Ethernet Cables:

ï¿1/2 Cable Length (Approx.): 140 mm | 2 m

� Documentation

� Quick Installation Guide (QIG)

Snom Accessories and Compatible Devices



� DECT Handset & DECT Handset & Charging Cradle

ï¿1/2 Up to 3 × HD1 (PN 00007002)

ï¿1/2 Power Adapter

ï¿⅓ Telephone Base PSU

� EU: PN 00004687 � UK: PN 00004688 � AU: PN 00004689

ï¿1/2 Charging Cradle PSU

� EU: PN 00004683 � UK: PN 00004684 � AU: PN 00004685

Price: £96.00