

Fanvil i66 Face Recognition Door Phone



Product Name: Fanvil i66 Face Recognition Door Phone

Manufacturer: Fanvil

Model Number: i66

Fanvil i66 Face Recognition Door Phone

The Fanvil i66 Face Recognition Door Phone boasts a 4-inch IPS colour screen and integrates advanced face recognition technology for precise identification. It ensures heightened security with anti-spoofing liveness detection, detecting fake images, videos, and masks effectively.

Fanvil i66 Face Recognition Door Phone Key Features:

- 4-inch IPS colour screen with clear and intuitive interface

- Equipped with the latest face recognition technology and anti-spoofing algorithms, ensuring community security

- Independently developed voice intelligent noise reduction algorithm ensures clearer audio and video calls

- Aluminium alloy casing design, showcasing high-end quality

- Supports the standard ONVIF protocol, providing high flexibility and excellent compatibility

- IP66/IK07 high protection rating, enhancing the lifespan and stability of the product

Moreover, it enables seamless audio and video communication through IP phones, indoor stations, or a mobile app. Offering various door opening options, it is ideal for enhancing security in communities, apartments, and office buildings.

Fanvil i66 Face Recognition Door Phone Technical Specifications

Panel Type

- Multi-apartment

- Community

- Hotel

Screen/Keyboard

- 4-inch 800x480 Colour Screen

- 12 Numeric Keys + 4 Function Keys

Body

- Aluminum

Colors

- Gunmetal

Sensor

- 1/2.8-inch

Camera

- 2 Mpx x 2 (Automatic lighting)

Viewing Angle

- 62deg; (Horizontal)

- 37.4deg; (Vertical)

Fanvil i66 Face Recognition Door Phone

Output video

• H.264 (Baseline, Main Profile)

Light Sensitivity

• 0.1 Lux

• (Infrared/White light fill light)

Card Storage

• 1,0000

Face Storage

• 1,0000

Power Consumption

• PoE: 7.7~19.8W

• Adapter: 6.3~18.5W

Power Supply

• DC 12V / 2A (If not using POE+)

• POE 802.3at Class 4

Working Temperature

• -20~+60°C;

Storage temperature

• -20~+70°C;

Size of the Panel

• 300×115.6×33.2mm

IP / IK Level

• IP66 / IK07

Installation

• Wall-mounted

• Flush-mounted (Need to Purchase Accessories Separately: EX103)

Functional Capabilities

• Supported Protocols: SIP 2.0 over UDP/TCP/TLS

• Lock Opening: Face Recognition, IC/ID Card, PIN Code, QR Code, By DTMF Code, Remote door opening

Fanvil i66 Face Recognition Door Phone

Interface

- Wiegand Input/Output
- Short Circuit Input/Output
- RS485 (Reserve)

Supported Wiegand

- Supported Wiegand 26, 34 bit

Supported ONVIF Types

- Profile S

Supported Standards

- Mifare Classic 1K/4K, Mifare DESFire, Mifare Ultralight, Mifare Plus Cards 13.56 MHz, Cards 125 kHz

Talking Mode

- Full duplex (High-definition Audio)

Additionally

- Built-in relay
- Open API
- Motion detection
- Tamper Alarm (gravity sensing)
- Smart noise reduction

Price: Â£303.50
