

Fanvil i66 Face Recognition Door Phone



Product Name: Fanvil i66 Face Recognition Door Phone

Manufacturer: Fanvil

Model Number: i66

Fanvil i66 Face Recognition Door Phone

The Fanvil i66 Face Recognition Door Phone boasts a 4-inch IPS colour screen and integrates advanced face recognition technology for precise identification. It ensures heightened security with anti-spoofing liveness detection, detecting fake images, videos, and masks effectively.

Fanvil i66 Face Recognition Door Phone Key Features:

- 4-inch IPS colour screen with clear and intuitive interface
- Equipped with the latest face recognition technology and anti-spoofing algorithms, ensuring community security
- Independently developed voice intelligent noise reduction algorithm ensures clearer audio and video calls
- Aluminium alloy casing design, showcasing high-end quality
- Supports the standard ONVIF protocol, providing high flexibility and excellent compatibility
- IP66/IK07 high protection rating, enhancing the lifespan and stability of the product

Moreover, it enables seamless audio and video communication through IP phones, indoor stations, or a mobile app. Offering various door opening options, it is ideal for enhancing security in communities, apartments, and office buildings.

Fanvil i66 Face Recognition Door Phone Technical Specifications

Panel Type

- Multi-apartment
- Community
- Hotel

Screen/Keyboard

- 4-inch 800×480 Colour Screen
- 12 Numeric Keys + 4 Function Keys

Body

- Aluminum

Colors

- Gunmetal

Sensor

- 1/2.8-inch

Camera

- 2 Mpx × 2 (Automatic lighting)

Viewing Angle

- 62° (Horizontal)
- 37.4° (Vertical)

Fanvil i66 Face Recognition Door Phone

Output video

1/2 H.264 (Baseline, Main Profile)

Light Sensitivity

1/2 0.1 Lux

1/2 (Infrared/White light fill light)

Card Storage

1/2 1,0000

Face Storage

1/2 1,0000

Power Consumption

1/2 PoE: 7.7~19.8W

1/2 Adapter: 6.3~18.5W

Power Supply

1/2 DC 12V / 2A (If not using POE+)

1/2 POE 802.3at Class 4

Working Temperature

1/2 -20~+60℃;

Storage temperature

1/2 -20~+70℃;

Size of the Panel

1/2 300×115.6×33.2mm

IP / IK Level

1/2 IP66 / IK07

Installation

1/2 Wall-mounted

1/2 Flush-mounted (Need to Purchase Accessories Separately: EX103)

Functional Capabilities

1/2 Supported Protocols: SIP 2.0 over UDP/TCP/TLS

1/2 Lock Opening: Face Recognition, IC/ID Card, PIN Code, QR Code, By DTMF Code, Remote door opening

Fanvil i66 Face Recognition Door Phone

Interface

- 1/2 Wiegand Input/Output
- 1/2 Short Circuit Input/Output
- 1/2 RS485 (Reserve)

Supported Wiegand

- 1/2 Supported Wiegand 26, 34 bit

Supported ONVIF Types

- 1/2 Profile S

Supported Standards

- 1/2 Mifare Classic 1K/4K, Mifare DESFire, Mifare Ultralight, Mifare Plus Cards 13.56 MHz, Cards 125 kHz

Talking Mode

- 1/2 Full duplex (High-definition Audio)

Additionally

- 1/2 Built-in relay
- 1/2 Open API
- 1/2 Motion detection
- 1/2 Tamper Alarm (gravity sensing)
- 1/2 Smart noise reduction

Please Enquire
