

Fanvil i504 SIP Indoor Station



Product Name: Fanvil i504 SIP Indoor Station

Manufacturer: Fanvil

Model Number: i504

Fanvil i504 SIP Indoor Station

The Fanvil i504 SIP Indoor Station is a 7-inch colour touch screen indoor station featuring 8 alarm inputs and an industrial power socket interface.

Fanvil i504 SIP Indoor Station Key Features:

- 7-inch color capacitive touch screen provides a more convenient user experience
- Built-in 2W speaker and AEC algorithm, it achieves high-quality two-way hands-free calling
- Check real-time video of third-party IP cameras and door phone to ensure security
- Rich interfaces facilitate the integration of various sensors, enabling comprehensive home security monitoring
- Powered by PoE or external source

Designed for use in residential communities, villas, office buildings, and similar environments, it serves to answer calls from the entrance, conduct intercom conversations with the entrance unit, and remotely unlock the entrance unit. Providing dependable security and user-friendly visitor call services, it contributes to establishing a secure and welcoming living environment for diverse users.

Fanvil i504 SIP Indoor Station Technical Specifications

Panel type

- Community
- Hotel
- Villa

Screen

- 7-inch color capacitive touch screen 1024×600

Body

- ABS

Speaker

- 2W

Interface

- 8×Alarm input
- 1×Short circuit output
- 1×Doorbell input
- 1×RS485 (Reserved)

Network

- 10/100 Mbps adaptive

Power Supply

- DC 12V / 1A

Fanvil i504 SIP Indoor Station

i504 PoE 802.3af

Power Consumption

i504 PoE: 3.65~6.64W

i504 Adapter: 2.71~5.53W

Working Temperature

i504 -10~50°C;

Storage Temperature

i504 -40~80°C;

Working Humidity

i504 10%~90%

Size (LWH)

i504 177.38x113.99x22.5mm

Installation

i504 Wall-mounted

Functional Capabilities

i504 Supported Protocols: SIP 2.0 over UDP/TCP/TLS

Audio

i504 Narrowband audio codec: G.711A/U, G.723.1, G.726-16/24/32/40, G.729AB, iLBC

i504 Broadband audio codec: G.722, OPUS

i504 Full-duplex hands-free calling, supports Acoustic Echo Cancellation (AEC)

Video

i504 Hardware video decoding: H.264/H.265 (Optional)

i504 Video call resolution: QVGA / CIF / VGA / 4CIF / 720P / 1080P

DTMF

i504 In-band, out-of-band DTMF (RFC2833), SIP Info

Do Not Disturb (DND)

i504 Supported, and the time can be user-defined

Additionally

i504 Supports viewing video from third-party IP cameras

i504 Supports customizing incoming call ringtones

i504 Supports remote door unlocking

Fanvil i504 SIP Indoor Station

i504 Supports sending/receiving messages

Please Enquire
