

Fanvil i505 Android Indoor Station



Product Name: Fanvil i505 Android Indoor Station

Manufacturer: Fanvil

Model Number: i505

Fanvil i505 Android Indoor Station

The Fanvil i505 Android Indoor Station is a 7-inch touch screen indoor station, boasting a sleek design and user-friendly interface. Powered by Android 9.0, it smoothly integrates with third-party applications.

Fanvil i505 Android Indoor Station Key Features:

- 7-inch colour capacitive touch screen provides a more convenient user experience
- Android 9.0 system ensures stable operation, meeting the customisation needs of industry applications and secondary development
- Built-in 2W speaker and AEC algorithm, it achieves high-quality two-way hands-free calling
- Check real-time video of third-party IP cameras and door phone to ensure security
- Rich interfaces facilitate the integration of various sensors, enabling comprehensive home security monitoring
- Powered by PoE or external source

Equipped with multiple expansion interfaces, it effortlessly links with security devices, enabling functionalities such as two-way intercom, remote door opening, and alarms. Tailored for use in residential communities, villas, office buildings, and similar settings, it enhances safety and convenience, delivering a seamless and secure living experience.

Fanvil i505 Android Indoor Station Technical Specifications

Panel type

- Community
- Hotel
- Villa

Screen

- 7-inch color capacitive touch screen 1024×600

Body

- ABS

Speaker

- 2W

Interface

- 8×Alarm input
- 1×Short circuit output
- 1×Doorbell input
- 1×RS485 (Reserved)

Network

- 10/100 Mbps adaptive

Power Supply

Fanvil i505 Android Indoor Station

i505 DC 12V / 1A

i505 PoE 802.3af

Power Consumption

i505 PoE: 2.83~7.64W

i505 Adapter: 2.46~6.51W

Working Temperature

i505 -10~50°C

Storage Temperature

i505 -40~80°C

Working Humidity

i505 10%~90%

Size (LWH)

i505 177.38x113.99x22.5mm

Installation

i505 Wall-mounted

Functional Capabilities

i505 Supported Protocols: SIP 2.0 over UDP/TCP/TLS

Audio

i505 Narrowband audio codec: G.711A/U, G.729AB, iLBC

i505 Broadband audio codec: G.722, OPUS

i505 Full-duplex hands-free calling, supports Acoustic Echo Cancellation (AEC)

Video

i505 Hardware video decoding: H.264, H.265 (Optional)

i505 Video call resolution: QVGA / CIF / VGA / 4CIF / 720P / 1080P

DTMF

i505 In-band, out-of-band DTMF (RFC2833), SIP Info

Do Not Disturb (DND)

i505 Supported, and the time can be user-defined

Additionally

i505 Supports viewing video from third-party IP cameras

Fanvil i505 Android Indoor Station

- ï¿½ Supports customising incoming call ringtones
- ï¿½ Supports remote door unlocking
- ï¿½ Supports sending/receiving messages
- ï¿½ Supports the installation of third-party app

Please Enquire
