

Fanvil i506W SIP Indoor Station



Product Name: Fanvil i506W SIP Indoor Station

Manufacturer: Fanvil Model Number: i506W

Fanvil i506W SIP Indoor Station

The Fanvil i506W SIP Indoor Station is a 10.1-inch colour touch screen indoor station featuring 8 alarm inputs and an industrial power socket interface. Designed primarily for residential communities, villas, office buildings, and similar environments, it functions to handle calls from the entrance, engage in intercom conversations with the entrance unit, and remotely unlock the entrance.

Fanvil i506W SIP Indoor Station Key Features:

าั¿½ 10.1-inch colour capacitive touch screen provides a more convenient user experience

ī¿½ Built-in 2W speaker and AEC algorithm, it achieves high-quality two-way hands-free calling

ī¿1/2 Check real-time video of third-party IP cameras and door phone to ensure security

រី¿½ Rich interfaces facilitate the integration of various sensors, enabling comprehensive home security monitoring

� Powered by PoE or external source

Providing dependable security and user-friendly visitor call services, it contributes to establishing a secure and comfortable living environment for a diverse range of users.

Fanvil i506W SIP Indoor Station Technical Specifications

Panel type

ï¿⅓ Community

ï¿⅓ Hotel

۲ز½ Villa

Screen

าั¿½ 10.1-inch color capacitive touch screen (IPS) 1280×800

Body

ABS

Speaker

%¿⅓ 2W

Wi-Fi

� 2.4G/5G

Interface

ï¿1/2 8×Alarm input

� 1×Short circuit output

� 1×Doorbell input

ï¿1/2 1×RS485 (Reserved)

Network

� 10/100 Mbps adaptive



Fanvil i506W SIP Indoor Station

Power Supply

� DC 12V / 1A � PoE 802.3af

Power Consumption

� PoE: 2.6~6.6W � Adapter: 1.98~5.5W

Working Temperature

� -10℃~50℃

Storage Temperature

� -40℃~80℃

Working Humidity

� 10%~90%

Size (LWH)

� 247.96x156.96x25.6mm

Installation

ï¿⅓ Wall-mounted

Functional Capabilities

า๊¿1/2 Supported Protocols: SIP 2.0 over UDP/TCP/TLS

Audio

Ϊ¿½ Narrowband audio codec: G.711A/U, G.723.1, G.726-16/24/32/40, G.729AB, iLBC

ï¿1/2 Broadband audio codec: G.722, OPUS

ī¿½ Full-duplex hands-free calling, supports Acoustic Echo Cancellation (AEC)

Video

تز½ Hardware video decoding: H.264, H.265 (Optional)

آذِر Video call resolution: QVGA / CIF / VGA / 4CIF / 720P / 1080P

DTMF

آذِر In-band, out-of-band DTMF (RFC2833), SIP Info

Do Not Disturb (DND)

� Supported, and the time can be user-defined

Additionally



Fanvil i506W SIP Indoor Station

- ï¿⅓ Supports viewing video from third-party IP cameras
- � Supports customizing incoming call ringtones
- ï¿1/2 Supports remote door unlocking
- ï¿⅓ Supports sending/receiving messages

Please Enquire