

## Fanvil A308i Android Console IP Phone



Product Name: Fanvil A308i Android Console IP Phone

Manufacturer: Fanvil

Model Number: A308i

### Fanvil A308i Android Console IP Phone

The Fanvil A308i Android Console IP Phone is an advanced Android console IP phone that seamlessly integrates audio and video applications, making it a versatile communication tool. Operating on Android 9.0, the A308i supports the installation of third-party applications, expanding its functionality and adaptability. Its intelligent speech algorithm, combined with a gooseneck microphone, ensures crystal-clear full-duplex voice calls with a maximum volume of 90dB, catering to diverse communication environments. Additionally, the built-in 5-megapixel adjustable camera delivers high-definition video, enhancing the quality of audio and video calls.

#### Fanvil A308i Android Console IP Phone Key Features

- ½ 20 SIP lines, 10-party audio conference, 3-party video conference
- ½ Equipped with a gooseneck microphone for precise voice pickup
- ½ Supports full duplex calls, with a maximum volume of up to 90 dB
- ½ Built-in adjustable 5 mega-pixel camera
- ½ Support HD audio with G.722 and Opus
- ½ Support video codec H.264, providing premium HD video calls
- ½ Built-in Fanvil broadcast & intercom system
- ½ 116 DSS keys on 7-inch touch screen
- ½ Dual-purpose bracket, support desktop and wall-mounted installation
- ½ Built-in 2.4G/5G Wi-Fi
- ½ Dual Gigabit ports, Integrated PoE

The A308i is designed with flexibility in mind, featuring a versatile bracket that supports both desktop and wall-mounted installations. This adaptability makes it suitable for various setup requirements, whether in an office, a conference room, or other professional settings. The combination of its robust hardware and the ability to customize through third-party apps positions the A308i as a comprehensive solution for modern communication needs.

#### Fanvil A32i - Technical Specifications

##### Generic

- ½ 20 SIP Lines
- ½ Gooseneck microphone
- ½ Full duplex call
- ½ HD Video Call
- ½ 10-party audio conference, 3-party video conference
- ½ Handset / Hands-free / Headset mode
- ½ 7-inch (1024x600) color touch screen
- ½ 116 Intelligent DSS Keys (Programmable)
- ½ Desktop and wall-mounted installation supported
- ½ Dual Gigabit ports, PoE power supply supported
- ½ 2.4G/5G dual band Wi-Fi

##### Operation System

- ½ 3-party applications supported
- ½ API for secondary development
- ½ Android 9.0 OS with higher security and better compatibility
- ½ Built-in applications: Files, Calendar, Gallery, Browser, Email, Calculator, Notepad, Sound Recorder, Clock, Video, Music

## Fanvil A308i Android Console IP Phone

### Phone Features

- Local phonebook (2000 entries)
- Remote phonebook (XML/LDAP, 2000 entries)
- Intelligent search for contacts and call log
- Call logs (In/out/missed, 1000 entries)
- Blocked/Allowed List
- Screen saver
- Voice message waiting indication (VMWI)
- Programmable DSS/Soft keys
- Network time synchronization
- Built-in dual band Wi-Fi
  - 2.4GHz
  - 5GHz

- Action URL / Active URI
- UaCSTA
- Audio/Video recording
- SIP Hotspot
- Multicast
- Action plan
- Listening

### Call Features

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (On server)
- 10-party audio conference, 3-party video conference
- Hot Line
- Hot desking
- BLF

### Video

- Video decoding: H.264, H.265 (optional)
- Video call resolution: CIF/VGA/4CIF/720P/1080P
- Image format: JPEG/PNG/BMP
- Video format: MP4
- Bandwidth selection: 64kbps~4Mbps
- Frame rate selection: 5~30fps

## Fanvil A308i Android Console IP Phone

- Video from remote site can be displayed in full screen
- Video call
- Video Preview
- Camera: 5 mega-pixel (Adjustable Angle)

### Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.729AB, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band & DTMF-Relay (RFC2833) / SIP INFO

### Network

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4
- IP Configuration: Static / DHCP
- Network Access Control: 802.1x
- VPN: OpenVPN (Requires third-party app support)
- VLAN
- LLDP
- CDP
- QoS

### Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- CDP
- LLDP
- 802.1x
- OpenVPN (Requires third-party app support)
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

### Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIPPNP/TR-069
- Web Management Portal
- Supports Web, Telnet
- Supports encrypted configuration files download with AES
- Supports Web upgrade
- Supports factory reset data

### Physical Specifications

## Fanvil A308i Android Console IP Phone

• Color: Grey  
• LCD x1: 7-inch (1024x600) color touch screen  
• Physical keys x5: Volume -/Volume +/Home/Hands-free/Return  
• HD Handset (RJ9) x1  
• Standard RJ9 Handset Wire x1  
• 1.5M CAT5 Ethernet Cable x1  
• Installation bracket x1  
• RJ9 Port x2: Connect with Handset, Headset  
• RJ45 Port x2: Network x1, PC x1 (Bridged to Network)  
• USB2.0: Type A x1, connect with USB card  
• Safety Keyhole x1  
• Power: 12V/1A or PoE  
• Power Consumption (PoE): 3.52~ 10.76W  
• Power Consumption (Adapter): 2.38~8.6W  
• Working Temperature: 0~45°C  
• Working Humidity: 10~95%  
• Installation: Desktop, Wall-mounted  
• Device Dimensions:  
    • Desktop Stand (45°): 265 x 172.1 x 145.2mm  
    • Desktop Stand (50°): 265 x 161.7 x 154.5mm  
  
• Gift Box Dimensions: 337 x 218 x 81mm  
• Outer CTN Dimensions: 456 x 430 x 357mm (10 PCS)

**Price: 289.71EUR**