



Product Name: Yealink P20 4K Ultra HD Presentation Assistant (PA20)

Manufacturer: Yealink Model Number: PA20

Yealink P20 4K Ultra HD Presentation Assistant (PA20)

The Yealink PA20 is a new 4K Ultra HD presentation assistant. Empowered with up to 4K/30FPS UHD hardware encode streaming output, PA20 saves a lot of effort by eliminating any software or driver installation. A USB Type-A/ full-featured USB Type-C port is suitable for different computers and phones. Since PA20 has the embedded meeting assistant software and Wi-Fi 6 chip, simply plug PA20 into the devices, and you can quickly be ready to present. PA20 provides you with a more convenient and richer content sharing experience.

Key Features and Benefits

تز½ Self-built Wi-Fi Network

ï¿1/2 4K/30fps Full HD Content Sharing

ï¿1/2 Adaptive Software/Hardware Encoding

� Dual-band 2.4GHz/5GHz wireless networks

آزِيً Plug and Play

� AES & amp; WPA Data Encryption

� Up to four content streams can be presented simultaneously

4K HD Presentation, Low Latency

Thanks to the high-performance 2x2 MIMO, Wi-Fi 6 module, PA20 delivers immediate response and a smooth and trouble-free presenting experience with low latency. PA20 supports a 2.4GHz/5GHz dual-band wireless network, perfect anti-interference capability, and up to 4K/30fps ultra HD presentation.

No Extra Driver, Plug-and-play

PA20 is suitable for devices that support free collaboration and have a full-featured USB Type-C port. PA20 adopts the built-in hardware encoding chip solution. No need to install any software or driver, and no CPU occupied.

Yealink P20 4K Ultra HD Presentation Assistant - Technical Specifications Basic

� Decoder: Up to 4k/30fps � Input Power: 5V/600 mA

تز1/2 Power Consumption: 2.2 W (Typical)

ï¿⅓ Interface:

Full-featured USB Type-C ×1

USB-C to USB-A Adapter x1

ï¿1/2 Button: START/STOP Button x 1

LED ½'¿ï

4K/UHD Indicator × 1

System Error Indicator × 1



System Status Indicator × 1
Wi-Fi
� Standard: 802.11 b/g/a/n/ac/ax � Frequency:
2400-2483.5MHz
5150-5250MHz
5250-5350MHz
5470-5725MHz
5725-5850MHz
� Security: WPA-PSK/WPA2-PSK
Device Compatibility
ï¿⅓ Operation System:
- Windows 7/8/10/11
- Mac OS 10.10 or later
Advanced Features
� IP-BYOD* � Desktop Sharing:
- Duplicated Desktop
- Extended Desktop
ï¿⅓ Collaboration:
- Annotation

- Intuitive Remote Control



- Multiple Screens Share (MeetingBoard/RoomCast)

Operating Environmental

� Temperature range: -10 - 40℃ � Humidity range: 0 - 90%, non-condensing

Dimensions

 $i \frac{1}{2}$ Weight (g/lb): 75 g (0.165 lb) $i \frac{1}{2}$ Size (mm/in): 220 mm × 38 mm × 16 mm (8.66″ x 1.50″ × 0.63″)

LED Status

LED LED Indicator Description

4K/UHD Indicator Solid green The hard-coded content sharing resolution reaches 4K.

System Error Indicator Solid red Fail to connect to the endpoint.

System Status Indicator
Flash green slowly
The connection has been completed, and is waiting for content sharing.

System Status Indicator Solid green Sharing content.

System Status Indicator Solid orange Updating/Pairing.



Price: £155.00