

Product Name: Snom HD331 Hotel/Hospitality Phone (HD331) Manufacturer: Snom Model Number: HD331

Snom HD331 Hotel/Hospitality Phone

The Snom HD331 is a hotel and guest room phone with a modern design that has been specially developed to meet high demands. Its cordless DECT handset ensures maximum freedom of movement, while the elegant, slim design fits perfectly into any ambience.

Snom HD331 Key Features

- ï¿1/2 Antibacterial housing
- ï¿1/2 Hospitality functions
- ï¿1/2 Individually customisable handset Sticker
- ï¿1⁄2 Wireless DECT handset
- � PoE power supply (exclusive)

Functionality and convenience for hotel guests

i¿1/2 Optimized operation: Speed dial keys allow direct access to hotel facilities such as reception, room service or wellness area.

 $i \ell 2$  Handsfree & amp; call control: Functions such as hands-free, hold and mute offer a comfortable user experience.

 $i_{\dot{c}}$ <sup>1</sup>/<sub>2</sub> Expandable: If required, up to three additional DECT handsets (Snom HD3) can be paired - ideal for larger suites or business rooms.

Technology & amp; future-proofing

i¿1/2 Central administration: All device settings can be managed efficiently and centrally, minimizing administrative effort.

Hygiene & amp; security

 $i_{\dot{c}}$ <sup>1</sup>/<sub>2</sub> Antibacterial housing: Reduces bacterial formation and makes cleaning easier - for the highest hygiene standards in hotel operations.

 $i_{\xi}$ <sup>1</sup>/<sub>2</sub> Visual call display: The large LED call and message display ensures clear visual communication and increases guest comfort.

ïزائ Individual labeling options: Perfectly adaptable to the specific requirements of your hotel.

The Snom HD331 combines modern design, intuitive operation and innovative technology - the perfect solution for hotels that value convenience, efficiency and future-proofing. \*Handset label not included

Snom HD331 Technical Specifications Basics and Equipment

i¿1/2 Product Information



i¿¼ Guest Room Phone (WLAN) | Corded Handset i¿¼ PN 00007008 i¿¼ Colour: Gunmetal Black

ï¿1/2 Equipment

� Anti-bacterial Housing
 � Sturdy, Solid Construction
 � Fully Customizable Faceplate for Hotel Branding and Dialing Instructions

ï¿1/2 Placement: Indoor, Desktop, Nightstand, Wall Mounting

**Dimensions and Weight** 

ï¿1/2 Dimensions (H x W x D, Approx.)

ï¿1/2 Corded handset (on the base cradle, desk mounted): 182 mm × 53 mm × 146 mm

ï¿1/2 Corded handset (on the base cradle, wall mounted): 216 mm × 53 mm × 56 mm

ï¿1/2 Weight (Approx.)

ï¿1/2 Corded handset (on the base cradle): 400 g

Indicators and Keys

ï¿1/2 Telephone Base: 3 LED Indicators

� Call status indication|Message waiting indication (MWI): 1 red LED � Mute Status Indication: 1 Red LED

ï¿<sup>1</sup>/<sub>2</sub> Speakerphone Mode: 1 Red LED

ĩ¿½ Corded handset: 20 hard keys in total
ĩ¿½ 12 keys (standard ITU telephone keypad)
ĩ¿¼ 4 dedicated audio keys

i¿½ Mute (with red LED) i¿½ Speakerphone mode (with red LED) i¿½ VOL+ → Volume + i¿½ VOL- → Volume -

i¿½ 1 dedicated function key: Messagei¿½ 3 programmable function keys: Speed dialling

Audio Devices and Features

ï¿1/2 Corded Handset



� Microphone

ï¿1/2 Handset Earpiece

ï¿1/2 Hearing Aid Compatible (HAC)

ï¿1/2 Built-in Assignable Ringtones

Interfaces and Connections

ï¿1/2 Power Options

ï¿1/2 Power over Ethernet (PoE)

ï¿1/2 IEEE 802.3at, Class 2

#### ï¿1/2 Wired Interfaces

ï¿1/2 Telephone base

ïزئ Network connectivity: RJ45-8P8C socket → Gigabit Ethernet (GbE) ïزئ Handset cord: custom socket

ï¿1/2 Corded handset

ï¿1/2 Handset cord: custom socket

ï¿1/2 Wireless Interfaces

ï¿1/2 Network Connectivity: Wireless LAN

Interoperability

ï¿1/2 Interoperable with all major IP-PBX platforms

Administration interfaces and setup

ïزئ Configuration and setup via voice menu ïزئ Advanced SIP configuration tool for easy mass deployment and phone monitoring

Networking Technologies and Protocols

ï¿1/2 VLAN Support: SIP (RFC 3261)

Call Features



� 1 SIP Identity / Account
 � Mute Microphone (via Dedicated Function Key)
 � Speed Dialling via Function Keys
 � Multicast Paging

Environmental Conditions

ïزئ Operating Ambient Temperature: 5 °C - 45 °C ïزئ Humidity (Non-Condensing): 5% - 95%

Package Contents

� Hardware

� Telephone Base � Handset � Handset cord: 330 mm � Footstand � Wall Mount Kit � 2 Ethernet Cables:

ï¿1/2 Cable Length (Approx.): 140 mm | 2 m

ï¿1/2 Documentation

ï¿1/2 Quick Installation Guide (QIG)

Snom Accessories and Compatible Devices

ï¿1/2 PoE injector: A5 (PN 00004065)

### **Please Enquire**