

## Snom HD30L Lobby Telephone (HD30L)



Product Name: Snom HD30L Lobby Telephone (HD30L)

Manufacturer: Snom

Model Number: HD30L

Snom HD30L Lobby Telephone (HD30L)

Elegant, corded SIP lobby phone

The Snom HD30L is a modern hotel lobby phone with a clear and slim design. It has no keypad and starts automatic dialling to a specified destination when the handset is lifted. This means that dialling is impossible. With the Snom lobby phone, you can ensure a smooth, intuitive user experience in any hotel lobby, waiting area or corridor. The antibacterial housing protects against germs and is easy to clean. Thanks to the inlay on the receiver shell, the H30L is easy to customise. Table or wall mounting possible. Three additional programmable buttons provide additional functions if required.

DSGVO by Design - The Snom HD30L also sets standards in terms of data protection and security. It was developed in accordance with GDPR requirements and does not store any personal data such as dialled phone numbers. Remote setup and maintenance are carried out exclusively via servers in Germany, ensuring the highest security standards.

### Snom HD30L Key Features

- Antibacterial housing
- Hospitality features
- Customisable faceplate
- Power over Ethernet (only)

### Snom HD30L Technical Specifications

#### Basics

#### • Product Information

- Lobby phone | Corded handset | PN 00007019
- Colour: gunmetal black

#### • Equipment

- Anti-bacterial housing
- Sturdy, solid construction
- Fully customisable faceplate for hotel branding and dialing instructions

#### • Placement: indoor, desktop, nightstand, wall mounting

#### Dimensions and Weight

#### • Dimensions (H x W x D, Approx.)

• Corded handset (on the base cradle, desk mounted): 182 mm &times; 53 mm &times; 146 mm

• Corded handset (on the base cradle, wall mounted): 216 mm &times; 53 mm &times; 56 mm

#### • Weight (Approx.)

## Snom HD30L Lobby Telephone (HD30L)

• Corded handset (on the base cradle): 400 g

### Indicators and Keys

• Corded handset: 2 LED indicators

• Mute status indication: 1 red LED

• Speakerphone mode: 1 red LED

• Corded handset: 4 dedicated audio keys

• Mute (with red LED)

• Speakerphone (with red LED)

• Volume +

• Volume -

### Audio Devices and Features

• Corded handset

• Microphone

• Handset earpiece

• External speaker

• Hearing aid compatible (HAC)

• Built-in assignable ringtones

### Interfaces and Connections

• Power Options

• Power over Ethernet (PoE)

• IEEE 802.3af, class 2

• Wired Interfaces

• Telephone base

• Network connectivity: RJ45-8P8C socket & Gigabit Ethernet (GbE)

• Handset cord: custom socket

## Snom HD30L Lobby Telephone (HD30L)

• Corded handset

• Handset cord: custom socket

### Interoperability

• Interoperable with all major IP-PBX platforms

### Administration interfaces and setup

• Configuration and setup via voice menu

• Configuration and setup via menu-driven web user interface (WUI)

• Advanced SIP configuration tool for easy mass deployment and phone monitoring

• Secure Redirection And Provisioning Service (SRAPS) support

### Networking technologies and protocols

• VLAN support

• SIP (RFC 3261)

### Call features

• 1 SIP identity / account

• Speed dialling via function keys

• Mute microphone (via dedicated function key)

• Multicast paging

### Environmental conditions

• Operating ambient temperature:

• 5 °C - +45 °C

• Humidity (non-condensing)

• 5 % - 95 %

### Package contents

• Hardware

• Telephone base

• Handset

• Handset cord: 330 mm

• Footstand

• Wall mount kit

• 2 Ethernet cables: Cable length (approx.) 125 mm | 2 m

• Documentation

## Snom HD30L Lobby Telephone (HD30L)

1½ Quick Installation Guide

Snom accessories and compatible devices

1½ PoE injector: A5 (PN 00004065)

**Please Enquire**

---