



Product Name: Snom HM2 DECT Hospitality Handset (HM2)

Manufacturer: Snom Model Number: HM2

Snom HM2 DECT Hospitality Handset

With the Snom HM2 you can expand your Snom HM201 with up to four additional cordless handsets and thus offer your guests all the benefits in a larger space, as you can make calls in up to five locations/rooms. In addition to their own charging cradle, all handsets have an elegant design and a large, clear colour display that your guests will find easy to navigate. It also has an antibacterial housing to protect against germs and is therefore easy to clean. This model can be customised via the display

Snom HM2 Key Features

าั¿½ Cordless DECT handset for extending the Snom HM201

� Antibacterial housing

� Large 2.8' colour display

� Programmable service key list

ï¿⅓ Hearing aid compatible

� Colour: Black

Snom HM2 Technical Specifications:

Basics

ï¿.½ Product information

� DECT handset|charging cradle|PN 00007007

� Colour: gunmetal black

� Placement

� indoor, desktop, nightstand

ï¿1/2 Sturdy, solid construction

� Ultra small footprint and compact design

� Anti-bacterial housing

ï¿1/2 Availability:

าั¿½ Bundle HM201 (HM2 DECT handset|HM201 Base station), EU & DK, PN 00007006

Dimensions and weight

آز½ Dimensions (L × W × H, approx.)

آذِ Handset: 180 mm × 50 mm × 15 mm

i¿1/2 Charging cradle: 32 mm × 50 mm × 63 mm

آذِرًا Handset (on the charging cradle): 190 mm × 50 mm × 63 mm

� Weight (approx.)



ï¿1/2 Handset: 147 g

ï¿1/2 Charging cradle: 215 g

ï¿1/2 Handset (on the charging cradle): 357 g

Display

īస్ట్ TFT liquid crystal display (LCD), true colour, extra slim, backlit

� Size (diagonal): 2.8″ (71 mm)

Keypad and function keys

ïزن 24 hard keys in total

า๊¿1/2 12 keys (standard ITU telephone keypad), backlit

ï¿⅓ 3 context-sensitive function keys

ï¿1/2 4 dedicated audio keys

ï¿⅓ Mute

ï¿⅓ Speakerphone

� Volume +

ï¿⅓ Volume -

ï¿1/2 5 dedicated function keys

ï¿⅓ Onhook

ï¿⅓ Offhook

ï¿⅓ Message

ï¿⅓ Front desk

� Emergency

Audio devices and features

ï¿⅓ Microphone | Casing speaker

ï¿1/2 Hearing aid compatible (HAC)

Interfaces and connections

ï¿1/2 Power options

� Handset: Battery lithium-ion 3.7 V, 1,000 mAh,preinstalled, removable, rechargeable, up to 7 h talk time, up to 120 h standby time, up to 11 h charging time

� Charging cradle: Power adapter 1 100 - 240 V (AC), 50 - 60 Hz, 150 mA | 6 V, 450 mA, 2.7 W

ï¿⅓ Wired interfaces



ï¿1/2 Charging cradle: custom socket

� Power adapter: cable with custom plug

ï¿⅓ Wireless interfaces

� DECT

DECT technology and features

ï¿1/2 Standard: DECT

� Authentication/encryption of base and handset

آز½ Wideband audio

� Frequency band

ï¿1/2 EU & UK: 1,881.792 - 1,897.344 MHz

User interfaces and setup

� Comfortable and intuitive menu structure

تزير Real time clock, room number, and guest name programming available

� Low battery indication

ï¿1/2 Remote maintenance

Call features

ī¿½ Quick call answer (by simple pick-up from the base/charger)

� Speed dialling: up to 10 (scrolling list on the display)

� Mute microphone (via dedicated function key)

تزن Speakerphone mode (via dedicated function key)

Environmental conditions

� Operating ambient temperature

� 0 °C - +40 °C

� Humidity (non-condensing)

� 5 % - 95 %

Package contents

ï¿⅓ Hardware



ï¿1/2 DECT handset HM2

ï¿⅓ Battery

� Charging cradle

� Power adapter

ï¿⅓ Documentation

� Quick Installation Guide (QIG)

Snom accessories and compatible devices

� Power adapter: Charging cradle PSU

� EU: PN 00004697 � UK: PN 00004698 � AU: PN 00004699

ï¿1/2 Battery HM2 (PN 00004627)

Please Enquire