

Snom HM2 DECT Hospitality Handset (HM2)



Product Name: Snom HM2 DECT Hospitality Handset (HM2)

Manufacturer: Snom

Model Number: HM2

Snom HM2 DECT Hospitality Handset

With the Snom HM2 you can expand your Snom HM201 with up to four additional cordless handsets and thus offer your guests all the benefits in a larger space, as you can make calls in up to five locations/rooms. In addition to their own charging cradle, all handsets have an elegant design and a large, clear colour display that your guests will find easy to navigate. It also has an antibacterial housing to protect against germs and is therefore easy to clean. This model can be customised via the display

Snom HM2 Key Features

- ½ Cordless DECT handset for extending the Snom HM201
- ½ Antibacterial housing
- ½ Large 2.8" colour display
- ½ Programmable service key list
- ½ Hearing aid compatible
- ½ Colour: Black

Snom HM2 Technical Specifications:

Basics

Product information

- ½ DECT handset|charging cradle|PN 00007007
- ½ Colour: gunmetal black

Placement

- ½ indoor, desktop, nightstand
- ½ Sturdy, solid construction
- ½ Ultra small footprint and compact design
- ½ Anti-bacterial housing

Availability:

- ½ Bundle HM201 (HM2 DECT handset|HM201 Base station), EU & UK, PN 00007006

Dimensions and weight

Dimensions (L × W × H, approx.)

- ½ Handset: 180 mm × 50 mm × 15 mm
- ½ Charging cradle: 32 mm × 50 mm × 63 mm
- ½ Handset (on the charging cradle): 190 mm × 50 mm × 63 mm

Weight (approx.)

Snom HM2 DECT Hospitality Handset (HM2)

• Handset: 147 g
• Charging cradle: 215 g
• Handset (on the charging cradle): 357 g

Display

• TFT liquid crystal display (LCD), true colour, extra slim, backlit
• Size (diagonal): 2.8" (71 mm)

Keypad and function keys

• 24 hard keys in total

• 12 keys (standard ITU telephone keypad), backlit
• 3 context-sensitive function keys
• 4 dedicated audio keys

• Mute
• Speakerphone
• Volume +
• Volume -

• 5 dedicated function keys

• Onhook
• Offhook
• Message
• Front desk
• Emergency

Audio devices and features

• Microphone | Casing speaker
• Hearing aid compatible (HAC)

Interfaces and connections

• Power options

• Handset: Battery lithium-ion 3.7 V, 1,000 mAh, preinstalled, removable, rechargeable, up to 7 h talk time, up to 120 h standby time, up to 11 h charging time
• Charging cradle: Power adapter 100 - 240 V (AC), 50 - 60 Hz, 150 mA | 6 V, 450 mA, 2.7 W

• Wired interfaces

Snom HM2 DECT Hospitality Handset (HM2)

• Charging cradle: custom socket
• Power adapter: cable with custom plug

• Wireless interfaces

• DECT

DECT technology and features

• Standard: DECT

• Authentication/encryption of base and handset
• Wideband audio

• Frequency band

• EU & UK: 1,881.792 - 1,897.344 MHz

User interfaces and setup

• Comfortable and intuitive menu structure
• Real time clock, room number, and guest name programming available
• Low battery indication
• Remote maintenance

Call features

• Quick call answer (by simple pick-up from the base/charger)
• Speed dialling: up to 10 (scrolling list on the display)
• Mute microphone (via dedicated function key)
• Speakerphone mode (via dedicated function key)

Environmental conditions

• Operating ambient temperature

• 0 °C - +40 °C

• Humidity (non-condensing)

• 5 % - 95 %

Package contents

• Hardware

Snom HM2 DECT Hospitality Handset (HM2)

• DECT handset HM2

• Battery

• Charging cradle

• Power adapter

• Documentation

• Quick Installation Guide (QIG)

Snom accessories and compatible devices

• Power adapter: Charging cradle PSU

• EU: PN 00004697

• UK: PN 00004698

• AU: PN 00004699

• Battery HM2 (PN 00004627)

Please Enquire
