



Product Name: Snom HD351A Analogue Guest Room Phone (HD351A) Manufacturer: Snom Model Number: HD351A

Snom HD351A Analogue Guest Room Phone (HD351A)

Elegant analogue room telephone with wireless DECT handset for the hotel and accommodation sector

The Snom HD351A is a cleverly designed, cordless DECT analogue telephone that has been specially developed for the requirements of the hotel and accommodation sector. It not only impresses with its elegant design, but also with its high level of functionality and user-friendliness. A particular highlight is the antibacterial housing, which offers effective protection against germs and therefore fulfils the high hygiene requirements of everyday hotel life. The phone's highly visible LED ensures that guests are easily alerted to incoming calls or waiting messages, which significantly increases the comfort and satisfaction of your guests. Another advantage of the Snom HD351A is the possibility of customisation. The phone can be fitted with an individual inlay on the bottom shell, which can be easily exchanged for a personalised touch. The phone can also be flexibly mounted on the wall or used as a desktop device to fit seamlessly into any room concept.

GDPR-compliant by design: The Snom HD351A also sets standards in terms of data protection and security. It was developed in accordance with the requirements of the GDPR and does not store any personal data such as dialled phone numbers. The Snom HD351A thus combines style, functionality and security and is the ideal choice for modern hotels that want to offer their guests the highest level of comfort and security. Snom HD351A Key Features

ï¿1/2 Analogue (PSTN) device

ï¿1/2 Anti-bacterial housing

ï¿1/2 Hospitality features

ï¿1/2 Customisable faceplate

� Analogue PABX support

i¿½ Cordless DECT Handset

i¿1/2 Extendable with up to 4x HD3 handsets

Snom HD351A Technical Specifications Basics

ï¿1/2 Product Information

ï¿1/2 Analog guest room phone | Cordless DECT handset | PN 00007031 ï¿1/2 Colour: gunmetal black

ï¿1⁄2 Equipment

ï¿1/2 Anti-bacterial housing

ï¿1/2 Sturdy, solid construction

i¿1/2 Cordless DECT handset: Customisable section for colour or hotel branding

i¿½ Telephone base: Fully customisable faceplate for hotel branding and dialing instructions

ï¿1/2 Placement: indoor, desktop, nightstand, wall mounting

Dimensions and Weight



ï¿¹/₂ Dimensions (H x W x D, Approx.)

 $\tilde{\imath}_{\ell} ^{\prime \prime \prime}$ Corded handset (on the base cradle, desk mounted): 109 mm × 146 mm × 182 mm

ï¿1/2 Corded handset (on the base cradle, wall mounted): 109 mm × 56 mm × 216 mm

ï¿1/2 Weight (Approx.)

ï¿1/2 Cordless DECT handset (on the base cradle): 796 g

Keys

 $i_{\lambda} \leq 50$ hard keys in total $i_{\lambda} \leq 10$ Telephone base:

i¿1/2 12 keys (standard ITU telephone keypad) i¿1/2 4 dedicated audio keys

i¿½ Mute (with red LED) i¿½ Speakerphone (with red LED) i¿½ Volume + i¿½ Volume -

ï¿1/2 3 dedicated function keys

� Message � Hold � Emergency

ï¿1/2 8 programmable function keys

ï¿1/2 Speed dialling

ï¿1/2 Cordless DECT handset

ïزئ 12 keys (standard ITU telephone keypad), backlit ïزئ 4 dedicated audio keys:

ï¿⅓ Mute (with red LED)

ï¿1/2 Speakerphone (with red LED)

� Volume +

� Volume -

ï¿1/2 3 programmable function keys



ï¿1/2 Speed dialling

ï¿1/2 4 dedicated function keys

i¿½ Talk (with green LED) i¿½ Off i¿½ Hold i¿½ Message

Indicators

ï¿¹/₂ 9 LED indicators ï¿¹/₂ Telephone base

ï¿1/2 Call status indication | Message waiting indication (MWI): 1 red LED

- ï¿1/2 Mute status indication: 1 red LED
- ï¿1/2 Speakerphone mode: 1 red LED
- ï¿1/2 Charging indication: 1 red LED

ï¿1/2 Cordless DECT handset

- ï¿1/2 Message waiting indication (MWI): 1 red LED
- ï¿1/2 Flash/Talk key indication: 1 green LED
- ï¿1/2 Speakerphone mode: 1 red LED
- $\ddot{\imath}_{{2}}{}^{{1}\!\!{2}}$ Mute status indication: 1 red LED
- $\ddot{\imath}_{{2}}{}^{{1}\!\!{2}}$ Low battery indication: 1 red LED

Interfaces and Connections

ï¿1/2 Power options

- ï¿1/2 Telephone base
- ï¿1/2 Power adapter
- � 100 240 V AC / 50 60 Hz / 500 mA | 5 V DC / 2 A

ï¿1/2 Cordless DECT handset

ï¿1/2 Battery lithium-ion, 3.7 V, 1,000 mAh, removable, rechargeable, up to 7 h talk time, up to 144 h standby time



ï¿1/2 Wired interfaces

� Network connectivity (PABX): RJ11-6P2C socket � Power adapter: coaxial power connector (socket)

ï¿1/2 Wireless interfaces

ï¿1∕2 Handset: DECT

Audio devices and features

ï¿1/2 Telephone base

� Casing microphone � Casing speaker

ï¿1/2 Cordless DECT handset

i¿¼ Microphone i¿¼ Handset earpiece i¿¼ Hearing aid compatible (HAC)

DECT technology and features

ï¿1/2 Standard: DECT

� Handsets: up to 4 total � Wideband audio

ï¿1/2 Frequency band

ï¿¹/₂ EU & UK: 1,881.792 - 1,897.344 MHz

ï¿1/2 Easy registration to compatible base stations

Call features

� Quick call answer (by simple pick-up from the base/charger)

ï¿1/2 Speed dialling via function keys

ï¿¹/₂ Mute microphone (via dedicated function key)

ï¿1/2 Speakerphone mode (via dedicated function key)

ï¿1/2 Hold (via dedicated function key)

Environmental conditions

ï¿1/2 Operating ambient temperature:



� 5 °C - +45 °C

ï¿1/2 Humidity (non-condensing):

� 5 % - 95 %

Package contents

ï¿1∕2 Hardware

� Telephone base
� Cordless DECT handset
� Battery
� Power adapter
� Footstand
� Wall mount kit

ï¿1/2 Documentation

ï¿1/2 Quick Installation Guide

Snom accessories and compatible devices

ï¿1/2 DECT handset & amp; charging cradle

ï¿1/2 Up to 3 × HD3 (PN 00007011)

ïزئ Battery PN 00004627 ïزئ Power adapter: HD351A PSU

ĩ¿½ EU: PN 00007036 ĩ¿½ UK: PN 00007037 ĩ¿½ AU: PN 00007038

Please Enquire