

Fanvil i60K Video Door Phone (i60K)

Product Name: Fanvil i60K Video Door Phone (i60K) Manufacturer: Fanvil Model Number: i60K

Fanvil i60K Video Door Phone (i60K)

The Fanvil i60K is a video door phone with a speed-dial button, a numeric keypad, and an IP65 rating for indoor and outdoor use. It supports various door-opening methods such as password, BLE, IC cards, remote DTMF and indoor switches for streamlined access management and is equipped with a 2 mega-pixel camera for audio and video communication. Compatible with SIP and ONVIF, it integrates with security systems and is ideal for villas, apartments, and communities.

Fanvil i60K Key Features:

ï¿1/2 1 speed-dial button and a numeric keypad

 i_{ℓ} ¹/₂ Equipped with a 2 mega-pixel HDR high-definition camera, it provides clearer imaging i_{ℓ} ¹/₂ IP65 high protection rating with wide temperature rate from -40℃ to 70℃, suitable for harsh outdoor environments

ï¿1/2 Rich interfaces for security device connectivity

تزائر Support the standard ONVIF protocol, providing high flexibility and excellent compatibility

Fanvil i61 - Technical Specifications Device Functions

ï¿1/2 Panel Type: Multi-apartment, Community, Villa

ï¿1/2 Keyboard: 1 speed-dial button and a numeric keypad

� Body: ABS+PC

ï¿1/2 Colors: Panel: black, Housing: Gunmetal

- ï¿1/2 Sensor: 1/2.9-inch,CMOS
- ï¿1/2 Camera: 2 Mpx, Support infrared
- ïزائ Viewing Angle: 140°(FOV) 100°(Horizontal) 57°(Vertical)
- ï¿1/2 Output video: H.264 (Baseline, Main Profile)
- ï¿1/2 Light Sensitivity: 0.1Lux
- ï¿1/2 Card Storage: 1,0000
- � Power Consumption: PoE:1.63~6.93W, Adapter: 1.51~6.16W
- ï¿1/2 Power Supply: DC 12V / 1A, PoE 802.3af Class 3
- ï¿¹/₂ Working Temperature: -40℃~+70℃
- ï¿1/2 Storage temperature: -40℃~+70℃
- ï¿1/2 Size of the Panel: (LWH) 70.7*149.7*30mm
- iz ½ IP / IK Level: IP65
- ï¿1/2 Installation: Wall-mounted, Rain cover

Functional Capabilities

تزئ Supported Protocols: SIP 2.0 over UDP/TCP/TLS

� Lock Opening: IC Card,By DTMF Code,Remote Door Opening, Password,BLE

i¿1/2 Interface: Wiegand Input/Output, Short Circuit Input/Output

ï¿1/2 Supported Wiegand: 26, 34 bit

ï¿1/2 Supported ONVIF Types: Profile S

iز1/2 Supported Standards: DTMF, IC Card, Indoor Switch, BLE/ Cards 13.56 MHz



Fanvil i60K Video Door Phone (i60K)

� Talking Mode: Full duplex (High-definition Audio) � Additionally: Built-in relay,Motion detection,Tamper Alarm,TF Card,Open API

Please Enquire