

# Yealink MVC Series S98 Microsoft Teams Rooms System for ProAV Rooms (MVC S98-C5-004)



Product Name: Yealink MVC Series S98 Microsoft Teams Rooms System for ProAV Rooms (MVC S98-C5-004)

Manufacturer: Yealink

Model Number: MVC S98-C5-004

Yealink MVC Series S98 Microsoft Teams Rooms System for ProAV Rooms (MVC S98-C5-004) Microsoft Teams Rooms System for Extra-Large Meeting Rooms

The Yealink MVC S98-C5U is a cutting-edge solution for Microsoft Teams Rooms, designed to enhance collaboration and is ideal for extra-large-sized meeting spaces. This set includes the new generation mini-PC MCore 4, the largescreen touch panel MTouch Plus, the intelligent four-lens camera SmartVision 80, the audio and video processor AVHub, the gigabit PoE+ switch RCH40 E2, the smart detection sensor RoomSensor, and the BYOD-Extender. Powered by the Intel Ultra5 125H processor, the MCore 4 delivers outstanding data processing capabilities and powerful AI computing power, offering a stable and efficient video conferencing experience. The MVC S98-C5U set comes standard with three SmartVision 80 cameras, which feature an innovative four-lens setup comprising a PTZ camera and three electronic cameras, ensuring comprehensive coverage of each corner of the meeting rooms and clear close-up shots of attendees. When paired with AVHub, users can customize the screen layout and realize Yealink's exclusive multi-camera solution, which can support up to 9 cameras connected at the same time, and realize multi-speaker tracking with voice incentive mechanism functions, adapt to the audio and video conferencing needs of various large and super large meeting rooms, classrooms, and training rooms. Combined with the MVC-BYOD-Extender, simply plug the USB cable into your PC to effortlessly utilize the system's audio and video equipment, transforming your Microsoft Teams meeting room into versatile, multi-functional modes. Additionally, to streamline meeting control, the MTouch Plus features an 11.6-inch touch interface for intuitive device operation. The RoomSensor intelligently detects the occupancy status of the meeting room and simultaneously displays real-time environmental metrics, such as temperature and humidity, on the MTouch Plus interface, delivering intelligent room management solutions. The MVC S98-C5U also supports both wired and wireless screen sharing, enabling participants to share content effortlessly. Meanwhile, the system's simple deployment and remote management capabilities make it easy to install and maintain, reducing setup time and operational complexity. MVC S98-C5U Microsoft Teams Rooms System 1

Yealink MVC S98-C5U Key Features:

- រ៉េ្ឌ Four-lens Camera Captures Every Detail with Exceptional Clarity
- าั¿½ Powerful Intelligent Tracking delivers immersive Meetings
- � Multi-cam solution, Flexible layout
- � Outstanding Data Processing Capability
- 12/2 Real-Time Content Sharing for Enhanced Collaboration
- � Simple Deployment and Easy Use
- � Remote Device Management

Four-lens Camera Captures Every Detail with Exceptional Clarity

The SmartVision 80 is equipped with three electronic cameras and a PTZ camera. The electronic cameras include a panoramic lens and two telephoto lenses, ensuring comprehensive coverage of the meeting room and delivering clear images of every participant. To further enhance clarity, the PTZ camera features 20x optical zoom, maintaining sharp focus even at a distance and providing an exceptional, high-quality visual experience.

Powerful Intelligent Tracking delivers immersive Meetings

The SmartVision 80 enhances the remote meeting experience with a variety of tracking modes, like IntelliFocus, Presenter Tracking, Speaker Tracking, and Auto Framing. When multiple SmartVision 80 units are used together, they expand the shooting range and introduce advanced capabilities, such as Multi-camera Intellifocus, Intelliframe, Microphone, and Camera Linkage.



# Yealink MVC Series S98 Microsoft Teams Rooms System for ProAV Rooms (MVC S98-C5-004)

These features enhance tracking accuracy and coverage, resulting in a more professional and efficient online meeting experience.

Multi-cam solution, Flexible layout

Relying on the audio and video processor AVHub, Yealink has developed a multi-camera solution that supports up to 9 Yealink cameras. Users can control them independently through MTouch Plus or splice the output video of multiple cameras and adjust the output video layout as desired. Various sets of the MVC S98-C5U series can be combined through network cables to build a conference room system that can be flexibly merged and divided.

**Outstanding Data Processing Capability** 

At the core of the MVC S98-C5U is the MCore 4, powered by the Intel Ultra5 125H processor, which boasts exceptional data processing capabilities and powerful AI computing capabilities with its NPU. It ensures smooth and efficient meetings, enabling intelligent conferencing features. The MCore 4 empowers smart meeting rooms, providing a stable and efficient operating environment for immersive remote communication.

Real-Time Content Sharing for Enhanced Collaboration

The bundle supports both wireless and wired content sharing for maximum flexibility. Wireless content sharing is made simple with the Yealink sharing dongle, which supports wireless sharing at 1080p/30fps resolution for a superior viewing experience. Wired content sharing is supported by connecting the MTouch to a USB-C or HDMI port on a laptop using the MTouch cable. Additionally, the MCore 4 is equipped with an HDMI-In interface, supporting 4K resolution auxiliary stream input to ensure lossless image presentation, further enhancing the content sharing experience.

Simple Deployment and Easy Use

A single CAT5e cable is sufficient to connect the MCore 4 and MTouch Plus, enabling both data transmission and power supply without the need for additional cables or power sources. Additionally, the RoomSensor operates via Bluetooth (BLE), eliminating the need for extra cables. Remote Device Management

These devices can support the Yealink Device Management Platform/Cloud Service, enabling remote management, monitoring, configuration, updates, and diagnostics of all connected devices. This feature ensures that your meeting room is always up-to-date and operating at peak performance.

Yealink MVC S98-C5U Technical Specifications Package Content

� MCore 4

ï¿⅓ MTouch Plus

ï¿⅓ RoomSensor

ï¿⅓ SmartVision 80 x 3

آز½ AVHub

ï¿⅓ RCH40 E2

ï¿1/2 BYOD-Extender

#### Preload

� Windows 11 IoT Enterprise X64

ï¿⅓ Windows 11 IoT Enterprise License

� Microsoft Teams Rooms App

� Yealink RoomConnect

MCore 4, Gen-4 Mini-PC

� Processor: Intel Ultra5 125H � Memory: 16GB(2\*8GB) DDR5



# Yealink MVC Series S98 Microsoft Teams Rooms System for ProAV Rooms (MVC S98-C5-004)

# ï¿1/2 BIOS feature:

ï¿1/2 3x HDMI video output -CEC -EDID

� TPM2.0

ï¿1/2 Kernel DMA

ï¿⅓ Interfaces:

� 1 x HDMI-Out 2.1 port

� 2 x HDMI-Out 2.0 port

� 1 x HDMI-In port

� 4 x USB3.0 Type-A Port

� 1 x MTouch Port (RJ-45)

� 1 x LAN port for AV network

� 1 x 10/100/1000 Gigabit Ethernet Port

� 1 x Power Supply Port

� 1 x 3.5mm headphone Port

� 1 x Reset port

� 1 x Security Slot

ï¿1/2 WiFi: IEEE 802.11 a/b/g/n/ac/ax

آذً1/2 Bluetooth: BT 5.2

### MTouch Plus

ï¿1/2 11.6-inch narrow bezel IPS display

� Angle between screen and desktop (30° ~ 70°)

تزير Adjustable angle of support frame (50° ~ 180°)

 $\ddot{i}$  $\frac{1}{2}$  1920 x 1080 video resolution

า๊¿½ Support wired and wireless (with WPP30) content sharing

ī¿½ Support external PD power supply to power the sharing device

ï¿1/2 Support HDMI/USB-C video input

ī¿½ Support desktop placement, desktop fixed, wall-mounted deployment

# RoomSensor

ï¿1/2 Detection angle: 120°

า๊¿1/2 Adjustable detection angle: ±20°

� Operating temperature: 0-40℃

� Operating humidity: 10-95%

### SmartVision 80

� Camera

� PTZ Camera: 20×optical zoom

i¿½ 69° DFOV, 61.5° HFOV, 36° VFOV(PTZ Camera)

آزا 110° DFOV, 98° HFOV, 82° VFOV(Panoramic Camera)

تزير 51° DFOV, 41.6° HFOV, 32° VFOV(Telephoto Camera)



# Yealink MVC Series S98 Microsoft Teams Rooms System for ProAV Rooms (MVC S98-C5-004)

# ï¿⅓ Al Feature:

- ï¿⅓ IntelliFrame
- � Participant Identification
- ï¿⅓ IntelliFocus
- ï¿⅓ Speaker Tracking
- � Presenter Tracking
- ï¿⅓ Video Fence
- PIP ينزï
- آز½ Auto Framing

#### ï¿⅓ Interfaces:

- ï¿1/2 1×USB 3.0 Type-B port
- ï¿1/2 1×USB 2.0 Type-A port
- � 2×VCH port(RJ45)
- � 1×Network Port (RJ45)
- � 1×HDMI out port
- ïز½ 1×Line in port
- ïز½ 1×Line out port
- � 1×Reset Button
- ï¿1/2 1×DC Power Port

# AVHub, audio and video processor

# ï¿⅓ Interfaces:

- � 2 x USB-A port
- ï¿⅓ 1 x USB-B port
- ï¿⅓ 1 x Codec port
- � 7 x Yealink VCH port(RJ-45)
- � 1 x RCA in/out interface
- � 1 x 6.3mm Line in interface
- � 1 x 6.3mm Line out interface
- � 1 x power interface

# ï¿1/2 Function Features:

- 12.1/2 Dividable and merging meeting rooms are supported
- � Support intelligent multi-speaker tracking

#### RCH40 E2

# � Interface&LED:

� 4 x 10/100/1000Mbps Port

� 1 x LED indicates Power state



# Yealink MVC Series S98 Microsoft Teams Rooms System for ProAV Rooms (MVC S98-C5-004)

# � 1 x LED indicates PoE Budget

� Physical Feature:

ï¿1/2 Multiple deployment method

� 90w total PoE Budget(30w per port)

تز1/2 Support standard PoE Supply(802.3af)

� Power adapter: PSE 48V 2A

� Dimension(WDH):100mm x 100mm x 23mm

� Operating Humidity: 5%-90%

# **BYOD-Extender**

ï¿⅓ Interfaces:

� 1.5m USB2.0 Type-A cable � 1 x VCH port (RJ45)

تز½ Physical Feature:

� Operating humidity: 10~95%

 $\ddot{i}$ ¿½ Operating temperature: 0~40℃

ï¿⅓ Dimension:89mm x 48mm x 17mm

# **Please Enquire**