

## Grandsteam Indoor Dual-Band Wi-Fi 7 Access Point (GWN7670)



Product Name: Grandsteam Indoor Dual-Band Wi-Fi 7 Access Point (GWN7670)

Manufacturer: Grandstream Model Number: GWN7670

Grandsteam Indoor Dual-Band Wi-Fi 7 Access Point (GWN7670)

The Grandstream GWN7670 is a new generation enterprise-grade Wi-Fi 7 access point, ideal for small-to-medium-sized businesses to build next-generation Wi-Fi networks. It offers dual-band 2x2:2 MIMO with DL/UL OFDMA technology and a sophisticated antenna design for maximum network throughput and expanded Wi-Fi coverage range. The GWN7670 improves bandwidth utilization and anti-interference ability with multi-RU and Preamble Puncturing technology. With 4096 QAM modulation, Wi-Fi 7 achieves a significant increase in data transfer rates. MLO technology optimizes spectrum resource utilization to ensure a smooth experience for every user. To ensure easy installation and management, the GWN7670 uses a controller-less distributed network management design in which the controller is embedded within the product's Web user interface The GWN7670 is also supported by GDMS Networking and GWN Manager, Grandstream's cloud and on-premise Wi-Fi management platform. It is the ideal Wi-Fi AP for voice-over-Wi-Fi deployments and offers a seamless connection with Grandstream's Wi-Fi capable IP phones. With support for advanced QoS, low-latency realtime applications, mesh networks, captive portals, BT location with BLE 5.3, 256 concurrent clients per AP and 2 x 2.5 Gigabit network ports with PoE+, GWN7670 is an ideal Wi-Fi access point for medium wireless network deployments with medium-to-high user density.

Grandstream GWN7670 Key Features:

- าั¿½ 3.6Gbps aggregate wireless throughput, 5Gbps aggregate wired throughout
- าั¿½ Integrated Wi-Fi 7 & Technology 2x2:2 MIMO with MLO, 4KQAM, MRU, Preamble Puncturing Technology
- � Up to 175-meter coverage range
- � Support 256 concurrent Wi-Fi client devices
- Ti21/2 Advanced QoS to ensure real-time performance of low-latency applications
- ī¿½ Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device
- � Self power adaptation upon auto detection of PoE+
- آذِ½ Embedded controller manages up to 50 local GWN APs; GDMS Networking offers unlimited AP management, & AP management, & P management

## Grandstream GWN7670 Technical Specifications Mechanical

ï¿1/2 Wi-Fi Standards IEEE 802.11 a/b/g/n/ac/ax/be

าั¿½ Antennas: 5 single frequency antennas 2.4GHz x 2, gain 3.5dBi 5GHz x 2, gain 5.5dBi BT qain 3.5dBi

T¿½ Wi-Fi Data Rates: 5G: IEEE 802.11be: Up to 2882 Mbps IEEE 802.11ax: 7.3 Mbps to 2402 Mbps IEEE 802.11ac: 6.5 Mbps to 1732 Mbps IEEE 802.11n: 6.5 Mbps to 600 Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 2.4G: IEEE 802.11be: Up to 688 Mbps IEEE 802.11ax: 7.3 Mbps to 574 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps \*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network

T¿½ Frequency Bands: 2.4GHz Radio: 2400 - 2483.5 MHz 5GHz Radio: 5150 - 5895 MHz\*Not all frequency bands can be used in all regions

� Channel Bandwidth: 2.4G: 20 and 40 MHz 5G: 20, 40, 80, and 160 MHz



## Grandsteam Indoor Dual-Band Wi-Fi 7 Access Point (GWN7670)

ϊ¿½ Wi-Fi and System Security: WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device

� MIMO: 2x2:2 2.4GHz 2x2:2 5GHz

ϊ¿½ Coverage Range: Up to 175 meters \*coverage range can vary based on environment ϊ¿½ Maximum TX Power: 2.4G: 26dBm 5G: 26dBm \*Maximum power varies by country, frequency band and MCS rate

ī¿½ Receiver Sensitivity: 2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz: -70dBm @MCS7; 802.11ax 20MHz: -60dBm @MCS11; 802.11ax 40MHz: -58dBm @MCS11 802.11be 20MHz: -65dBm @MCS11; 802.11be 40MHz: -62dBm @MCS11 5G 802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz: -70dBm @MCS7; 802.11ac 20MHz: -67dBm@MCS8; 802.11ac: 40MHz: -63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9; 802.11ax 20MHz: -60dBm @MCS11; 802.11ax 40MHz: -58dBm @MCS11;802.11ax 80MHz: -56dBm @MCS11;802.11ax 160MHz: -52dBm@ MCS11 802.11be 20MHz: -59dBm @MCS13; 802.11be 40MHz: -56dBm @MCS13; 802.11be 80MHz: -54dBm @MCS13; 802.11be 160MHz: -52dBm @MCS13

آذِرُ SSIDs: 32 SSIDs total, 16 per radio (2.4GHz & amp; 5GHz)

� Concurrent Clients: 256

� Network Interfaces: 2x 2.5G Ethernet WAN/LAN

آذِرُ Auxiliary Ports: 1x Reset Pinhole, 1x Kensington lock

ï¿1/2 Bluetooth®: BLE 5.3

12.1/2 Mounting: Indoor wall mount or ceiling mount, kits included

ī స్ట్రి LEDs: 1 tri-color LED for device tracking and status indication

� Network Protocols: IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM

� QoS: 802.11e/WMM, VLAN, TOS

� Network Management: Embedded controller can manage up to 50 local GWN APs GDMS Networking offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs

� Power and Green Energy Efficiency: PoE/PoE+ 802.3af/at; Maximum Power Consumption: 14.5W

าั¿½ Environmental: Operation: 0°Cto 45°C Storage: -30°C to 60°C Humidity: 10% to 90% Non-condensing

آذِيًّ Physical: Unit Dimension: 185mmx185mmx44.5mm; Unit Weight: 527g Entire Package Dimension: 228.5mmx220mmx79mm; Entire Package Weight: 877g

� Package Content: GWN7670 Wi-Fi 7 Wireless AP, Mounting Kits, Quick Start Guide � Compliance: FCC, CE, RCM, IC

Price: \$112.97