

## Grandstream Indoor Wi-Fi 6E Access Point (GWN7665)



Product Name: Grandstream Indoor Wi-Fi 6E Access Point (GWN7665)

Manufacturer: Grandstream

Model Number: GWN7665

### Grandstream Indoor Wi-Fi 6E Access Point (GWN7665)

The Grandstream GWN7665 is a powerful, enterprise-grade Wi-Fi 6E access point, ideal for small-to-medium sized businesses, multiple floor buildings, residential settings and commercial locations. It offers tri-band 2x2:2 MU-MIMO with DL/UL OFDMA technology and a sophisticated internal antenna design for stronger anti-interference, more stable connection, maximum network throughput and expanded Wi-Fi coverage range. The GWN7665 is supported by GWN.Cloud and GWN Manager, Grandstream's cloud and on-premise Wi-Fi management platform that makes managing your network or several networks across multiple locations easier than ever before. It also uses a controller-less network management architecture in which the controller is embedded within the product's web user interface for easy administration of locally deployed Wi-Fi APs. The GWN7665 is the ideal Wi-Fi AP for voice-over-Wi-Fi deployments and offers a seamless connection with Grandstream's Wi-Fi capable IP phones. With support for advanced QoS, low-latency real-time applications, mesh networks, captive portals, Bluetooth® Low Energy (BLE) 5.2, 384 concurrent clients and dual Gigabit network ports with PoE/PoE+, the GWN7665 is an ideal Wi-Fi access point for business-grade wireless network deployments with medium-to-high user density.

Grandstream GWN7665 Key Features:

- 5.4Gbps aggregate wireless throughput 3.5 Gigabit wireline ports
- Tri-band 2x2:2 MU- MIMO with DL/UL OFDMA technology
- Up to 175-meter coverage range
- Support 384 concurrent Wi-Fi client
- Advanced QoS to ensure real-time performance of low-latency applications
- Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device
- Self power adaptation upon auto detection of PoE or PoE+
- Embedded controller manages up to 50 local GWN APs; GWN.Cloud offers unlimited AP management, & GWN Manager offers on-premise software AP management

### Grandstream GWN7665 Technical Specifications

#### Mechanical

- Wi-Fi Standards: IEEE 802.11 a/b/g/n/ac/ax
- Antennas: 7 single frequency antennas 2.4GHz x 2, gain 4.0dBi 5 GHz x 2, gain 5.0dBi 6 GHz x 2, gain 4.5dBi BT, gain 4.0dBi
- Wi-Fi Data Rates: 2.4G: IEEE 802.11ax: 7.3 Mbps to 573.5 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 5G: IEEE 802.11ax: 7.3 Mbps to 2403 Mbps IEEE 802.11ac: 6.5 Mbps to 1734 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 6G: IEEE 802.11ax: 7.3 Mbps to 2403 Mbps IEEE 802.11ac: 6.5 Mbps to 1734 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps \*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network
- Frequency Bands: 2.4GHz Radio: 2412 - 2484 MHz 5GHz Radio: 5180 - 5825 MHz 6GHz Radio: 5945 -7125MHz \*Not all frequency bands can be used in all regions
- Channel Bandwidth: 2.4G: 20 and 40 MHz 5G: 20, 40, 80, and 160 MHz 6G: 20, 40 80 and 160MHz
- Wi-Fi and System Security: WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/ control lockdown via digital signatures, unique

## Grandstream Indoor Wi-Fi 6E Access Point (GWN7665)

security certificate and random default password per device

• MIMO: 2x2:2 2.4GHz 2x2:2 5GHz

• Coverage Range: Up to 175 meters \*coverage range can vary based on environment

• Maximum TX Power: 2.4G: 26dBm 5G: 26dBm 6G: 26 dBm \*Maximum power varies by country, frequency band and MCS rate

• Receiver Sensitivity: 2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz:-70dBm @MCS7 802.11ax 20MHz: -60dBm @MCS11; 802.11ax 40MHz: -58dBm @MCS11 5G 802.11a: -90dBm @6Mbps, -72dBm @54Mbps; 802.11n 20MHz: -71dBm @MCS7; 802.11n 40MHz:-68dBm @MCS7; 802.11ac 20MHz: -65dBm@MCS8; 802.11ac: 40MHz:- 61dBm @MCS9; 802.11ac 80MHz: -57dBm @MCS9;802.11ac 160MHz: -55dBm @ MCS9; 802.11ax 20MHz: -58dBm @MCS11; 802.11ax 40MHz: -56dBm @MCS11;802.11ax 80MHz: -54dBm @MCS11;802.11ax 160MHz: -51dBm @ MCS11 6G 802.11a: -90dBm @6Mbps, -72dBm @54Mbps; 802.11n 20MHz: -71dBm @MCS7; 802.11n 40MHz:-68dBm @MCS7; 802.11ac 20MHz: -65dBm@MCS8; 802.11ac: 40MHz:- 61dBm @MCS9; 802.11ac 80MHz: -57dBm @MCS9;802.11ac 160MHz: -55dBm @ MCS9; 802.11ax 20MHz: -58dBm @MCS11; 802.11ax 40MHz: -56dBm @MCS11;802.11ax 80MHz: -54dBm @MCS11;802.11ax 160MHz: -51dBm @ MCS11

• SSIDs: 48 SSIDs total, 16 per radio (2.4GHz & 5GHz & 6GHz)

• Concurrent Clients: 384

• Network Interfaces: 1x autosensing 10/100/1000 Base-T Ethernet Port 1x autosensing 10/100/2500 Base-T Ethernet Port

• Auxiliary Ports: 1x Reset Pinhole, 1x Kensington lock

• Bluetooth®: BLE 5.2

• Mounting: Indoor wall mount or ceiling mount, kits included

• LEDs: 3 tri-color LEDs for device tracking and status indication

• Network Protocols: IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM

• QoS: 802.11e/WMM, VLAN, TOS

• Network Management: Embedded controller can manage up to 50 local GWN APs GDMS Networking offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs

• Power and Green Energy Efficiency: PoE/PoE+ 802.3af/at; Maximum Power Consumption: 22.55W

• Environmental: Operation: : 0&deg;Cto 50&deg;C Storage: -10&deg;C to 60&deg;C

Humidity: 10% to 95% Non-condensing

• Physical: Unit Dimension: 205.3mmx205.3mmx45.9mm; Unit Weight: 765g Entire Package Dimension: 258mmx247mmx86mm; Entire Package Weight: 1106g

• Package Content: GWN7665 Wireless AP, Mounting Kits, Quick Start Guide

• Compliance: FCC, CE, RCM, IC,UKCA

**Price: Â£94.80**