

Fanvil VIK-01 Video Intercom Kit (VIK-01)



Product Name: Fanvil VIK-01 Video Intercom Kit (VIK-01)

Manufacturer: Fanvil Model Number: VIK-01

Fanvil VIK-01 Video Intercom Kit (VIK-01)

The Fanvil VIK-01 integrates the i504W SIP Indoor Station, i60 Video Door Phone, and Fanvil Link App, ideal for villas and single-family homes. Users can make HD video calls and remotely unlock doors via the indoor unit or Fanvil Link App, with multiple unlocking options and 2.4G/5G Wi-Fi support. Achieve plug-and-play deployment with simple power and network connections. Fanvil VIK-01 Key Features

- � Plug-and-play, quickly deployment.
- � Flexible door access methods.
- ī¿½ Monitor door phone camera footage on both mobile and indoor station.
- � Remote door opening anytime, anywhere
- � Support one-touch calling.
- � CCTV integration

Fanvil VIK-01 Video Intercom Kit Technical Specifications Overview

าั¿½ Screen: 7-inch color capacitive touch screen 1024×600

� Body: ABS � Speaker: 2W

� Wi-Fi: 2.4G/5G(i504W Supported)

T¿½ Interface: 8× Alarm input, 1× Short circuit output, 1× Doorbell input,

1×RS485(Reserved)

� Network: 10/100 Mbps adaptive � Power Supply: DC 12V / 1A

� Power Consumption: PoE: 3.65~6.64W � Working: -10℃~50℃ � Storage: -40℃~80℃ � Working Humidity: 10%~90% � Size (LWH): 177.38x113.99x22.5mm

ï¿1/2 nstallation: Wall-mounted

Functional Capabilities

าั¿1/2 Supported Protocols: SIP 2.0 over UDP/TCP/TLS

� Audio: Narrowband audio codec: G.711A/U, G.723.1, G.726-16/24/32/40, G.729AB, iLBC, Broadband audio codec: G.722, OPUS, Full-duplex hands-free calling, supports Acoustic Echo Cancellation (AEC)

าั¿½ Video: Hardware video decoding: H.264,H.265 (Optional), Video call resolution: QVGA / CIF / VGA / 4CIF / 720P / 1080P

� DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info

าั¿½ Do Not Disturb (DND): Supported, and the time can be user-defined

T¿½ Additionally: Supports viewing video from third-party IP cameras, Supports customizing incoming call ringtones, Supports remote door unlocking, Supports sending/receiving messages

Fanvil i60 Specifications

ï¿1/2 Keyboard: 1 Speed-dial Button

ï¿⅓ Body: ABS+PC

า๊¿½ Colors: Panel: black, Housing: Gunmetal



Fanvil VIK-01 Video Intercom Kit (VIK-01)

- Title Sensor: 1/2.9-inch,CMOS Title Camera: 2 Mpx, Support infrared
- آزا Viewing Angle: 140°(FOV) 100°(Horizontal) 57°(Vertical)
- آذِيً Output video: H.264 (Baseline, Main Profile)
- � Light Sensitivity: 0.1Lux � Card Storage: 1,0000
- ī¿½ Power Consumption: PoE:1.63~6.93W, Adapter: 1.51~6.16W
- � Power Supply: DC 12V / 1A, PoE 802.3af Class 3 � Working Temperature: -40℃~+70℃ π¿½ Storage temperature: -40℃~+70℃
- ï¿1/2 Size of the Panel: 50*130*30mm
- � IP / IK Level: IP65
- า๊¿1/2 Installation: Wall-mounted Rain cover

Functional Capabilities

- i¿1/2 Supported Protocols: SIP 2.0 over UDP/TCP/TLS
- าั¿½ Lock Opening: IC Card,By DTMF Code,Remote Door Opening, BLE
- า๊ะ่½ Interface: Wiegand Input/Output, Short Circuit Input/Output
- � Supported Wiegand Types: 26, 34 bit
- ï¿1/2 Supported ONVIF Types: Profile S
- آذًا Supported Standards: DTMF, IC Card, Indoor Switch, BLE, Cards 13.56 MHz
- i¿½ Talking Mode: Full duplex (High-definition Audio)
- تزئ Additionally: Built-in relay,Motion detection,Tamper Alarm,TF

Card,Open API

Price: £130.00